INCH-POUND

A-A-54871
17 May 1993

COMMERCIAL ITEM DESCRIPTION

PILLOWCASE

(Nonwoven Fabric, White, Disposable)

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for MIL-P-36215A which is cancelled.

This Commercial Item Description covers a disposable, white, nonwoven pillowcase.

Salient characteristics:

The pillowcase shall be a white disposable pillowcase made of nonwoven material, composed of a wet-laid or air-laid nonwoven fabric. The material shall conform to the following specifications:

Basis weight (24 by 36 inches, 500 sheets), minimum pounds	48.0
Dry tensile breaking strength (Minimum pounds per 15 millimeters width)	
Machine direction	5.0
Cross direction	2.0
Wet tensile breaking strength (Minimum pounds per 15 millimeters width, after 15 plus or minus 3 seconds water immersion)	
Machine direction	1.0
Cross direction	1.0
Bursting strength, Mullen, points	10.0
Tear resistance, minimum grams	
Machine direction	300.0
Cross direction	200.0

AMSC N/A FSC 6532

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:39Z
Check the source to verify that this is the current version before use.

As an alternate, the nonwoven material shall be composed of a spunbonded polypropylene with a nominal basis weight of 1.5 ounces/square yard. The following physical requirements apply to the spunbonded polypropylene:

Weight, oz./sq. yd. minimum	1.47
Breaking strength, lbs. minimum	
Machine direction	23.0
Cross direction	17.0
Flame resistance, seconds minimum (NFPA Test Method 702)	8.0
Colorfastness to water	Good

The pillowcase material shall be tested in accordance with the following methods of the Technical Association of the Pulp and Paper Industry (TAPPI):

Test	Method
Bursting Strength of Paper	T403-ts-63
Tensile Breaking Strength of Paper and Paperboard	T404-ts-66
Basis Weight of Paper and Paperboard	T410-os-61
Internal Tearing Resistance of Paper	T414-ts-65
Wet Tensile Breaking Strength of Paper and Paperboard	T456-m-45
Flammability of Treated Paper and Paperboard	T461-os-68

The pillowcase material shall be such as to result in a finished pillowcase approaching the comfort of the conventional textile pillowcase. No known irritating or toxic elements shall be present in the finished material. The material shall be white in color and shall offer a soft pliable surface which shall be lint free and free from objectionable noises when used by a restless patient. The

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:39Z
Check the source to verify that this is the current version before use.

material shall be free of objectionable odors when wet or dry. Masking agents may be employed to mask objectionable odors with another more pleasant odor providing the odor of the finished pillowcase is faint and in no way objectionable. The material shall be rendered water-resistant and shall be treated to prevent soak-through of blood, perspiration and the other fluids. The material shall be rendered fire-resistant, and, when tested in accordance with TAPPI Method T461-os-68, shall show not more than 5-1/2 inches char in 12 seconds and 3 seconds afterglow. The material shall show an immediate extinguishing of flame when the lighted match is removed.

The pillowcase shall be of the slip-on envelope type, and shall be constructed of one or two pieces of material. The finished overall flat dimensions shall be 31-1/2 inches plus or minus 1/2 inch long, and 20-1/2 inches plus or minus 1/2 inch wide. When constructed from one piece, the material shall be folded so that only the sides shall be joined or folded so that only one side and one end are joined, leaving the opposite end open. When constructed from two pieces of material, one end and the sides shall be superimposed and joined. The seams shall be glued or sewed, and shall be straight and even. Folding, or overlapping, of seams is prohibited.

The seams, if glued, shall adhere securely throughout their entire area, and shall be free from wrinkles. The seams shall be stronger than the adjoining material when separation by hand is attempted. The glued seam width shall be 1/8 to 3/16 inch wide for the side seams, and 1/8 to 1/4 inch wide for the bottom seam. The side seams shall start not more than 1/16 inch from the side edge of the material, and the bottom seam shall start not more than 3/8 inch from the bottom edge of the material. There shall be no excess glue, nor pronounced discoloration, along the seam area. The adhesive used shall be a suitable polyvinyl acetate adhesive.

If the seams are sewed, the stitch type shall conform to an overedge stitch type in the 500 series. There shall be six to ten stitches per inch. The thread shall be white cotton thread, ticket no. 50, 3 ply.

Workmanship. The nonwoven fabric pillowcase shall be free from defects which detract from its appearance or impair its serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Unit. Package (PG). One package containing ten pillow cases, as specified, constitutes one unit.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, with an AQL of 4.0 (percent defective) and an inspection level of II. The unit of product for examination purposes shall be one nonwoven fabric pillowcase.

Sampling for tests. Sampling for tests, including dimensional test, shall be conducted in accordance with MIL-STD-105, with an AQL of 2.5 (percent defective) and an inspection level of S-3. The unit of product for test purposes shall be one nonwoven fabric pillowcase.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:39Z
Check the source to verify that this is the current version before use.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

Ordering data. Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document.

6532-01-125-3269

MILITARY INTERESTS:

Custodians:

Air Force - 03
Army - MD
Navy - MS

PREPARING ACTIVITY:

DoD-MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

FDA-MPQAS
USPHS
VA - OSS

Project Number: 6532-1202

Location: PILL013C.DOC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

1. RECOMMEND A CHANGE:	1. DOCUMENT NUMBER: A-A-54871	2. DOCUMENT DATE (YYMMDD): 17 May 1993

3. DOCUMENT TITLE: PILLOWCASE (Nonwoven Fabric, White, Disposable)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME: DEFENSE PERSONNEL SUPPORT CENTER ATTN: DPSC-MSE	b. TELEPHONE (Include Area Code) (1) Commercial: AC 215-737-2870 (2) AUTOVON: AV 444-2870
c. ADDRESS (Include Zip Code) 2800 SO. 20TH STREET PHILADELPHIA, PA 19145	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 — Previous editions are obsolete. 96/290

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:39Z
Check the source to verify that this is the current version before use.