N-P-361C
May 25, 1973
SUPERSEDING
Fed. Spec. N-P-361B
June 10, 1964

FEDERAL SPECIFICATION

PIE CRUST MIX; PREPARED

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal Agencies.

1. SCOPE

1.1 This specification covers prepared pie crust mix intended as an item of general issue for all Federal agencies.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter

Federal Standard:

FED-STD-123	-	Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC., Atlanta, Chicago, Kansas City, MO., Ft. Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 8920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items.
MIL-L-35078	-	Loads, Unit; Preparation of Nonperishable Subsistence.

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-668	-	Sanitary Standards for Food Plants.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

PUBLICATIONS

Department of Health, Education and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

United States Department of Agriculture

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Information Division, Agricultural Marketing Service, U. S. Department of Agriculture, Washington, DC 20250.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, Post Office Box 540, Benjamin Franklin Station, Washington, DC 20044.)

American Oil Chemists Society

Official and Tentative Methods of the American Oil Chemists' Society

(Application for copies should be addressed to the American Oil Chemists Society, 508 South Sixth Street, Champaign, IL 61820.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association Inc., Agent

(Applications for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for references from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. All materials shall be clean, wholesome and free from evidence of insect infestation or other objectionable foreign matter.

3.1.1 Pastry flour enriched. Pastry flour enriched, shall be unbleached soft wheat flour. It shall have an ash content of not more than 0.45 percent based on 14 percent moisture for flour. In addition, the viscosity shall be not less than 30 and not more than 50 (MacMichael Viscosimeter Reading.)

3.1.2 Shortening. Shortening shall be prepared from vegetable fat, which has been subjected to interesterification. Food and Drug approved antioxidants may be incorporated into the product. The shortening shall have a stability of not less than 60 hours (AOM) and shall contain not more than 0.15 percent moisture and volatile matter and not more than 0.08 percent free fatty acid.

3.1.3 High solids shortening. High solids shortening shall be made from hydrogenerated vegetable oil. The shortening shall comply with the following analysis (see 6.7 for suggested solid fat index).

Capillary melting point	127± 3°F
Free fatty acids	0.1 percent maximum
A.O.M. stability	200 hours (Minimum)

3.1.4 Salt. Salt shall be white, refined sodium chloride, with or without anti-caking agents. Iodized salt shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

3.2 Formulation. The prepared pie dough mix shall be processed according to the following formula:

Material	Percent by weight
Pastry flour	Not more than 64.4
Shortening	Not less than 27.0
Shortening (High solids)	Not less than 8.0
Salt	0.6 ± 0.1

3.3 Finished product. The finished mix shall be well blended, into a free flowing homogeneous mixture. It shall be free from dirt, filth, mustiness, extraneous matter, objectionable odor(s) and lumps other than those which disintegrate readily upon application of slight finger pressure. The moisture content of the finished mix shall be not more than 9.0 percent.

3.4 Performance. The pie dough when prepared and baked in accordance with 4.3.2, shall yield a crust that is evenly and throughly baked, uniformly brown, without burnt or scorched areas and shall not stick to the pan. The crust shall have a thickness of not more than 1/4 inch and not less than 1/8 inch thick. The texture shall be flaky, tender and crisp. The crust shall have no undesirable flavor or odor.

3.5 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

3.6 Workmanship. The product shall be prepared, processed, and packaged under modern sanitary conditions and in accordance with good commercial practice. For Military agencies the product shall be processed in establishments meeting the requirements of MIL-STD-668.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling. Sampling of the finished product covered by this specification, and samples of any materials, components, or constituents entering into the preparation of the finished product may be taken at any time by the Government inspector to determine compliance with requirements.

4.2 Inspection.

4.2.1 General. Inspection shall be made by the procuring agency or a duly authorized representative at the time and place designated by the procuring agency. It may be made at the site of manufacture, both during and after processing and packing, at any suitable point in transit, or after delivery to the point of destination.

4.2.2 Final inspection. Unless otherwise specified (see 6.1), final inspection shall be made after delivery to the point of destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.2.3 Condition inspection of containers. When inspection of product for quality and condition is performed by the U. S. Department of Agriculture, the United States Standards for Condition of Food Containers shall apply. (For applicable criteria governing inspection of containers for Military agencies, (see 4.2.6.3).

4.2.4 Responsibility for inspection. The supplier is responsible for meeting all the provisions of the specification prior to submission to the Government for acceptance. Unless otherwise specified in the contract or order, the supplier is required to perform the examination and tests prescribed herein, using his own or any other inspection facilities and services.

4.2.4.1 Inspection records. Inspection records of the examinations and tests shall be complete and made available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2.5 Preacceptance inspection (plant sanitation inspection).

4.2.5.1 Civil agencies. When specified (see 6.1), inspection of plants producing the product will be conducted upon request of the contracting officer to the appropriate Government inspection agency. Award of contracts will be limited to establishments known to maintain proper sanitary conditions or which have received prior sanitary approval recommended by the inspection agency.

4.2.5.2 Military agencies. The product shall be rejected if produced in plants not meeting the requirements of 3.6.

4.2.6 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except as otherwise indicated herein.

4.2.6.1 Component and material inspection. In accordance with 4.2.4 and 4.2.4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents.

4.2.6.1.1 Ingredients. Conformance of ingredients to identity requirements (kind) shall be ascertained by examination of pertinent labels, marking, invoices, or other valid documents. In addition, each ingredient shall be examined organoleptically, as necessary to determine conformance to condition requirements of 3.1. The sample unit shall be approximately one pound of ingredient from a primary container. The sample size shall be five. In the event a lot consists of less than five primary containers, a sample unit shall be extracted from each container in the lot. Nonconformance with identity requirements or one or more sample units not conforming to condition requirements shall indicate an unacceptable ingredient and use of such shall be cause for rejection of the involved finished product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.2.6.1.2 Testing of shortening, flour and cans. Tests for shortening, flour and cans shall be in accordance with table I. Test requirements for the characteristics listed shall be average requirements. Test procedures shall be as specified in 4.3. Test failure shall indicate an unacceptable component and use of such shall be cause for rejection of the involved end item.

TABLE I. Testing of shortening, flour and cans (see 4.2.6.1)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref. and rqmt para.
Shortening	1-pound composite 1/	Pounds	S-1	Stability Free fatty acid Moisture and volatile matter	Pass or fail 2/ Nearest 0.01 percent Nearest 0.01 percent	3.1.2 4.3
Shortening (High solids)	1-pound composite 1/	Pounds	S-1	Stability Free fatty acid Capillary melting point	Pass or fail 2/ Nearest 0.01 percent Nearest degree F	3.1.3 4.3
Flour	1-pound composite 1/	Pounds	S1	Ash Viscosity	Nearest 0.01 percent Nearest unit	3.1.1 4.3
Cans 3/	1-can w/lid	Cans	S-1	Tinplate	Nearest 0.01 lb/base box	5.1.1 4.3

1/ Composite shall be derived from the number of containers indicated by the inspection level.
2/ If failure report to nearest hour.
3/ Tests on external coating (when required) and can label (military) shall be performed on the same cans submitted for tinplate test.

4.2.6.2 Examination of formulation. Unless otherwise specified (see 6.1), examination shall be performed to determine conformance to formulation requirements of 3.2. Records of formulation shall be maintained. The records shall be examined by the assigned Government inspector. In the event the Government inspector is in the plant during production, he shall perform an examination of the actual formulation. When specified (see 6.1), the Government inspector shall perform continuous examination of the formulation procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.2.6.3 Examination of end item. Examination shall be in accordance with tables III through V and 4.2.6.3.1 through 4.2.6.3.3. Sampling plans for the aforementioned tables shall be in accordance with table II. The acceptable quality levels (AQLs) shall be expressed as percent defective for table III and defects per hundred units for table IV and V.

TABLE II. Sampling plans

Table	Sample unit	Lot size expressed in	Inspection level	AQLs Major	AQLs Minor	AQLs Total
III	1-filled primary container	Primary containers	S-2		2.5	
IV	1-filled primary container	Primary containers	S-2	1.5		4.0
V	4-ounces from a primary container	Primary containers	S-1	1.5		10.0

TABLE III. Examination for net weight 1/ 2/

Category	Defect
Minor	
201	Net weight more than 5-percent under specified net weight (for containers required to have 1-pound or less)
202	Net weight more than 2-percent under specified net weight (for containers required to have more than 1-pound but less than 10-pounds)
203	Net weight more than 1-percent under specified net weight (for containers required to have 10-pounds or more)

1/ Report results to nearest 1/8-ounce for containers required to have 1-pound or less; nearest 1/2-ounce for container required to have more than 1-pound but less than 10-pounds; nearest ounce for containers required to have 10-pounds but less than 50-pounds; nearest 1/8-pound for containers required to have 50-pounds or more.

2/ Lot shall be rejected if the average net weight of the samples is less than the specified net weight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

TABLE IV. Examination of finished product 1/

Category		Defect
Major	Minor	
	201	Not well blended
101		Lumps which do not disintegrate upon light finger pressure
102		Foreign odor

1/ Presence of foreign material (e.g., insects, filth, metal, glass, paint, dirt etc.) shall be cause for rejection of the lot.

TABLE V. Evaluation of baked product 1/

Category		Defect
Major	Minor	
101		Sticks to pan
	201	Not a uniform brown color
102		Not free of burnt or scorched areas
103		Texture not flaky, tender or crisp
	202	Thickness more than 1/4 inch or less than 1/8 inch 2/
104		Undesirable flavor or odor

1/ See 4.3.2 for preparation. Make one determination per sample unit.
2/ Measuring device shall be calibrated in 1/32 inch increments.

4.2.6.3.1 Examination of primary containers. Examination of primary containers for condition and labeling shall be in accordance with the United States Standards for Condition of Food Containers. Examination of cans for seam leakage shall be in accordance with applicable quality assurance provisions of PPP-C-29.

4.2.6.3.2 Examination of shipping containers. The filled and closed shipping containers shall be examined in accordance with the quality assurance provisions in the appendix of PPP-B-636. In addition, the following defects shall be included in the examination: Major - Markings missing, incorrect or illegible; Minor - Quantity or arrangement of contents not as required. For packing as specified in 5.2.3.1 only the defects pertaining to marking and quantity of contents shall apply.

4.2.6.3.3 Examination of unit loads. Unit loads shall be examined in accordance with the quality assurance provisions of MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.2.6.4 Testing of finished product. The finished product shall be tested for moisture in accordance with 4.3. The sample for testing shall be a one-pound composite of the product derived from the number of primary containers indicated by inspection level S-2. Lot size shall be expressed in terms of primary containers. Test results shall be reported to the nearest 0.1 percent. A test failure shall be cause for rejection of the lot.

4.3 Test methods. Examination and test procedures which differ from those specified herein, unless otherwise excepted, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government contracting officer determines that such procedures and controls do not provide, as a minimum, such quality assurance, the supplier will use the procedures set forth herein. In case of dispute as to examination or test results, the procedures specified herein will govern.

4.3.1 Test procedures.

4.3.1.1 Chemical analyses. Chemical analyses shall be conducted in accordance with the following methods from Offical Methods of Analysis of the Association of Official Analytical Chemists or Official and Tentative Methods of the American Oil Chemists Society as applicable:

Test	Source	Method
Pastry flour 1/		
Viscosity	Chapter: Cereal Foods Section: Wheat flour	MacMichael Viscosimeter Method
Ash	Chapter: Cereal Foods Section: Wheat flour	Direct Method
Vegetable Shortening 2/		
Fat stability (AOM)		Cd 12-57
Moisture and volatile matter		Cd 2d-25
Free fatty acid		Ca 5a-40
High solid shortening 2/		
Fat stability (AOM)		Cd 12-57
Free fatty acid		Ca 5a-40
Capillary melting point		Cc 1-25
Finished product 1/		
Moisture	Chapter: Sugar and Sugar Products Section: Sugars, sirups and Molasses	Moisture (Vacuum oven method)

1/ Official Methods of Analysis of the Association of Official Agricultural Chemists.
2/ Official and Tentative Methods of the American Oil Chemists Society (AOCS).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:11Z
Check the source to verify that this is the currentversion before use.

4.3.1.2 Tin coating weight. Tin coating weight shall be determined by any method specified in PPP-C-96.

4.3.2 Baking evaluation.

4.3.2.1 Baking. Pie crust dough shall be prepared and baked in accordance with the following directions: Place 6 ounces of prepared mix in a mixing bowl, stir to break apart and add 1-1/2 fluid ounces of ice water (3 tablespoons). Mix lightly until dough holds together. Shape dough into a ball, place on lightly floured board and roll to form a circle of 10-1/2 inches in diameter. Fold and transfer dough to a 9-inch pie pan. Fit dough in pan, trim excess edges and prick bottom and sides with tines of a fork. Place in 450°F preheated oven and bake 8 to 10 minutes, or until the crust is golden brown.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with 5.1.1 or 5.1.2, as specified (see 6.1).

5.1.1 Level A. A net weight of five pounds of the product shall be filled into a size 603 by 700 open-top style, round, metal can with soldered side seam and compound-lined, double-seamed and hermetically sealed can. A minus 2 percent tolerance will be allowed in any one container, provided the average net weight of the cans inspected in accordance with table III, is not less than 5 pounds. The cans shall be made throughout from not less than commercial 0.25 pound per base box electrolytic tin plate (see 4.3.1.2), and shall be coated outside with a coating conforming to type I or II, or when specified (see 6.1), type III of TT-C-495. The cans shall not leak when subjected to procedures for seam leakage in PPP-C-29.

5.1.2 Level C. Unless otherwise specified, commercial packaging of the type, size and net weight specified (see 6.1) will be acceptable. The following minus tolerances will be allowed in any one container, provided the average net weight of the containers inspected in accordance with table III are not less than the net weight specified: 5% for containers of 1 pound or less; 2% for containers of more than 1 pound but less than 10 pounds; and 1% for containers of 10 pounds or more.

5.2 Packing. The product shall be packed in accordance with 5.2.1, 5.2.2 or 5.2.3, as specified (see 6.1). When packaged in accordance with 5.1.1, the shipping box may be top-opening or end opening. Strapping of the shipping box shall be in the same relation to the contents of the end opening box as for the top-opening box.

5.2.1 Level A. Six cans of the product, arranged 3 in length by 2 in width by 1 in depth, shall be packed on end in a snug-fitting fiberboard box, constructed, closed and reinforced in accordance with style RSC, V2s of PPP-B-636.

5.2.2 Level B. Six cans of the product, arranged 3 in length by 2 in width by 1 in depth, shall be packed on end in a snug-fitting fiberboard box, constructed, closed and reinforced in accordance with style RSC, V3c, V3s or V4s of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

5.2.2.1 When specified (see 6.1 and 6.6), the shipping container specified in 5.2.2 shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636, except that 2 bands shall be used, one lengthwise and one girthwise.

5.2.3 Level C. Not more than 30 pounds of the product shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC, type CF or SF, class domestic, method II closure of PPP-B-636.

5.2.3.1 When specified (see 6.1 and 6.8), the shipping container shall be in accordance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.2.4 When specified (see 6.1), the pie crust mix, packed as specified in 5.2, shall be arranged in unit loads in accordance with MIL-L-35078 for type and class of load specified.

5.3 Labeling and marking.

5.3.1 Military agencies.

5.3.1.1 Cans. Cans shall be labeled in accordance with MIL-L-1497 and shall have the following directions lithographed on the lid of the can:

DIRECTIONS FOR USE

Makes	13 (9-inch crusts (shells)
Pie Crust Mix	5 lb. (1-No.10 can)
Water (cold or ice)	2-1/2 cups

1. Place contents in mixer bowl and stir to separate
2. Add water and mix at low speed, until dough holds together
3. Divide dough into 13-7-1/2 ounce pieces
4. Shape into a ball, place on lightly floured board and roll evenly, about 1/8 inch thick and 1-1/2 inches wider than pie pan
5. Place dough on a 9-inch pan, trim edges, fold under to form a raised edge
6. Prick bottom and sides of shell with a fork when baked unfilled, (for filled pie do not prick shell - bake according to pie recipe)
7. Bake at 450°F, for 8 to 10 minutes or until lightly browned

5.3.1.2 Other containers. Commercial labeling or additional labeling, as specified, that complies with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder, is acceptable.

5.3.1.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.3.1.4 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

5.3.2 Civil agencies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

5.3.2.1 Unit containers. Commercial labeling and additional labeling, as specified, that complies with the Food, Drug, and Cosmetic Act and regulations promulgated thereunder, is acceptable.

5.3.2.2 Shipping containers. Shipping containers shall be marked in accordance with the requirements of FED-STD-123 and such other information as specified by individual agencies.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number and date of this specification.
(b) When final inspection shall be made prior to delivery, to point of destination (see 4.2.2).
(c) When plant sanitation inspection shall be performed by Civil agencies (see 4.2.5.1).
(d) When examination of formulation is not required or when Government inspection of formulation on a continuous basis is not required (see 4.2.6.2).
(e) Applicable levels of packaging and packing required (see 5.1 and 5.2).
(f) Type, size, and net weight of containers required for level C packaging (see 5.1.2).
(g) When type III can coating is required (see 5.1.1).
(h) When packing specified in 5.2.2.1 or 5.2.3.1 is required.
(i) Type and class of unit load when unit loading is specified (see 5.2.4).

6.2 If samples with bids are necessary, they shall be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid samples shall be definitely stated.

6.3 Supplier's inspection. The supplier shall assure that the product conforms to the specification prior to submission to the Government for final inspection.

6.4 Destination inspection (Civil agencies only). When finished product has been inspected and passed at point other than destination, the contract should require that the product be inspected at destination for identity, condition, and quantity only.

6.5 Selection of levels (Military agencies). Based on conditions known or expected to be encountered during shipping, handling and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR 700-15, NAVSUPINST 4030.28, AFR 71-6, MCO 4030.14D or DSAR 4145.7, as applicable.

6.6 Packing specified in 5.2.2.1 is intended for transfer at sea operations or specific overseas operations.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:11Z
Check the source to verify that this is the current version before use.

6.7 Solids fat index. High solids shortening may have following solids fat index:

Temperature °F	Percent solids
50	80
70	80
80	80
92	80
100	77
110	62

6.8 Packing specified in 5.2.3.1 is intended for direct shipment from the supply source to the first consuming activity for immediate use within CONUS.

Custodians:

Army - GL
Navy - SA
Air Force - 45

Review activities:

Army - MD
Navy - MC, MS
DP-SS

Preparing activity:

Army - GL

Project No. 8920-0164

Civil Agency Coordinating Activities:

GSA-FSS
AGR-CMS
VA-DMS
HEW-FDA, NIH

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

N-P-361C PIE CRUST MIX; PREPARED

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY NATICK LABORATORIES
NATICK, MASS. 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AMXRET-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commander
US Army Natick Laboratories
ATTN: AMXRET-EQS
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.