P-D-240
AUGUST 19, 1960

FEDERAL SPECIFICATION

DETERGENT, SURGICAL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope.—This specification covers an antibacterial, nonalkaline, nonirritating, emollient, sudsing, liquid cream detergent, suitable for rapid reduction of skin surface bacteria by washing and scrubbing.

1.2 Classification.

1.2.1 *Sizes.*—Surgical detergent shall be of the following sizes, as specified (see 6.1):

Size 1.—5 ounces
Size 2.—1 gallon

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards.—The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

PPP–B–566—Boxes, Folding, Paperboard.

PPP–B–585—Boxes, Wood, Wirebound.

PPP–B–601—Boxes, Wood, Cleated-Plywood.

PPP–B–621—Boxes, Wood, Nailed and Lock-Corner.

PPP–B–636—Box, Fiberboard.

PPP–B–676—Boxes, Set-Up, Paperboard.

PPP–M–186—Medicinal Products and Clinical Laboratory Reagents; General Specification for Containers, Packaging and Packing.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications:

MIL–B–10377—Box, Wood, Cleated, Veneer, Paper, Overlaid.

MIL–L–10547—Liners, Case, Waterproof.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. — The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

American Chemical Society Specifications:

Reagent Chemicals.

(Application for copies should be addressed to the American Chemical Society, 1155 Sixteenth St., N. W., Washington 6, D. C.)

American Pharmaceutical Association Publication:

National Formulary.

(Application for copies should be addressed to the J. B. Lippincott Company, Philadelphia, Pa.)

Official Methods of Analysis of the Association of Official Agricultural Chemists.

(Application for copies should be addressed to the Association of Official Agricultural Chemists, P.O. Box 540, Benjamin Franklin Station, Washington 4, D. C.)

Rosin's Reagent Chemicals and Standards.

(Application for copies should be addressed to D. Van Nostrand Co., Inc., 250 Fourth Ave., New York 3, N. Y.

U. S. Pharmacopoeial Convention, Inc.

Pharmacopoeia of the United States.

(Application for copies should be addressed to the Mack Publishing Company, Easton, Pa.)

3. REQUIREMENTS

3.1 Material.—Material shall be a stable, homogeneous, white to cream colored preparation, without added coloring agent. The material shall be in accordance with the following formula:

Hexachlorophene, U.S.P.	3 percent weight/weight (w/w)
Detergent agent (see 3.1.2)	50 percent w/w
Emollients (see 3.1.3)	8 percent w/w
Inert ingredients (vehicle) qs.	100 percent w/w

When assayed as specified herein, the hexachlorophene content shall be not less than 92 percent and not more than 108 percent of the specified amount, and the emollients content shall be not less than 88 percent and not more than 118 percent of the specified amount. The quantity of detergent agent shall be not less than 95 percent and not more than 105 percent of the specified amount.

3.1.1 *Hexachlorophene.*—Hexachlorophene shall be in accordance with the tests, standards, and requirements of the U.S.P. Hexachlorophene in the finished product shall be determined by both methods specified in 4.5.1.

3.1.2 *Detergent agent.*—Detergent agent shall be an alkyl aryl polyether sulfonate containing 28 percent ± 3 percent solids by weight and shall exhibit its identity and presence in the surgical detergent when tested as specified in 4.5.2.

3.1.3 *Emollients.*—Emollients shall be lanolin cholesterols and petrolatum. The total quantity of emollients shall be determined by the test specified in 4.5.3.

3.2 Physical properties of the finished product.

3.2.1 *pH.* — pH shall be 5.0 to 6.0 at 25° centigrade (C.) when tested as specified in 4.5.4.

3.2.2 *Viscosity.*—Viscosity shall be 5 to 20 seconds at 25° C. when tested as specified in 4.5.5.

3.2.3 *Homogenicity.*—The majority of the particles in the dispersed (internal) phase shall range in size from 2 to 10 microns. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

particles shall average between 3 and 7 microns when tested as specified in 4.5.6.

3.2.4 *Total solids.*—The preparation shall contain 29 to 34 percent total solids by weight when tested as specified in 4.5.7.

3.2.5 *Stability.*—Separation shall not be evident. After return to room temperature, the contents shall be capable of being readily poured from all three cylinders when tested as specified in 4.5.8.

3.2.6 *Germicidal activity.*—Germicidal activity, expressed as phenol coefficient, shall be at least 1.5 when tested as specified in 4.5.9.

3.3 Contents.

3.3.1 *Size 1.*—Filled immediate containers shall contain an average volume of not less than 5.0 fluid ounces (148 cubic centimeters (cc.)) and no immediate container shall contain less than 4.75 fluid ounces (135 cc.) when tested as specified in 4.5.10.1.

3.3.2 *Size 2.*—Filled immediate containers shall contain an average volume of not less than 1.0 gallon (128 fluid ounces) and no immediate container shall contain less than 0.95 gallon (121.6 fluid ounces) when tested as specified in 4.5.10.2.

3.4 Delivery schedule for Military Medical Supply Agency procurement.—Not more than 6 months shall have elapsed from the date of manufacture of the product, to the date of delivery to the Government.

3.5 Workmanship.—The material and its containers shall be free from defects which detract from their appearance or may impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Supplier responsibilities for inspection.—The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Lot.—For purposes of this specification, a lot, batch, or control is that single, uniform, and homogeneous quantity of surgical detergent produced from one formulation, subjected to the same compounding and manufacturing operation, and filled into final containers.

4.3 Sampling.—Sampling shall be conducted in accordance with Military Standard MIL–STD–105.

For visual examination	*Inspection level*
Major A	L5
Major B	II (normal, single)
Major C	II (normal, single)
Major D	II (normal, single)

For end item testing: Acceptance number shall be zero (0) for all sample sizes.

AQL (defects per 100 units)	*Unit of product*
1.0	Filled bottle
1.0	Labeled bottle
1.0	Intermediate containers
1.0	Exterior containers

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

The contents of the units selected from each lot shall be treated as a composite sample for that lot for all the following tests with the exception of the "Label Adhesion", "Contents", and "Leakage" tests.

Characteristic	Req. par.	Test par.	Level	Minimum sample
Hexachlorophene	3.1.1	4.5.1	Size 1—L2 Size 2—L1	7 2
Detergent agent	3.1.2	4.5.2		
Emollients	3.1.3	4.5.3		
pH	3.2.1	4.5.4		
Viscosity	3.2.2	4.5.5		
Homogenicity	3.2.3	4.5.6		
Total solids	3.2.4	4.5.7		
Stability	3.2.5	4.5.8		
Germicidal action	3.2.6	4.5.9		
Label adhesion	5.4.1.1.1	----------	----------	10*
Leakage:				
Size 1	5.1.1.1	PPP–M–186	L3	10*
Size 2	5.1.1.2	PPP–M–186	L2	3*
Contents:				
Size 1	3.3.1	4.5.10.1	L3	10*
Size 2	3.3.2	4.5.10.2	L2	3*

* Where applicable, the same sample shall be used for the determination of two or more tests.

4.4 Examination.—The surgical detergent shall be examined to determine compliance with all requirements contained in this specification.

4.4.1 *Classification of defects.*—Examination shall be conducted in accordance with the following classification of defects:

Categories and defects**

Major A

101. Color not white to cream.
102. Detergent not homogeneous.
103. Detergent not free of foreign particulate matter.

Major B

151. Container and closure not type specified.
152. Labeling not complete.
153. Labeling not legible.

Major C

175. Material and marking of intermediate container not as specified.

Major D

185. Material and marking of exterior container not as specified.

** Examination is not restricted to the classified possible defects listed above.

4.5 Test procedures.

4.5.1 *Quantitative determinations for hexachlorophene.*

A.—Spectrophotometric.

(1) Prepare a Standard Solution "A" to contain 3.00 milligrams (mg.) of Hexachlorophene, U.S.P., 1.0 milliliters (ml.) 1*N* Hydrochloric Acid, and sufficient Methanol A.C.S. to make exactly 100 ml.

(2) Prepare a Blank Solution "B" to contain 1.0 ml. of 1*N* Hydrochloric Acid and sufficient Methanol A.C.S. to make 100 ml.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

(3) Prepare the Sample Solution "S" as follows: Accurately weigh about 250 mg. of the well mixed sample into a tared 25-ml. volumetric flask, then dilute with Methanol A.C.S. to exactly 25 ml. Mix thoroughly and carefully filter through paper, taking adequate precaution to prevent evaporation. Discard the first portion of the filtrate and volumetrically transfer a 10-ml. aliquot of the subsequent clear filtrate to a 100-ml. volumetric flask. Add some Methanol A.C.S., then 1.0 ml. of 1*N* Hydrochloric Acid, and finally add sufficient Methanol A.C.S. to make exactly 100 ml. Mix thoroughly. This final dilution is Sample Solution "S" for the spectrophotometric assay. Note: The original solution may be centrifuged in lieu of being filtered through paper.

(4) Using a Beckman Model "DU" spectrophotometer with 1 centimeter (cm.) quartz cuvettes at wave length of 298.5 millimicrons (mu.), adjust to zero optical density reading for Solution "B". Determine optical density readings for Solutions "S" and "A", then calculate concentration of hexachlorophene in original sample.

B. — Alkali carbonate fusion method (Organic halogen). Place 10 grams (g.) of an equimolecular mixture of anhydrous sodium carbonate and potassium carbonate in a nickel fusion crucible, and add approximately 3 g. of sample accurately weighed. Without mixing, add 10 g. more of the carbonate mixture on top of the sample and place the crucible, uncovered, in an oven for 1 hour at 105° C. At the end of this time, transfer the crucible, partially covered, to a cold muffle furnace and heat to 550°-575° C. for 30 minutes, then remove the crucible and allow to cool. Transfer the contents of the crucible with the aid of distilled water to a 400-ml. beaker and heat to boiling. Filter the hot solution, collecting the filtrate in a 600-ml. beaker. Wash the filter paper and contents with hot distilled water until the washings are free from chloride. Chill the combined filtrate in ice and when cold (approximately 10° C.) render the solution acid to Congo Red paper by the addition of nitric acid which is added slowly while stirring. Add exactly 50 ml. of *N*/10 $AgNO_3$ to the acidified solution, and heat to boiling. Gently boil the mixture until the precipitate is well coagulated and the supernatant liquid is clear. Cool the mixture in ice to room temperature; add a few drops of Nitrobenzene (Rosin) and titrate the excess silver nitrate with *N*/10 KCNS using ferric alum T.S., as indicator. In order to correct for any inorganic chloride content of the sample, the following blank determination is necessary:

Blank determination. — Accurately weigh an additional 3–4 g. of well mixed sample and place in a 250-ml. Erlenmeyer flask. Add 10 ml. of distilled water, mix thoroughly by swirling, and follow by the addition of 5 ml. of glacial acetic acid and 50 ml. of Methanol A.C.S. Titrate the solution with *N*/10 Silver Nitrate to a lavender end point using 2 drops of 1 percent solution of Eosin yellowish prepared with 50 percent methanol as the solvent. Each ml. of *N*/10 $AgNO_3$ = 0.003546 g. chlorine. Make the necessary mathematical corrections for the inorganic chloride content of the sample and calculate the hexachlorophene content. Each ml. of *N*/10 $AgNO_3$ = 0.006782 g. hexachlorophene.

4.5.2 *Characterization and identification of detergent in the finished product.*

A. — Resistance to acid hydrolysis. Place about 3 g. of sample into a 250-ml. Erlenmeyer flask and add 100 ml. of 10 percent hydrochloric acid (Diluted Hydrochloric Acid, N.F.). Swirl the solution until homogeneous, add a few boiling stones, and gently boil over a flame for one hour, keeping the volume constant by the addition of hot distilled water. At the end of the one (1) hour period, copious foaming shall occur upon increase of the boiling rate.

B.—Ultra-violet absorption spectra. Examine a portion of Sample Solution "S" as prepared for the spectrophotometric assay for hexachlorophene, using a Beckman Model "DU" spectrophotometer with 1 cm. quartz cuvettes. Characteristic maxima due to the detergent are obtainable at wave lengths of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

277 mu. and 284 mu. and a characteristic minimum at 280 mu.

4.5.3 *Emollient content.*—Transfer a thoroughly mixed sample of about 10 g. to a tared standard New York State 8 percent "Babcock" milk test bottle by means of a suitable hypodermic syringe equipped with a cannula or glass tube about 6 inches in length, an outside diameter of about 4 millimeters (mm.), and a bore diameter of about 2 mm. Accurately weigh to determine the weight of the surgical detergent sample. Add 25 ml. of an 80 percent volume/volume (v/v) propylene glycol-water solution followed by 10 ml. of a (1 + 1) phosphoric acid-water solution. Mix the solution thoroughly and dilute to the bottom of the neck with 80 percent v/v propylene glycol-water solution. Immerse in a water bath maintained at a temperature of 60° ± 1° C., for 15 minutes. Adjust the volume of the emollient layer by the addition of 80 percent propylene glycol-water solution so that the emollient will lie within the graduated area of the neck. Re-heat for 5 minutes at 60° ± 1° C. and centrifuge for 5 minutes at 800 revolutions per minute. Remove from the centrifuge cups and place in the 60° ± 1° C. bath for 15 minutes. Remove from the bath and with the aid of dividers quickly measure the volume of emollient. Convert scale reading to ml. and calculate weight of emollient based on a specific gravity value of 0.85.

4.5.4 *pH.*—Place 10 ml. of the well-mixed sample into a 25-ml. graduated cylinder, and add 5 ml. of distilled water. Mix thoroughly and determine the pH of the emulsion with a suitable pH meter using the glass electrode and preferably a sleeve type calomel electrode.

4.5.5 *Viscosity.* — Fill the viscosimeter tube with the thoroughly shaken sample and tamp gently to remove air. Immerse in a water bath maintained at a temperature of 25° ± 1° C. for 15 minutes or until the contents of the tube have attained a temperature of 25° ± 1° C. when tested by the insertion of a thermometer. Remove from the bath, dry tube immediately, and determine the viscosity by recording the time required for the standard balls to drop through the 10 inch zone marked off. A total of 3 or 4 balls, added one at a time, should be used. The average time in seconds for a selected part (top, bottom, or middle) of the last two balls to pass from upper to lower lines of the tube shall be taken as viscosity.

Viscosimeter: A glass tube about 15 inches long with an inside diameter of 15 mm. ± 0.3 mm., which has a zone marked off 10 inches ± 0.2 inches in length, equidistant. from each end. This tube is used with ½ inch diameter anticorrosive metal balls, weighing between 8.15 g. and 8.50 g.

4.5.6 *Homogenicity.*—Place a small amount of the undiluted sample on a microscope slide, using a glass rod, and cover with a cover slip. With a minimum amount of pressure, press the cover slip down and rotate slightly so as to form a thin film. Examine under the low power objective. The product should show a uniform dispersion. Particle size shall be as specified and shall be determined under suitable magnification.

4.5.7 *Total solids.* — Accurately weigh a covered shallow moisture dish containing about ⅛ inch of purified sand that has been dried at 100° C. Place about 4 or 5 ml. of sample into the dish, cover quickly and accurately weigh. Place in an oven maintained at 100° C. and dry overnight, (approximately 18 hours). Cool in a desiccator and weigh. Calculate percent of total solids.

4.5.8 *Stability.*—Place from 8 to 16 fluid ounces in each of 3 cylindrical, colorless, clear-glass, stoppered cylinders so that the height of sample in each container is at least 5 inches. Allow one container to remain at room temperature, another in an incubator at 37° ± 2° C., and a third in a refrigerator at 5° to 10° C. The cylinders shall remain undisturbed for 7 days.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

4.5.9 *Germicidal activity.* — Germicidal activity shall be determined by a standard phenol coefficient test run at 20° C. using as a test organism Micrococcus pyogenes var. aureus (F.D.A. 209, A.T.C.C. No. 6538).

(a) Weigh 5.2 g. of the sample (based on a specific gravity of 1.04) into a tared 50-ml. graduated cylinder and then bring to volume with sterile distilled water.

(b) Mix this 10 percent stock solution thoroughly by inverting the cylinder a sufficient number of times to insure none of the sample adheres to the bottom of the cylinder. Excessive foaming should be avoided.

(c) From this 10 percent stock solution the dilutions indicated in table I are prepared in sterile distilled water. The resulting dilutions shall be used in the test.

TABLE I.—*Dilutions*

Vol. of 10 percent stock solution		Vol. of sterile distilled water	Resulting dilution of sample
2 ml.	+	8 ml.	1–50
1 ml.	+	9 ml.	1–100
1 ml.	+	14 ml.	1–150
1 ml.	+	19 ml.	1–200
1 ml.	+	29 ml.	1–300

(d) Proceed as directed in A.O.A.C., 8th Edition, page 91, 5.181 (2) using Nutrient Broth as a subculture medium and test the surgical detergent using Micrococcus pyogenes, var. aureus as the test organism.

4.5.10 *Contents.*

4.5.10.1 *Size 1.*—The volume of contents shall be determined by pouring the material into a graduated cylinder calibrated to at least 2 ml. The volume of contents shall be determined at 25° ± 2° C. As an alternate, the volume may be determined from the weight of the contents and appropriate conversion to volume.

4.5.10.2 *Size 2.* — The volume of contents shall be determined by pouring portions of the material into a graduated cylinder calibrated to at least 50 ml. The volume of contents shall be determined at 25° ± 2° C. As an alternate, the volume may be determined from the weight of the contents and appropriate conversion to volume.

5. PREPARATION FOR DELIVERY

For civil agency procurement, Fed. Std. No. 102 shall be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.

5.1 Immediate containers.

5.1.1 *Level A.*

5.1.1.1 *5-ounce, size 1.* — Immediate containers shall be in accordance with all applicable requirements of Federal Specification PPP–M–186. Immediate container classification shall be group A, class 2-polyethylene, style 1, grade 1–green, and closure K. Bottle design shall include a 24 mm. phenol-resin twin screwcap closure with an orifice not exceeding $\frac{1}{16}$ inch to facilitate dispensing. The top cap shall be 13 mm., inside diameter, and shall have a pulp and vinylite liner. The bottom cap shall be 24 mm., inside diameter, and shall have a friction fit polyethylene liner. The polyethylene liner of the bottom cap may be omitted provided the unlined cap makes a secure leakproof closure on the threads of the polyethylene bottle. As an alternate, a 24 mm. inside diameter, "Polytop Loc-top" (Polytop Corp.) closure, or equal, may be used. The weight of each immediate container, without closure, shall be not less than 19.5 g. and not more than 21.5 g.

5.1.1.2 *One-gallon, size 2.*—Immediate containers shall be in accordance with all applicable requirements of Federal Specification PPP–M–186. Immediate container classification shall be group A, class 1, type e, style 1, grade 1, closure A, and having an outer seal.

5.1.1.3 *Level C.* — Immediate containers shall be commercial containers of the type, size, and kind commonly used for the purpose or as specified in the procurement document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

5.2 Packaging.

5.2.1 *Unit of issue.*—One bottle, as specified, constitutes one unit.

5.2.2 *Packaging quantities.*—The number of units of issue indicated in table II shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in procurement document.

TABLE II. — *Packaging quantities*

	Unit package	Intermediate package	Exterior container
5-ounce, size 1	1 unit	12 units	144 units
One-gallon, size 2	1 unit	Not required	4 units

5.2.2.1 *Packing variation permitted.*—If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.2.3 *Level A.*

5.2.3.1 *5-ounce, size 1.*

5.2.3.1.1 *Unit package.* — Each bottle (1 unit) shall be individually packaged in a carton conforming to the requirements of Federal Specification PPP–B–566, PPP–B–636, or PPP–B–676. Closure shall be adequate to prevent spillage of contents under normal handling.

5.2.3.1.2 *Intermediate package.*—Intermediate package shall be a carton of appropriate size constructed in accordance with Federal Specification PPP–B–636, type I, class 1. Closure shall be adequate to prevent spillage of contents under normal handling.

5.2.3.2 *One-gallon, size 2.*

5.2.3.2.1 *Unit package.* — Each bottle (1 unit) shall be individually packaged in a carton with liners and pads as specified below.

5.2.3.2.1.1 *Carton.*—Each bottle shall be packaged in a double-faced corrugated fiberboard carton of suitable size and design, constructed in accordance with Federal Specification PPP–B–636, and fabricated from not less than 200-pound test fiberboard. Carton design shall include two (2) double-wall liners, and top and bottom air cell pads.

5.2.3.2.1.2 *Liner.*—Each liner shall be of one-piece, covering the sides and ends of carton. Liners shall be fabricated of not less than 275-pound test double-wall corrugated fiberboard of any combination of A, B, or C flutes except B–B.

5.2.3.2.1.3 *Pads.*—Top and bottom air cell pads shall be fabricated of scored corrugated fiberboard of not less than 200-pound test. Completed pad shall be approximately ¾ inch in thickness and positioned on top and bottom edge of liner.

5.2.4 *Level C.*—Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose within the continental limits of the United States of America.

5.3 Packing.

5.3.1 *Level A.*

5.3.1.1 *Exterior container.*—Exterior container shall be designed for type 3 load and constructed in accordance with Federal Specification PPP–B–585, style 3, for class 3 use; PPP–B–601, table II, using type III, class 1 plywood; PPP–B–621, table IV; or Military Specification MIL–B–10377, table II.

5.3.1.2 *Case liner.*—Each level A box shall be lined with a waterproof case liner con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

forming to Military Specification MIL–L–10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto.

5.3.1.3 *Strapping.* — Strapping, when required, shall be in accordance with applicable box specifications.

Note.—Strapping will not be required for shipment forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.3.2 *Level B.*

5.3.2.1 *Exterior container.*—Exterior container shall be a box of suitable size and design fabricated from not less than 275-pound test fiberboard, and constructed in accordance with Federal Specification PPP–B–636. Closure shall be as specified in appendix thereto.

5.3.3 *Level C.* — The subject commodity shall be packaged in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.4 **Marking.**

5.4.1 *Labeling.*

5.4.1.1 *For Military Medical Supply Agency procurement.*—Immediate containers for 5-ounce, size 1, and one-gallon, size 2, shall be labeled bearing the applicable information as specified in labeling paragraph of Federal Specification PPP–M–186. The unit of issue, quantity, and contract number are not required. Label shall also include the hexachlorophene content, directions for use, and the statements: "Shake Before Using" and "Do Not Freeze". The quantity of contents shall be designated as: "5 oz. (148 cc.)" for 5-ounce, size 1, and "1 gal. (3.78 l.)" for one-gallon, size 2.

5.4.1.1.1 *Adhesion of label.*—Label on immediate containers shall comply with adhesion of label test as specified in Federal Specification PPP–M–186.

5.4.1.2 *For other agency procurement.*—Immediate containers shall be commercially labeled or as specified in the procurement document.

5.4.2 *Unit package.*

5.4.2.1 *5-ounce, size 1.*—Marking shall be as specified in 5.4.1.1. In addition, the date of manufacture shall appear.

5.4.2.2 *One-gallon, size 2.*—Each unit package shall be marked in accordance with section 5 of Military Standard MIL–STD–129. Date of manufacture shall be shown in lieu of date packed. Lot (control) number shall be shown. Marking shall include the legend: "DO NOT PERMIT TO FREEZE".

5.4.3 *Intermediate package.*

5.4.3.1 *5-ounce, size 1.*—Each intermediate package shall be marked in accordance with section 5 of Military Standard MIL–STD–129. Date of manufacture shall be shown in lieu of date packed. Lot (control) number shall be shown. Marking shall include the legend: "DO NOT PERMIT TO FREEZE".

5.4.4 *Exterior container.* — Exterior container shall be marked in accordance with Military Standard MIL–STD–129, except that 6.2(c), 6.2(d), 6.5, and 7.5.1 shall not be applicable. Service color and service symbol markings are required only on direct shipments from the contractor's plant to overseas activities. Date of manufacture shall be shown in lieu of date packed. Lot (control) numbers shall be shown. Marking shall include the legend: "DO NOT PERMIT TO FREEZE".

5.4.5 *Civil agencies.*—Shipments shall be marked in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. — Procurement documents should specify the following:

(*a*) Number and date of this specification.

(*b*) Size required (see 1.2).

(*c*) Selection of applicable levels of packaging, packing, and marking (see 5.1, 5.2, 5.3, and 5.4).

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Federal Government requirements.

6.3 Transportation description.—Transportation description applicable to this item is:

Rail:

Soap NOIBN Liquid
Carload minimum weight 36,000 pounds per Uniform Freight Classification.

Truck:

Truckload minimum weight 36,000 pounds per National Motor Freight Classification.

Notice. — When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded, by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:
Army—M
Navy—Md
Air Force.

Copies of this specification may be purchased for 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:17Z
Check the source to verify that this is the current version before use.