P-P-576b
September 9, 1964

SUPERSEDING
Fed. Spec. P-P-576a
October 21, 1958

FEDERAL SPECIFICATION

POLISH, STOVE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers one type and one grade of stove polish, (see 6.1).

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-I-666—Iron Castings, Malleable.
PPP-B-636—Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547—Liners, Case, and Sheet, Overwrap, Water-Vaporproof, or Waterproof, Flexible.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The manufacturer is given wide latitude in the selection of component materials to produce a stove polish which meets the requirements of this specification.

3.2 Color, form and weight. The stove polish shall be black, in cake form, and shall have a net weight of 6 ± 0.25 ounces. The stove polish shall be capable of being readily

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

mixed in water. When prepared in accordance with 4.4.1, the stove polish shall form a paste which can be readily applied for the performance test specified in 4.3.6.

3.3 Performance. The stove polish shall be nonflammable when tested as specified in 4.3.6 and shall produce no obnoxious fumes when applied as directed by the manufacturer. The applied coating shall be lustrous black and shall not readily burn off.

3.4 Workmanship. The finished product shall be clean, and uniform, and shall conform to the levels established in this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels in section 4.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection. Sampling for inspection shall be in accordance with MIL-STD-105, except where otherwise indicated. For purposes of sampling, a lot for examinations and tests shall consist of all end items made with the same components during a normal production run and manufactured under essentially the same conditions and at essentially the same time.

4.2.1 *Inspection of materials and components.* The supplier is responsible for insuring that all materials and components used in the end item were manufactured and inspected in accordance with the requirements of this specification and with referenced specifications and standards to the extent applicable, except that this specification shall govern in the event of any inconsistency.

4.3 Inspection of the end item.

4.3.1 *Examination of the end item.* The end item shall be examined for the defects in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.3.5. The lot size for purposes of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of shipping containers for examination under 4.3.4 and in units of primary containers for examination in 4.3.2 and 4.3.3.

4.3.2 *Examination of the stove polish for defects in color, form and workmanship.* The sample unit for this examination shall be the contents of one filled primary container.

Examine	*Defects*
Color	Not black.
Form	Not cake.
Workmanship	Evidence of foreign matter.
	Not homogeneous.

4.3.3 *Examination for defects in net contents.* The sample unit for this examination shall be one filled primary container. The quality of the lot shall be unacceptable if the average net weight per individual filled container examined is less than the specified or indicated weight.

4.3.4 *Examination of preparation for delivery.* An examination shall be made to determine that packing, weight and markings comply with the requirements of section 5 of this specification. Defects shall be scored in accordance with the following list. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. Closed shipping containers, fully prepared for delivery, shall be examined for closure defects. The lot size shall be the number of shipping containers in the end item inspection lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Examine	Defect
Packing	Not in accordance with contract requirements. Container not as specified; closures not accomplished by specified or required methods or materials. Any nonconforming component; component missing, damaged or otherwise defective. Inadequate application of components: such as incomplete closure of case liners; container flaps loose; or inadequate sealing, strapping or stapling. Bulged or distorted containers.
Weight	Net weight exceeds specified requirements.
Markings (exterior and interior, as applicable)	Omitted, illegible, incorrect, incomplete or not in accordance with contract requirements.

4.3.5 *Inspection levels and acceptable quality levels for examinations.* The inspection levels for determining the sample size and the acceptable quality levels (AQLs), expressed in defects per 100 units, shall be as follows:

Examination paragraph	Inspection levels	AQLs
4.3.2	S-2	2.5
4.3.3	S-2	—
4.3.4	S-2	4.0

4.3.6 *Testing of the end item.* The end item shall be tested for the applicable characteristics as specified in table I for each inspection lot. The lot size shall be the number of cakes of stove polish in the end item inspection lot. The sample unit for testing shall be 1 cake. The sample size shall be as specified below. No more than one sample unit shall be taken from a shipping container. For lot acceptance, there shall be no failure on any test to meet all requirements applicable to the sample unit. Results shall be reported as "Pass" or "Fail".

Lot size (cakes)	Sample size
0—800	2
801—22,000	3
22,001 and over	5

TABLE I.—*Instructions for testing end item*

Characteristic	Reference to requirement paragraph	Reference to test method paragraph
Paste preparation	3.2	4.4.1
Performance:		
Ease of application	3.2 and 3.3	4.4.2
Color	3.2 and 3.3	4.4.2
Odor	3.3	4.4.2
Burn off	3.3	4.4.2
Flammability	3.3	4.4.3

4.4 Test procedures.

4.4.1 *Paste preparation.* Place a full or portion of a cake of polish in a suitable receptacle and moisten with water until the cake is softened and easily disintegrated with a glass rod or spatula. Add a sufficient amount of water to form a cream or paste which can be readily applied with a cloth or brush.

4.4.2 *Performance.* An unused stove lid made of cast iron or a piece of cast iron material approximately 6 by 6 inches, conforming to QQ-I-666 shall be heated to redness on the underside using a Bunsen burner; maintained at this condition for one minute. After cooling to room temperature (60° to 80°F.), the polish shall be applied in accordance with manufacturer's instructions. The ease of application and the presence of obnoxious fumes, if any, shall be noted. The color of the thoroughly-dried deposit shall also be noted. Then the test specimen shall be reheated for the time and duration previously specified. The polish shall not burn off during this heat treatment.

4.4.3 *Flammability.* Spread approximately 1 ounce of paste on a steel panel and heat with an inverted Bunsen burner. Observe whether paste ignites, burns, or smolders.

5. PREPARATION FOR DELIVERY

(Fed. Std. No. 102 should be referred to for definitions and application of the various levels of packaging and packing for civil agency procurements.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5.1 Packaging. Packaging shall be level A, B, or C, as specified, (see 6.2 and 6.3).

5.1.1 *Level A.* The stove polish shall be packaged in accordance with the manufacturer's normal practice.

5.2 Packing. Packing shall be level A, B, or C, as specified, (see 6.2).

5.2.1 *Level A.* Stove polish, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to class V3c or V3s of PPP-B-636. Each shipping container shall be provided with a type I or II, grade C case liner conforming MIL-L-10547. Each shipping container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.2 *Level B.* Stove polish, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to type CF or SF, class-domestic, style RSC of PPP-B-636. All flaps of the fiberboard shipping container shall be secured with an adhesive commercially used for the specific product being packed by application throughout the entire area of contact between the flaps, or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.3 *Level C.* Stove polish, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages, and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or orders, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The stove polish covered by this specification is intended for cleaning and polishing iron and cast iron stoves, and steel stove pipes.

6.2 Ordering data. Purchaser should exercise any desired options offered herein, and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Selection of applicable levels of packing, (see 5.2).

6.3 Levels B and C packaging. When level B or C packaging is specified for civil agency procurement, the requirement of 5.1.1 level A packaging shall apply, (see 5.1).

6.4 Transportation description. Transportation description and minimum weights applicable to this commodity are:

Rail:

Stove polish.
Carload minimum weight 36,000 pounds.

Motor:

Stove polish.
Truckload minimum weight 36,000 pounds, subject to Rule 115, National Motor Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army—GL

Navy—YD

Air Force—69

Interested activities:

Review

Army—GL MD

Navy—YD

Air Force—69

User

Army—SM

Navy—MC

Preparing activity:

Army—GL

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.