P-S-571F
February 6, 1973

SUPERSEDING
Fed. Spec. P-S-571E
April 10, 1968 and
Fed. Spec. P-S-606D
August 12, 1963
(See 6.5)

FEDERAL SPECIFICATION

SOAP, SCOURING (CAKE FORM): AND SOAP, SCRUBBING, ALKALINE (POWDER FORM)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of scouring soaps in cake form and one type of alkaline scrubbing soap in powder form (see 6.1).

1.2 Classification. The scouring and scrubbing soaps covered by this specification shall be of the following types and size containers, as specified (see 6.2):

Type I - Fine abrasive (cake form).
Type II - Coarse abrasive (cake form).
Type III - Strong alkaline (powder form).
1 pound
2.5 pound
100 pound
250 pound

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

Federal Specifications:

| | | |
|---|---|---|
| PPP-B-566 | - | Boxes, Folding, Paperboard. |
| PPP-B-636 | - | Boxes, Shipping, Fiberboard. |
| PPP-F-320 | - | Fiberboard; Corrugated And Solid, Sheet Stock (Container Grade), And Cut Shapes. |
| PPP-P-45 | - | Packaging Of Bulk Quantities Of Soaps, Detergents And Related Products (Chip, Powdered, Or Granular Form) For Domestic And Overseas Shipment. |

Federal Standards:

| | | |
|---|---|---|
| FED-STD-123 | - | Marking for Domestic Shipment (Civil Agencies). |
| FED-STD-313 | - | Symbols for Packages and Containers for Hazardous Industrial Chemicals and Materials. |
| FED-STD-536 | - | Soap and Soap-Products (Including Synthetic Detergents); Sampling and Testing. |
| FED-STD-595 | - | Colors. |

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

| | | |
|---|---|---|
| MIL-L-10547 | - | Liners, Case, and Sheet, Overwrap; Watervaporproof, or Waterproof, Flexible. |

Military Standards:

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - | Marking for Shipment and Storage. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

21 CFR 191 - Federal Hazardous Substances Act.

(The code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C., 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Material. The types I and II scouring soaps, shall be made from soap and abrasive, uniformly mixed. The abrasive used for type I shall be ground feldspar and for type II, ground quartz. The alkaline soap, type III, shall consist of soap and alkaline salts which have been mixed in the molten state before crystallization. The type III soap shall dissolve readily in tepid water.

3.2 Physical and chemical requirements. The soaps shall conform to the requirements specified in table I, when tested as specified in 4.3.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

TABLE I. Physical and chemical requirements

| Characteristics | Type I | | Type II | | Type III | |
|---|---|---|---|---|---|---|
| | Min. percent | Max. percent | Min. percent | Max. percent | Min. percent | Max. percent |
| Moisture and volatile matter | -- | 5.0 | -- | 6.0 | -- | -- |
| Free alkali (calculated as NaOH) | -- | 0.1 | -- | 0.1 | -- | 0.5 |
| Free acid (calculated as oleic acid) | -- | 0.5 | -- | 0.5 | -- | -- |
| pH of a 0.5 percent solution | -- | -- | -- | -- | 11.0 | 11.5 |
| Matter insoluble in water | Remainder | Remainder | Remainder | Remainder | -- | 1.0 |
| Titer of mixed fatty acids prepared from the soap, °C | -- | -- | -- | -- | -- | 18.0 |
| Alkaline salts (calculated as $Na_2CO_3$) | -- | 1.5 | -- | 4.0 | 40.0 | -- |
| Anhydrous soap | 6.0 | 10.0 | 8.0 | 12.0 | 15.0 | -- |
| Sum of anhydrous and alkaline salts (Alkaline salts calculated as $Na_2CO_3$) | -- | -- | -- | -- | -- | -- |
| Material insoluble in water retained on a No. 100 sieve | -- | 1.0 | -- | 1.0 | -- | -- |
| Material insoluble in water retained on a No. 200 sieve | -- | 5.0 | -- | -- | -- | -- |

3.3 Weight. Each cake of scouring soap, type I and II, shall weigh not less than eight ounces nor more than eleven ounces.

3.4 Odor. The soaps shall have no rancid, fishy, or horsey odor.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

3.5 Color. The type I scouring soap shall be cream-colored or white. The type II scouring soap shall be light gray or light tan. The type III scrubbing soap shall be uniform in color and not darker than color number 30257 of FED-STD-595 (see 6.3).

3.6 Form. Types I and II scouring soap shall be in cake form. The type III scrubbing soap shall be in powder form.

3.7 Abrasiveness (type I only). Type I scouring soap shall not scratch window glass, when tested as specified in 4.4.1.

3.8 Labeling. Each interior package (when applicable) and shipping container of scouring soap of specified type shall be durably and legibly marked with the following information, precautions, and directions for use and shall conform to the Federal Hazardous Substances Act.

3.8.1 Type I.

"SOAP, SCOURING (CAKE FORM - FINE ABRASIVE)
P-S-571
TYPE I"
Federal Stock Number
Manufacturer's name/address
date of pack and lot number

"A scouring soap (fine abrasive) for use in cleaning glass and porcelain surfaces.

CAUTION: KEEP OUT OF REACH OF CHILDREN
RINSE HANDS AFTER USE
AVOID CONTACT WITH EYES AND EYE LIDS
STORE IN COOL DRY PLACE

DIRECTIONS: DAMPEN A SOFT CLOTH OR SPONGE,
SQUEEZING OUT EXCESS WATER,
WORK SOAP INTO CLOTH OR SPONGE,
RUB THE SOILED AREA BRISKLY USING A CIRCULAR MOTION,
LET DRY, WIPE CLEAN WITH A CLEAN CLOTH OR SPONGE."

3.8.2 Type II.

"SOAP, SCOURING (CAKE FORM - COARSE ABRASIVE)
P-S-571
TYPE II"
Federal Stock Number
Manufacturer's name/address
date of pack and lot number

"A scouring soap (coarse abrasive) for use in scouring pots and pans.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

CAUTION: KEEP OUT OF REACH OF CHILDREN
RINSE HANDS AFTER USE
AVOID CONTACT WITH EYES AND EYE LIDS
STORE IN COOL DRY PLACE

DIRECTIONS: THOROUGHLY WET THE ENTIRE SURFACE OF THE ITEM TO BE CLEANED WITH CLEAN WARM WATER
DAMPEN A SOFT CLOTH OR SPONGE,
SQUEEZING OUT EXCESS WATER
WORK SOAP INTO CLOTH OR SPONGE
RUB THE SOILED AREA BRISKLY USING A CIRCULAR MOTION
RINSE USING CLEAN WARM WATER OR WIPE CLEAN WITH A CLEAN CLOTH OR SPONGE
APPLY THE SCOURING SOAP SEVERAL TIMES ON SEVERELY STAINED SURFACES."

3.8.3 Type III. "SOAP, SCRUBBING (POWDER FORM - STRONG ALKALINE)
P-S-571
TYPE III"
Federal Stock Number
Manufacturer's name/address
date of pack and lot number

"A scrubbing soap (strong alkaline) for use in washing down concrete ramps, garage floors, and washing out garbage pails and garbage pail racks and in other areas where a water hose is used for flushing and rinsing.

CAUTION: AVOID PROLONGED OR REPEATED SKIN CONTACT
DO NOT TAKE INTERNALLY
AVOID CONTACT WITH EYES OR EYE LIDS
(FLUSH WITH WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION)

DO NOT USE ON DISHES, POTS AND PANS, FABRICS OR GENERAL CLEANING
KEEP OUT OF REACH OF CHILDREN
RINSE HANDS AFTER USE
STORE IN COOL DRY PLACE
MAY CAUSE BURNS

DIRECTIONS: ADD TWO OUNCES OF SCRUBBING SOAP TO EACH GALLON OF WARM WATER SCRUB, MOP OR WIPE THE SOLUTION INTO THE SOILED AREA, THEN RINSE AWAY THE LOOSENED SOIL WITH FRESH WATER. REPEAT IF NECESSARY."



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

3.9 Workmanship. The types I and II scouring soap shall be in cake form, homogeneous in appearance and texture, firm, not crumbly, free from cracks, crushed edges, and holes. Type III soap shall be clean, uniform, free-flowing, and shall not lump or cake.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter. For purposes of sampling, an inspection lot for examination and tests shall consist of all the end item of one type prepared in a single batch and submitted for inspection at one time.

4.2.1 Inspection of materials and components. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, or qualified in this specification or applicable purchase document.

4.2.2 Inspection of the end item.

4.2.2.1 Examination of the end item. The end item shall be examined for the defects in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.2.4. The lot size, for purpose of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of cakes of scouring soap for types I and II and in units of filled primary containers of the specified capacity for type III for examination in 4.2.2.1.1, 4.2.2.1.2, 4.2.2.1.3, and in units of shipping containers for examination in 4.2.3. Random samples shall be drawn from each lot of end items offered for inspection.

4.2.2.1.1 Examination of the primary container for visual defects in construction and markings (type III). The sample unit for this examination shall be one filled primary container.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Construction | Not in container specified.<br>Any leakage or sifting of contents.<br>Any split, break, dent, hole, tear, or puncture.<br>Seams or closures not as specified in liner or container. |
| Markings (label or printing | Omitted, illegible, incorrect, incomplete, not in accordance with requirements.<br>Label or printing not clear, smeared. |

4.2.2.1.2 Examination for defects in net contents (type III). The sample unit for this examination shall be one filled primary container. The lot shall be unacceptable if the average net contents per container is less than the specified or indicated quantity.

4.2.2.1.3 Examination of the end item for defects in workmanship, odor, color, and weight. The sample unit for this examination shall be one cake of scouring soap for types I and II and the contents of one filled primary container for type III.

| Examine | Defect |
|---|---|
| Workmanship | Not in cake or powder form, as applicable.<br>Not clean, uniform, homogeneous in appearance and texture, or firm, as applicable.<br>Crumbly, types I and II; not free flowing, type III.<br>Cracks, crushed edges, or holes, types I and II.<br>Lumping or caking, type III. |
| Color | Not uniform or as specified. Darker than color chip number 30257, unless otherwise specified. |
| Odor | Rancid, fishy, or horsey odor. |
| Weight (types I and II | Any sample unit weighing less than specified. |

4.2.3 Examination of preparation for delivery requirements. An examination shall be made to determine whether the packaging, packing, and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Marking (exterior and interior, when applicable) | Omitted, incorrect; illegible; of improper size, location, sequence or method of application. |
| Materials | Any component missing, damaged or not as specified. |
| Workmanship | Inadequate application of components, such as: Fiberboard container or case liner not as specified; incomplete closure of container flaps or case liners, improper taping; inadequate stapling or loose strapping. Bulged or distorted container. |
| Content | Number of interior packages (when applicable) or cakes of soap per shipping container is more or less than specified. |
| Weight | Quantity of soap in powder form is less than that indicated by the specified interior package or shipping container. |

4.2.4 Inspection levels and acceptable quality levels (AQLs) for examinations. The inspection levels, for determining the sample size, and the acceptable quality levels (AQLs), expressed in defects per hundred units, shall be as follows:

| Examination paragraph | Inspection levels | AQLs |
|---|---|---|
| 4.2.2.1.1 | S-4 | 2.5 |
| 4.2.2.1.2 | S-2 | NA |
| 4.2.2.1.3 | S-3 | 1.5 |
| 4.2.3 | S-2 | 4.0 |

4.3 Testing of the end item. The end item shall be tested for the characteristics specified in table I and 3.7. The methods of testing specified in FED-STD-536, wherever applicable, and as listed in table II shall be followed. The lot size shall be expressed in units of one cake each of scouring soap for types I and II, and in units of one pound each of powder for type III. The sample unit shall be composed of two cakes of scouring soap for types I and II and a 1-pound composite sample for type III. The sample size shall be as shown in the table below. When specified in table II, tests shall be performed on composite sample or on sample unit basis. One cake of scouring soap (types I and II) from each sample unit shall be ground and thoroughly mixed to obtain the composite. Two specimens of each sample unit, for moisture and volatile matter determination, shall be weighed immediately upon opening the sealed



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

container. For soap powder (type III), the composite sample shall be made up by randomly sampling throughout the lot with a minimum of 3 containers sampled. Care shall be exercised to prevent the loss or absorption of moisture or loss of volatile matter during the sampling, weighing and storage of the specimens and samples. The lot shall be unacceptable if one or more sample units or the composite sample fails to meet any test requirement specified.

| Lot size (cakes or pounds) | Sample size |
|---|---|
| 800 or less | 2 |
| 801 up to and including 22,000 | 3 |
| 22,001 or more | 5 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

## INSTRUCTIONS FOR TESTING OF THE END ITEM

TABLE II

| CHARACTERISTIC | Specification Reference | | Requirements Applicable To | | Number Determinations Per Unit | Results Reported As | | Inspect Level | AQL |
|---|---|---|---|---|---|---|---|---|---|
| | Requirement | Test Method | Sample Unit | Comp Sample | | Pass or Fail | Numerically to Nearest | | |
| Moisture and volatile matter | Table I | 201 | X | | 2 | | 0.1 percent ave of 2 determinations | | |
| Free alkali | Table I | 302 | | X | 2 | | 0.01 percent ave of 2 determinations | | |
| Free acid | Table I | 302 | | X | 2 | | " | | |
| Material insoluble in water | Table I | 303 | | X | 2 | | 0.1 percent ave of 2 determinations | | |
| Alkaline salts | Table I | 304 | | X | 2 | | " | | |
| Anhydrous soap | Table I | 401 | | X | 2 | | " | | |
| Sieve test | Table I | 2101 | | X | 2 | | " | | |
| Abrasiveness (type I only) | 3.7 | 4.3.1 | X | | 1 | X | | | |
| pH of a 0.5 percent solution | Table I | 4.4.2 | | X | 2 | | Numerically to nearest 0.1 pH | | the unit |
| Titer of mixed fatty acids prepared from the soap | Table I | 901* | | X | 2 | | Numerically to nearest degree | | the (°C) |

* FED-STD-536





AMXRE Form 598
8 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

4.3.1 Certificate of compliance. The supplier shall submit to the contracting officer a certificate of compliance certifying that the abrasive used for type I scouring soap is ground feldspar and that the abrasive used for type II scouring soap is ground quartz.

4.4 Test procedure.

4.4.1 Abrasiveness (type I). The scouring soap shall be tested to determine whether it visibly scratches window glass by applying the scouring soap to a moistened cloth and then rubbing a glass surface with the cloth. Care shall be taken to employ 1 ounce ± 0.1 ounce of scouring soap on the portion of the cloth contacting the surface.

4.4.2 pH value. Determine the pH at 25° ± 1°C of a 0.5 percent solution by weight of type III soap, in freshly boiled distilled water, using a pH meter with a glass electrode. Calibrate the pH meter before use by checking against a standard buffer solution of pH 10.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cake form. Scouring soap in cake form does not require packaging.

5.1.1.2 Powder form.

5.1.1.2.1 One-pound and 2.5 pound quantities. One-pound or 2.5 pound quantities of scrubbing soap in powder form, as required, shall be packaged in a snug-fitting siftproof folding paperboard box conforming to variety 2, style I, type A, class a or b of PPP-B-566. Each box shall be securely closed in accordance with the applicable requirements specified in the appendix of the box specification.

5.1.1.2.2 One-hundred and 250-pound quantities. One-hundred or 250-pound quantities of scrubbing soap in powder form, as required, do not require packaging.

5.1.2 Level B. One-pound or 2.5 pound quantities of scrubbing soap in powder form, as required, shall be packaged as specified in 5.1.1.2.1 (see 6.2).

5.1.3 Level C. Scrubbing soap shall be packaged to afford adequate protection against physical damage and deterioration during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5.2.1.1 Cake form. One-hundred cakes of scouring soap of one type only shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be provided with top and bottom pads which measure 1/2-inch less than the length and width dimensions of the container and shall be fabricated of fiberboard material conforming to grade V3c or V3s of PPP-F-320. Each shipping container shall be provided with a case liner constructed in accordance with type I of MIL-L-10547, except that the case liner material shall consist of a lamination of 30-pound basis weight (24 by 36-500) draft paper (± 5%) and 0.001-inch minimum thick polyethylene film (± 25%). The bottom and side seams shall be heat sealed with seams not less than 3/8-inch in width. Closure of the case liner shall be accomplished by heat sealing or by a lockseam which is folded flat against the contents. Excess air shall be expelled from the case liner prior to the closure operation. Each shipping container shall be closed and reinforced in accordance with the appendix of the container specification.

5.2.1.2 Powder form.

5.2.1.2.1 One-pound and 2.5 pound quantities. Forty-eight 1-pound or twenty-four 2.5 pound quantities of scrubbing soap in powder form, packaged as specified in 5.1.1.2.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed, waterproofed, and reinforced in accordance with the appendix of the container specification.

5.2.1.2.2 One-hundred and 250-pound quantities. One-hundred or 250-pound quantities of scrubbing soap in powder form shall be packed in accordance with the applicable level A requirements specified in PPP-P-45.

5.2.2 Level B.

5.2.2.1 Cake form. One hundred cakes of scouring soap of one type only shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be provided with fiberboard pads and a case liner as specified in 5.2.1.1, except that the pads shall be fabricated of the same material as the shipping container. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

5.2.2.2 Powder form.

5.2.2.2.1 One-pound and 2.5 pound quantities. Forty-eight 1-pound or twenty-four 2.5 pound quantities of scrubbing soap in powder form, packaged as specified in 5.1.1.2.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

5.2.2.2.2 One-hundred and 250-pound quantities. One-hundred or 250-pound quantities of scrubbing soap in powder form shall be packed in accordance with the applicable level B requirements specified in PPP-P-45.

5.2.2.3 When specified (see 6.2), the fiberboard shipping container specified in 5.2.2.1 and 5.2.2.2.1 shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification.

5.2.3 Level C. Scrubbing soap, packaged as specified in 5.1 (when applicable), shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages, when applicable, and shipping containers shall be marked in accordance with FED-STD-123 and FED-STD-313.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages, when applicable, and shipping containers shall be marked in accordance with MIL-STD-129 and FED-STD-313.

5.3.3 Special marking. In addition, each interior package and shipping container of scouring soap shall be marked with the information specified in 3.8, as applicable.

6. NOTES

6.1 Intended use. Type I scouring soap is intended for use in cleaning glass and porcelain surfaces. Type II scouring soap is intended for use in scouring pots and pans. Type III scrubbing soap is intended for washing down concrete ramps, garage floors, and washing out garbage pails and garbage pail racks where a water hose is used for flushing and rinsing. It is not suitable for interior floors, walls, lavatories, dishes, pots and pans, or fabrics, because of its poor rinsibility and its high alkalinity.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and size container required (see 1.2 and 5.1.1.2).
(c) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.

(d) When level B packaging is required for civil agencies (see 5.1.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).
(f) Time for computing net weight (see 6.4).

6.3 Color chips. Color chips are available from all General Services Administration Business Service Centers.

6.4 Basis of purchase. The soaps are purchased by net weight. The soaps are subject to a possible gain or loss of weight, due to change in moisture content, depending on packaging, atmospheric, and storage conditions. Therefore, the time for computing net weight, with reference to acceptance of delivery, should be specified in the contract or purchase order. Preferable net weight of material should be determined at the time of sampling for test.

6.5 Supersession data. The requirements of P-S-606D have been incorporated into P-S-571F as type III. Unit containers specified in section 5 of P-S-606D have been added to section 1, herein.

Custodians:

Army - GL
Air Force - 84

Review activity:

Army - MD

User activities:

Navy - MC, MS, SH

Preparing activity:

Army - GL

Civil Agency Interest:

GSA-FSS

Project No. 7930-0276

---

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:18Z
Check the source to verify that this is the current version before use.