INCH-POUND

MIL-DTL-3628/193A
05 July 2016
SUPERSEDING
MIL-DTL-3628/193
15 November 1996

DETAIL SPECIFICATION SHEET

# BADGE, QUALIFICATION, AVIATION, COMBAT AIRCREW MEMBER, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.




DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL:
WINGS AND SCROLL: (-1 and -2) Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No C-752)
CENTER DEVICE AND STAR: (-1 and -2) Red Brass 85/15 (UNS Alloy C-230)

FINISH:
WINGS, AND SCROLL: (-1 and -2) Nickel Plated (C-230 only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.
CENTER DEVICE AND STAR: 24K Gold Plated, Mirror-like Finish and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
WINGS AND SCROLL:
HEIGHT (Overall):
-1: 15/16 inch (REF)
-2: 9/16 inch (REF)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: 2 inches (REF)
-2: 1-3/8 inches (REF)
THICKNESS (Throughout):
-1: 0.020 inch Minimum
-2: 0.020 inch Minimum
CENTER DEVICE:
DIAMETER:
-1: 3/8 inch (REF)
-2: 1/4 inch (REF)
THICKNEST (At thickest point):
-1: 0.100 inch ± 0.005 inch
-2: 0.060 inch ± 0.005 inch

ATTACHING DEVICE AND STARS:

1. Attaching device shall be prong and wing type clutch.

2. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart. -1: 1-1/2 inches ± 1/32 inch -2: 1 inch ± 1/32 inch.

3. The stars shown on the scroll are for illustrative purposes only.

4. The scroll shall have three holes with the center hole on the vertical center line of the badge. The two outside holes for -1 shall be 1/16 inch in diameter and 5/32 inch apart. The two outside holes for -2 shall be 3/64 inch in diameter and 5/64 inch apart.

5. The stars shall have staple type prongs.

6. Three stars of the required size shall be packaged in a plastic bag and included with the badge. The stars shall be mounted by the recipient as needed.

7. The center device shall be soldered or riveted to the wings.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A full forcer will be permitted to bring up the scroll and wings.

3. Piercing shall be as indicated.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-2016-370)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.