A-A-1297
May 16, 1984

COMMERCIAL ITEM DESCRIPTION

HAMMER, HAND, TRIMMERS', TACK, MAGNETIZED

The General Services Administration has authorized the use of this commercial item description in preference to Type VIII, Class 2 of Federal Specification GGG-H-86.

Salient Characteristics:

Design. Trimmers' tack hammer/magnetized end for picking up and starting the driving of tacks/opposite end suitable for driving tacks/similar to figure below.

Material. Head-forged carbon or alloy steel.

Hardness. The faces shall be hardened to not less than 45 nor more 60 on the Rockwell "C" scale.

Finish. Polished striking faces/protective coating of the entire head to deter rusting.

Handle. Fiberglass or clear lacquered hickory as specified.



(Figure is illustrative and not restrictive)

Hammer, Hand, Trimmers', Tack, Magnetized

Nominal Head Weight	Handle Type	Handle Length Overall ±1	National Stock Number
Ounces		Inches	
5	Fiberglass	11	5120-00-904-0028
5	Hickory	11	5120-00-293-2193
8	Hickory	11	5120-00-596-9709

Marking. Hammers shall be legibly marked with the manufacturer's name or trademark. The country of origin shall be marked on each hammer.

Workmanship. All hammers shall be free from imperfections which may affect their safety, appearance, serviceability, or durability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

Test:

Handgrip Test. Hammers with handgrips shall be subjected to test. Each sample shall be conditioned climatically to 30 degrees F, plus or minus 2 degrees F, and remain at this temperature for 1 hour or until thermal stabilization has occured. The sample shall then be cycled to plus 120 degrees F, plus or minus 2 degrees F, and remain at this temperature for 1 hour or until thermal stabilization has occurred. The sample shall then be conditioned to plus 70 degrees F, plus or minus 10 degrees F (room ambient temperature).

The samples shall then be subjected to a pull test force applied to the grip parallel to the longitudinal axis of the handle with the hammerhead securely captured to restrict movement. In order to minimize normal forces to the handle, the handgrip shall be captured using a woven wire cable grip or suitable device.

The pull test force is to be as noted below, except, that for certain sizes where the handgrip pull test force is found to be greater than the pull-apart force (tensile force). In this instance the handgrips shall be subjected to the head pull-apart force (tensile force) as a maximum in lieu of the specified force.

Grips which loosen or separate from the handle shall be cause for rejection.

After application of the pull test, the hammers shall be held by the head, and the grip twisted at the normal handgrip position by hand in alternating directions with a torque as noted in the Table below. Five complete twisting cycles shall be performed, after which there shall be no grip looseness or separation from the handle.

Hammerhead Weight	Pull Test Force	Torque Test
Less than 16 oz.	500 lbs.	40 in-lbs.
16 oz. and over	700 lbs.	50 in-lbs.

Fiberglass Handle Overstrike Test. Hammers with fiberglass handles shall withstand twenty three full swinging overstrike blows by an average built man (160 to 180 pounds), commensurate with the end use and weight of the hammer. The blows shall be against that portion of the handle directly behind the head and on a substantially supported steel object having a minimum 3/8 inch full radius.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

Fiberglass Bending Moment Test. Hammers with fiberglass handles shall be subjected to the test below in lieu of the static force test found in ANSI B173.2. Samples of the assembled striking tool shall not break, chip, or crack when subjected to the applicable load and distance listed below. The distance shall be measured from the top of the tool head. The striking tool head shall be locked securely in the test fixture with the striking face down and with the handle extended in the horizontal plane. The load shall be applied gradually and in a vertical direction.

BENDING MOMENT TEST LOADS FOR FIBERGLASS HANDLED HAMMERS

Headweight Ounces	Distance (Inches)	Applied Load (Pounds Minimum)
5	10	70
8	10	100

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

ANSI Standards are available from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTEREST:

Custodian

Air Force - 99
Army - GL
Navy - SH

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.