COMMERCIAL ITEM DESCRIPTION

DIE, THREAD CUTTING
(ROUND, SPLIT, METRIC SERIES)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-D-296.

This commercial item description covers adjustable, round split dies with metric threads.

Salient characteristics:

Design. Dies shall be cylindrical in shape with a split (slot) from the threads to the periphery. One side of the slot shall be tapped and furnished with an adjustment setscrew. Two dimples in the periphery, 180 degrees apart and 90 degrees to the slot, and midway between the die's faces shall be provided for retaining the die in the diestock. Threads shall be right-hand unless otherwise specified.

Material. Carbon tool steel or high speed steel.

Hardness. Rockwell C57 to 63 for carbon tool steel, Rockwell C61 to 65 for high speed steel. The cutting lands of the die threads shall show no evidence of partial or total decarbonization.

Sizes. Dies shall be furnished in the following sizes.

National Stock Number (NSN)	Thread Size (millimeters)	Nominal dimensions (inches)	
		Diameter	Thickness
5136-00-186-6039	S2.5	13/16	1/4
5136-00-186-6041	S4.5	13/16	1/4
5136-00-186-6043	M7	13/16	1/4
5136-00-186-6044	M9	1-1/2	1/2
5136-00-186-6045	M12	1-1/2	1/2
5136-00-186-6046	M16	2	5/8
5136-00-186-6048	M22	2	5/8
5136-00-186-6055	M14	1-1/2	1/2
5136-00-186-6056	S3.5	13/16	1/4
5136-00-186-6058	M6	13/16	1/4
5136-00-186-6059	M8	1-1/2	1/2
5136-00-186-6060	M10	1-1/2	1/2
5136-00-186-6061	M18	2	5/8
5136-00-223-7391	M20	2	5/8
5136-00-223-7393	M24	2	5/8
5136-00-273-0027	S2	13/16	1/4
5136-00-273-0032	S4	13/16	1/4

Threads. Thread form shall be ISO Metric thread form. Threads on the front face shall be chamfered approximatel 2 to 3 threads and 1 to 1-1/2 threads on the back face.

Marking. The dies shall be marked on the front face in a legible and permanent manner with the manufacturer's name or trademark, the thread size, and "HS", "HSS", or "High Speed" to indicate high speed steel, if applicable.

Workmanship. All dies shall be free from imperfections which may affect their appearance, serviceability, or durability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications standards and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

Recovered materials. The manufacturer shall utilize recovered material to the maximum practical extent.

Preservation, packaging, packing, and marking. The dies shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

GSA DC-01002138

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.