MILITARY SPECIFICATION

CASE, CARTRIDGE, 20MM, XM204E1 (Steel)

This amendment forms a part of Military Specification MIL-C-50602(MU), dated 12 November 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

In the title delete "XM204E1" and substitute "M204". Make similar model change wherever "XM204E1" appears in the specification.

Para 2.1, under DRAWINGS, Munition Command in fourth line, delete M206E2 and substitute "M206A1".

Para 4.2.1.a, delete and substitute the following:

"a. Inspection and non-firing test(s)

80 cartridge cases (uncoated)
26 cartridge cases (coated)"

Para 4.3.3.1, under Major, delete Major Defect, "102. Thickness, head rim, min ---------- Gage"

Para 4.3.3.1 (cont) under Major:

Delete the word Concentricity in defect 107 and substitute "Runout"

Delete defects 113, 114, and 115 and substitute the following:
"113. Wall thickness, at first location from inside base surface ---- Gage"
"114. Wall thickness, at second location from inside base surface --- Gage"
"115. Wall thickness, at third location from inside base surface ---- Gage"

Delete defect 126 and substitute "126. Exterior protective finish missing or incomplete ---------- Visual"

Add defect 128 below 127.
"128. Convexity or concavity of head surface ---------- Gage"

Para 4.3.4.1, Table II, delete "I or S" in line 10 and substitute "H or S"

Para 4.4.4 Function and Casualty.-third line, delete M206E2 and substitute "M206A1".

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A784

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:30Z
Check the source to verify that this is the currentversion before use.