MIL-G-49460(ER)
AMENDMENT 1
4 March 1987

MILITARY SPECIFICATION
GENERATOR, DIRECT CURRENT: G-76B/G

This amendment forms a part of Military Specification MIL-G-49460(ER) dated 4 December 1986, and is approved for use by the U.S. ARMY LABCOM, Department of the Army and is avaiable for use by all Departments and Agencies of the Department of Defense.

PAGE 16

Change paragraph 4.8.1 to read:

4.8.1 Burn-In. The Generator Head Assembly (11744747) with a Power Conditioning Unit (11744773) attached shall be connected to an electric motor and operated over a 5 hour period (1/2 hour on, 1 hour off, 1/2 hour on, 1 hour off, 1/2 hour on, 1 hour off, 1/2 hour on) at a speed of 68 RPM into a 10 ohm load.

PAGE 17

Change paragraph 4.8.6 to read:

4.8.6 Torque. Connect a 10 ohm load across pins B and D of the output connector (Pins A and C are open circuit). Run the Generator head at 68 RPM for 5 minutes before taking the measurement. The unit shall meet the requirements of 3.4.5

Preparing Activity
Army - ER

Project No. 6115 - A516

FSC 6115

Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:08Z
Check the source to verify that this is the current version before use.