MIL-P-50570A (AR)
AMENDMENT 3
23 February 1984
SUPERSEDING
AMENDMENT 2
15 January 1980

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, ROCKET ASSISTED
M549 & M549A1, DELAY ASSEMBLY FOR

This amendment forms a part of Military Specification MIL-P-50570A (AR), dated 19 July, 1979, and is approved for use by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Delete the following Military Specification:

"MIL-E-463 - Ethyl Alcohol, For Ordnance Use"

PAGE 2

3.3.1: Delete in its entirety.

PAGE 11

4.4.2.4: Delete Minor defect 201 in its entirety.

PAGE 12

4.4.2.5: Add the following Minor defect:

"Minor category:

Minor 203: Distance from end of tube to inside bottom of igniter plug, min. 0.40% 3.2 Gage".

PAGE 16

Add the following new paragraph:

"4.4.3.9 Density of delay composition pellets. A sample of 5 pellets shall be randomly selected from each lot and the density determined in accordance with 4.5.5 for compliance in accordance with the requirements on Drawing 9235983. If any pellet does not meet the required density, the lot shall be rejected."

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

PAGE 17

4.5.1.1.2: Delete in its entirety and substitute the following paragraph:

"4.5.1.1.2 Plus 145°F. This test shall be conducted as specified in 4.5.1.1.1 except that the conditioning temperature for the delay assembly and projectile shall be plus 145°F and a PXR-6297 proof charge conditioned at +145°F is to be used in lieu of a M203 series propelling charge."

4.5.1.2.1: Delete in its entirety and substitute the following paragraph:

"4.5.1.2.1 Plus 145°F. This test shall be conducted as specified in 4.5.1.1.1 except that the conditioning temperature for the delay assembly and projectile shall be plus 145°F and a PXR-6297 proof charge conditioned at plus 145°F is to be used in lieu of a M203 series propelling charge."

PAGE 18

Add the following new paragraph:

"4.5.5 Determination of density. The density of the delay composition pellet shall be calculated as follows:

$$\text{Density} = \frac{\text{Pellet wt.}}{(\text{Length of Pellet})\quad(\text{Dia. of Pellet})^2\quad(.7854)}$$

Note: All weights and dimensions are to be used in metric units."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-A-661)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.