MIL-P-50578D (AR)
AMENDMENT 1
30 July 1985

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, RA, M549 AND M549A1
(WITH WARHEAD AND MOTOR BODY)
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-50578D (AR), dated 20 December 1984, and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 30

4.4.3.4.2.2: Change "15" in the first sentence to "14".

PAGE 35

4.5.3.2: Delete in its entirety and substitute the following:

4.5.3.2 Safety. The projectiles for this test shall be divided into three groups. Group 1, consisting of five projectiles, shall be conditioned and fired at -65°F with Charge 8, M203 series propelling charges conditioned at -65°F. Group 2, consisting of four projectiles, shall be conditioned and fired at 145°F with M203 propelling charges conditioned at 145°F. Group 3, consisting of five projectiles, shall be conditioned at 145°F and fired with PXR-6297 proof propelling charges conditioned at 145°F. The cold phase (Group 1) shall be fired at a quadrant elevation of 51 degrees, and the hot phases (Group 2 and 3) shall be fired at a quandrant elevation of 24 degrees.

PAGE 37

6.7: Under the safety phase, change "15" to "14" and Total Sample Projectiles Required from "25" to "24".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A854)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.