INCH-POUND

MIL-P-50603B(AR)
AMENDMENT 1
25 May 1992

MILITARY SPECIFICATION

PRIMER, PERCUSSION, M115

This Amendment forms a part of Military Specification MIL-P-50603B(AR) , dated 1 July 1986, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Other Government documents, drawings and publications; under project and packaging drawings delete the following entry:

"12013224 -Cartridge, 25mm, TP-T-M793"

PAGE 18

4.5.3.2, Change from:

"4.5.3.2 Action time for 25mm. The method of test shall be as specified in AS12013566. The test sample primers shall be assembled into cartridge cases that have been previously accepted. In addition, each cartridge case shall be inspected for depth and diameter of primer pocket and length to shoulder basic diameter. The sample primed cases shall be inspected for absence of booster, serialized and the weight of propellant recorded. After assembly as a cartridge, 25mm, TP-T, M793, Dwg. 12013224 each test cartridge shall be inspected for projectile crimp missing or incomplete. Depth of primer seating, primer crimp missing, loose primer, maximum profile and alignment, and presence of foreign matter on the primer. The sample test cartridge, conditioned for a minimum of four hours in a conditioning chamber which has been established at -54°C ± 3°C, shall be handled in accordance with paragraph 5.2.3.10 of AS12013566 and fired in a test barrel."

To:

"4.5.3.2 Action Time for 25mm. The Method of test shall be as specified in AS12013566. The test cartridge used to test sample primers may be any of the various qualified 25mm cartridges using the M115 percussion primer. The test sample primers shall be assembled into cartridge cases that have been previously accepted. In addition, each cartridge case, shall be

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

inspected for depth and diameter of the primer pocket. The sample primed cases shall be inspected for absence/presence of booster, as applicable; serialized and the weight of propellant recorded. After assembly per applicable cartridge drawing, each test cartridge shall be inspected for projectile crimp missing or incomplete, depth of primer seating, primer crimp missing, loose primer, maximum profile and alignment, and presence of foreign matter on the primer. The sample test cartridge, conditioned for a minimum of four hours in a conditioning chamber which as been established at -54°C ± 3°C, shall be handled in accordance with paragraph 5.2.3.10 of AS12013566 and fired in a test barrel."

Page 19

4.5.4.2, Change from:

"4.5.4.2 Function and Casualty for primers for use in 25mm cartridge and weapon systems. The method of test shall be as specified in AS12013566. The test sample primers shall be assembled into cartridge cases that have been-previously accepted. In addition, each cartridge case shall be inspected for depth and diameter of primer pocket and length to shoulder basic diameter. The sample primed cases shall be inspected for absence of the booster. After assembly as a cartridge, 25mm TP-T, M793, Dwg. 12013224, each test cartridge shall be inspected for projectile crimp improper or incomplete, depth of primer seating, primer crimp missing, loose primer, maximum profile and alignment and presence of foreign matter on the primer. The sample test cartridge shall be linked and fired at ambient temperature in the M242 gun in bursts of approximately 25 cartridges at a cyclic rate of not less than 175 nor greater than 225 RPM. The gun barrel shall be at ambient temperature at the beginning of the test and cooled to ambient temperature after every 100 rounds."

To :

"4.5.4.2 Function and Casualtv for primers for use in 25mm cartridge and weapon systems. The method of test shall be as specified in AS12013566. The test cartridge used to test sample primers may be any of the various qualified 25mm cartridges using the M115, Percussion primer. The test sample primers shall be assembled into cartridge cases that have been previously accepted. In addition, each-cartridge case shall be inspected for depth and diameter of the primer packet. The sample primed cases shall be inspected for absence/presence of booster, as applicable. After assembly per applicable cartridge drawing, each test cartridge shall be inspected for projectile

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

crimp improper or incomplete, depth of primer seating, primer crimp missing, loose primer, maximum profile and alignment and presence of foreign matter on the primer. The sample test cartridges shall be linked and fired at ambient temperature in the M242 gun in bursts of approximately 25 cartridges at a cyclic rate of not less than 175 nor greater than 225 rpm. The gun barrel shall be at ambient temperature at the beginning of the test and cooled to ambient temperature after every 100 rounds .

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AB84)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.