

CSINK 120° ±10° TO OD OF THREAD
THREAD T
SPECIFICATION MIL-S-7742
UNLESS OTHERWISE
SPECIFIED

THIS SURFACE AND PITCH DIAMETER OF THREAD TO BE CONCENTRIC WITHIN .004 FULL INDICATOR READING

	DASH NO.				⑦			⑦	⑦									WEIGHT MAX	
	BRASS	COR RES STL	TUBE DIA	THREAD T	A ±.015	B	C DIA	D REF	E ±.015	F DIA	O DIA	H +.004 -.000 DIA	J DIA	K	L	P PITCH DIA	Q REF	BRASS	COR RES STL
(b)	2	C2	.125	5/16-32 ~~NEF~~-3B	.438	.375 +.003 -.004	(d) .375		.344	.312	.375	.173	.279 +.004 -.000	.281	.234		.43		
	3	C3	.188	3/8 -24 UNF-3B	.500	.438 +.003 -.004	(d) .438		.406	.375	.438	.257	.330 +.006 -.000	.328	.281		.51		
	4	C4	.250	7/16-20 UNF-3B	.500	.562 ±.004	.531	.156	.250	.438	.500	.316	.385 +.005 -.000	.375	.312		.65		
(c)	5	C5	.312	1/2 -20 UNF-3B	.531	.625 ±.004	.594		.281	.531	.594	.379	.447 +.006 -.000	.406	.344		.72		
	6	C6	.375	5/8 -18 UNF-3B	.562	.750 ±.004	.719	.188		.625	.719	.473	.565 +.008 -.000	.438	.375		.87		
	8	C8	.500	3/4 -16 UNF-3B	.688	.875 ±.004	.844	.219	.344	.750	.875	.598	.682 +.008 -.000	.531	.438		1.01		
	10	C10	.625	15/16-14 NS-3	.812	1.062 ±.005	1.062	.250	.438	.938	1.062	.719	.848 +.004 -.000	.625	.531	.8911 +.0036 -.0000	1.23		
(a)	12		.750	1-1/8 -12 UNF-3B	.875	1.250 ±.005	1.250		.531	1.062	1.250	.863	1.305 +.009 -.000	.719	.625		1.44		
	16		1.000	1-1/2 -12 UNF-3B	1.000	1.750 ±.016	1.688	.312	.562	1.500	1.750	1.140	1.410 +.009 -.000	.750			2.02		

(a) INACTIVE FOR DESIGN AFTER 23 NOVEMBER 1942.
(b) INACTIVE FOR DESIGN AFTER 9 MAY 1947 EXCEPT FOR OXYGEN SYSTEMS AND ENGINE PRIMER LINES.
(c) DASH NO. 5, 6, 8, 10, ARE NOT TO BE USED ON ENGINE PRIMER LINES.
(d) DIAMETER OF 30° CHAMFER AT END.

MATERIAL: BRASS; BARS, SHAPES, OR FORGINGS.
CORROSION-RESISTANT STEEL; BARS, SHAPES, OR FORGINGS.
SEE PROCUREMENT SPECIFICATION.

FINISH: SEE PROCUREMENT SPECIFICATION.

ADD P BEFORE DASH NO. FOR CADMIUM-PLATED BRASS NUT.

EXAMPLES OF PART NO.: AN805-4 - NUT-UNION, BRASS FOR .250 (4/16) TUBING OD.
AN805P4 - NUT-UNION, BRASS, CADMIUM PLATED FOR .250 (4/16) TUBING OD.
AN805C4 - NUT-UNION, CORROSION-RESISTANT STEEL FOR .250 (4/16) TUBING OD.

BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS WHICH MIGHT BECOME DISLODGED UNDER USAGE.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.005, ANGLES ±1/2°.

FOR DEFINITION AND APPLICATION OF DRAWING STATUS NOTES, SEE ANA BULLETIN NO. 337.

APPROVED 23 Nov 42 REVISED ① 8 Jan 43 ② 30 Mar 43 ③ 9 May 47 ④ 9 Jun 50 ⑤ 1 Jun 54 ⑥ 1 Sep 55 ⑦ 14 Aug 56

PROCUREMENT SPECIFICATION
MIL-F-6001

AIR FORCE-NAVY AERONAUTICAL STANDARD

NUT, UNION

AN805

NC This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design, not later than 6 months after the latest date of approval shown.

NOT When Government drawings, specifications, or ot[illegible] are used for any purpose other than in connection w[illegible] definitely related Government procurement operation, the United States Government there[illegible]curs no responsibility, nor any obligation whatsoever; [illegible] the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 202610-26T14:16Z
Check the source to verify that this is the currentversion before use.