DETAIL SPECIFICATION SHEET

FUSE BOXES, FEEDER DISTRIBUTION, SUBMERSIBLE, (15 FEET), 250 VOLTS, ALTERNATING CURRENT, THREE PHASE BUSES, SINGLE AND THREE PHASE BRANCHES, 0-30 AMPERE FUSES, SYMBOLS 560.1, 561.1, 562.1, AND 563.1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-24646.





FIGURE 1. Fuse box assembly, typical. Item No. 01, 02, 03, 04
(Symbol 560.1 shown)

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.




Symbol no.	Dimensions (ref)		
	A	B	C
560.1	16.38	15.38	5.62
561.1	20.38	15.38	5.62
562.1	27.38	15.38	5.62
563.1	16.38	15.38	5.62

FIGURE 2. Enclosure, overall dimensions. Item No. 05, 06, 07
(Symbols 560.1, 561.1, 562.1, and 563.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.



A. Symbols 562.1




B. Symbols 560.1, 561.1, and 563.1

SYMBOL NO	DIMENSIONS	
	A	B
560.1	9.25	4.62
561.1	12.00	6.00
563.1	9.25	4.62

FIGURE 3. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.




SYMBOL NO	DIMENSIONS		
	A	B	C
560.1	7.12	7.12	2.70
561.1	11.61	7.12	2.80
562.1	16.12	7.12	2.70
563.1	7.61	7.12	2.80


FIGURE 4. Fuse block assembly, typical. 08, 09, 10, 11
(Symbols 560.1, 561.1, 562.1 and 563.1)


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.

A. Two 3-phase branches
(Symbols 560.1 and 563.1)




B. Four 3-phase branches
(Symbol 561.1)





C. Six single-phase branches
(Symbol 561.1)



D. Six 3-phase branches
(Symbol 562.1)

NOTE: MAIN TERMINALS
SYMBOL 560.1 75 MCM
SYMBOL 563.1 200 MCM

FIGURE 5. Wiring diagrams. 12, 13, 14, 15

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Symbol numbers: See table I.

Design:

Electrical rating: 250 volts alternating current, 0-30 ampere, 60 hertz.
Dimensions and configuration: See figures 1, 2, 3 and 4.
Wiring diagrams: See figure 5.
Mounting dimensions: See figure 3.
Degree of enclosure: Submersible (15 feet).
Designation and marking: See MIL-DTL-24646.
Parts: The parts listed in table II and specified in MIL-DTL-24646 shall be used in the construction of the fuse boxes specified herein.

General information:
Military part numbers and general information are as specified in table I.

TABLE I. Military part numbers and general information.

Military part no.	Symbol no.	Weight in pounds	No. of circuits	Feeder MCM	Branch MCM	Fuse size	Bus bar size	Supersedes	
								Drawing no.	Type
M24646/10-001	560.1	28.0	2	75	40	0-30A	0.75 x 0.19	9000-S-6202-74171	F-14A
M24646/10-002	561.1	35.5	4	75	40	0-30A	0.75 x 0.25	9000-S-6202-74172	F-16A
M24646/10-003	562.1	48.0	6	75	40	0-30A	0.75 x 0.19	9000-S-6202-74173	F-18A
M24646/10-004	563.1	29.2	2	200	40	0-30A	1.00 x 0.25	9000-S-803-74170	F-12A

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list.

Item no. 1/	Description	QTY M /-				Material/ specification	Remarks
		001	002	003	004		
01	Fuse box assembly (sym 560.1)	-				MIL-DTL-24646/10	See fig. 1
02	Fuse box assembly (sym 561.1)		-			MIL-DTL-24646/10	See fig. 1
03	Fuse box assembly (sym 562.1			-		MIL-DTL-24646/10	See fig. 1
04	Fuse box assembly (sym 563.1)				-	MIL-DTL-24646/10	See fig. 1
05 2/	Enclosure (12 x 13 x 3)	1			1	M24142/6-008	See fig. 2 Type A mod
06 2/	Enclosure (12 x 17 x 3)		1			M24142/6-009	See fig. 2 Type A mod
07 2/	Enclosure (12 x 24 x 3)			1		M24142/6-010	See fig. 2 Type A mod
08 2/	Enclosure (12 x 13 x 3)				1	M24142/6-008	See fig. 2 Type A mod
09	Fuse block assembly	1				MIL-DTL-24646/10	See fig. 4
10	Fuse block assembly		1			MIL-DTL-24646/10	See fig. 4
11	Fuse block assembly			1		MIL-DTL-24646/10	See fig. 4
12	Fuse block assembly				1	MIL-DTL-24646/10	See fig. 4
13	Wiring diagram	2				MIL-E-2036	See fig. 5
14	Wiring diagram		2			MIL-E-2036	See fig. 5
15	Wiring diagram			2		MIL-E-2036	See fig. 5
16	Wiring diagram				1	MIL-E-2036	See fig. 5
17	Fuse clip (0-30A)	12	24	36	12	AA55507/1-06	N/A
18	Identification plate	1	1	1	1	Brass, ASTM B36/B36M B121/B121M	N/A
19	Information plate	2	4	6	2	Brass, ASTM B36/B36M B121/B121M	N/A

1/ Item numbers after the figure titles are the same as the item numbers shown in this table.

2/ Enclosure is same as MIL-E-24142/6(SH), except for inside depth which is 3 inches instead of 5 inches shown.

Custodian:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 5920-0758-09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:33Z
Check the source to verify that this is the current version before use.