MIL-L-43762A
9 December 1977
SUPERSEDING
MIL-L-43762
21 December 1971

MILITARY SPECIFICATION

LIDS, RECLOSURE, PLASTIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers plastic reclosure lids for cans.

1.2 Classification. Plastic reclosure lids included in this specification shall be of the following sizes, as specified (see 6.2):

Size 1 for 211 diameter can
Size 2 for 303 diameter can
Size 3 for 307 diameter can
Size 4 for 401 diameter can
Size 5 for 404 diameter can
Size 6 for 502 diameter can
Size 7 for 603 diameter can

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATION

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8110

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 - Marking for Shipment and Storage

FEDERAL

FED-STD-101 - Preservation, Packaging, and Packing Materials: Test Procedures

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

21 CFR - Federal Food, Drug, and Cosmetic Act, and Regulations Promulgated Thereunder

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. The plastic material shall be low density polyethylene with antioxidants or other substances incorporated in the plastic and shall conform to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. No changes of material initially used shall be permitted without prior approval of the contracting officer. There shall be no odor imparted by the material (see 4.3.1 and 6.4).

3.2 Design and construction. Lids shall be circular and flat. Lids may have depressed centers. Lids shall be designed to replace removable can tops. Lids shall have a ring on top which permits both lid and can stacking when tested as specified in 4.3.4. The lid skirt shall be designed to fit over the bead of the can. Lids shall snap on and not become loose or fall off when tested as specified in 4.3.2. The lids shall not deform or curl when tested as specified in 4.3.3.

3.3 Dimensions. The dimensions of each lid size shall be as shown in table I. The dimensions shown in table I are with the lid at 72°F (22°C) and not installed on a can nor otherwise confined. Tolerance on the thicknesses shall be ± 0.004 inch (0.10 mm), all other dimensions ± 0.020 inch (0.51 mm) (see 6.5).

TABLE I. Lid dimensions

Lid size	Thickness of bead groove wall inches	(mm)	Skirt length inches	(mm)	Outside diameter inches	(mm)	Top thickness inches	(mm)	Ring thickness inches	(mm)
211	0.030	0.76	.250	6.4	2.750	70	.028	0.71	0.028	0.71
303	0.035	0.90	.250	6.4	3.220	82	.030	0.76	0.030	0.76
307	0.037	0.94	.257	6.5	3.452	88	.030	0.76	0.030	0.76
401	0.035	0.90	.277	7.0	4.081	104	.030	0.76	0.034	0.86
404	0.028	0.71	.272	6.9	4.269	108	.030	0.76	0.030	0.76
502	0.045	1.14	.265	6.7	5.160	131	.033	0.83	0.037	0.94
603	0.042	1.06	.370	9.4	6.234	158	.034	0.86	0.045	1.14

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

3.4 Markings. The manufacturers trade mark or symbol shall be clearly, permanently and legibly marked on the top of the lid.

3.5 Workmanship. The finished lid shall be clean and free of pits, frayed or torn edges, cracks, gouges, or burns.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all lids of one size offered for inspection at the same time. The sample unit shall be one lid.

* 4.2.2.1 Visual examination. The completed lid shall be examined for defects in table II. The inspection level shall be S-4 and the acceptable quality levels (AQL's) shall be 6.5, expressed in terms of defects per hundred units.

TABLE II. Visual defects

Examine	Defect
Design and construction	Not circular Not flat (except for depressed center, when furnished) Ring on top of lid missing Ring not concentric with outer edge of lid
Markings	Not clear, illegible, not located as specified, or not permanent
Workmanship	Pits, cracks, gouges, burns, torn or frayed edges

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

4.2.2.2 Dimensional examination. The completed lid shall be examined to determine compliance with dimensional requirements. Any nonconforming dimension shall be classified as a defect. The inspection level shall be S-2 and AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

* 4.2.2.3 End item testing. Five sample lids shall be tested in accordance with 4.3.1 and 4.3.2. Three of the five sample lids shall then be tested in accordance with 4.3.3 and 4.3.4. Any nonconformance shall be cause for rejection of the lot.

* 4.2.3 Inspection of packaging.

* 4.2.3.1 Inspection for packaging, packing, and marking. An inspection shall be made to determine that packaging, packing, and marking comply with the requirements of section 5. Defects shall be as indicated in table III. The sample unit for this examination shall be one shipping container fully prepared for delivery except it need not be closed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

TABLE III. Packaging inspection

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Lids not in one stack Bags not tight fitting enough to keep lids in line Bag not closed as specified Bulged or distorted container
Contents	Number of lids per interior package and shipping container is more or less than specified

4.2.3.2 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

4.3 Test.

4.3.1 Odor test. Odor test shall be as specified in Method 4018 of FED-STD-101, except that the sample shall be five lids. Evidence of odor shall constitute failure of this test.

4.3.2 Looseness test. The top of a commercial can of the proper size shall be removed by a can opener and the specified size lid placed on the can. The can shall be inverted. Failure of the lid to snap onto, or stay on, the can shall constitute failure of this test.

4.3.3 Hot water test. The lids shall be placed in 190° ± 5°F (87.7° ± 3°C) water for a period of 15 ± 1 minute. Evidence of deformation or curling shall constitute failure of this test.

4.3.4 Stacking test. The lid shall be placed on the proper size can. The can shall be placed on top of another can of the same size. Failure to stack properly shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Fifty lids shall be placed in one stack and preserved-packaged in a tight-fitting plastic bag. The lids shall fit in the bag to keep the stack in line. The minimum thickness of the film shall be 0.75 mils (0.02 mm). Bag closure shall be by heat seal or mechanical tie.

* 5.1.2 Level C. The lids shall be preserved-packaged to afford adequate protection against deterioration, contamination or physical damage during shipment from supply source to receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

* 5.2.1 Level A packing. Two thousand lids, of one size only, preserved-packaged as specified in 5.1, shall be packed flat in a snug-fitting fiberboard box conforming to style RSC-L, V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each box shall be closed in accordance with Method III, waterproofed in accordance with Method V and reinforced in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:14Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. Two thousand lids of one size only, preserved-packaged as specified in 5.1, shall be packed flat in a snug-fitting fiberboard box conforming to style RSC-L, type CF, variety SW or SF, class domestic of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each shipping container shall be securely closed in accordance with Method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant shipping containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with Method III as specified in the appendix of PPP-B-636.

5.2.3 Level C packing. Lids, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The lids covered by this purchase description are intended for use in the reclosure of 211, 303, 307, 401, 404, 502, and 603 diameter cans.

6.2 Ordering data. Procurement data should specify the following:

(a) Title, number, and date of this specification.
(b) Size (see 1.2).
(c) Selection of applicable level of preservation-packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant class fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

6.5 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document are based on practices, conversion factors, and symbols specified in ASTM E 380, Standard for Metric Practice, and are for information only. In each instance, the value stated in U.S. customary units shall be controlling.

Custodians:

Army - GL
Navy - SA
Air Force - 69

Review activities:

Army - MD
Navy - MS
Air Force - 99
DLA - SS, GS

Preparing activity:

Army - GL

Project No. 8110-0242

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-L-43762A - Lids, Peclosure, Plastic

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314



Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:14Z
Check the source to verify that this is the current version before use.