MIL-S-43770/7

31 March 1972

MILITARY SPECIFICATION SHEET

SNAP HOOKS, CAST BODY, LOOP EYE SWIVEL

The complete requirement for procuring the snap hooks described herein shall consist of this document and the issue in effect of Specification MIL-S-43770.

This specification is mandatory for use by all the departments and agencies of the Department of Defense.

REQUIREMENTS.

Configuration: See illustration.

Strength. Tension load of 400 pounds min.

Dimensions: Inches, plus 1/16 minus 0 tolerance (see table I).

Material.

Body and swivel eye - Malleable iron casting
Tongue - Carbon steel strip
Rivet - Steel
Spring - Copper alloy wire

Finish: Zinc coating or cadmium plating.

Test method: Strength requirement shall be determined by applying a longitudinal force of 400 pounds to the hook end with the other end held by webbing capable of withstanding the load. Any evidence of deformation, cracks or breaks shall be classified as a defect.

PART NUMBER. Consists of the letter M, the specification sheet number, and a dash number from table I. Example: M43770/7-MIZ1.

Code Letters:

MIZ indicates malleable iron body (MI), zinc or cadmium plated (Z).

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:17Z
Check the source to verify that this is the current version before use.

MIL-S-43770/7

31 March 1972

MILITARY SPECIFICATION SHEET

SNAP HOOKS, CAST BODY, LOOP EYE SWIVEL

The complete requirement for procuring the snap hooks described herein shall consist of this document and the issue in effect of Specification MIL-S-43770.

This specification is mandatory for use by all the departments and agencies of the Department of Defense.

REQUIREMENTS.

Configuration: See illustration.

Strength. Tension load of 400 pounds min.

Dimensions. Inches, plus 1/16 minus 0 tolerance (see table I).

Material:

Body and swivel eye - Malleable iron casting
Tongue - Carbon steel strip
Rivet - Steel
Spring - Copper alloy wire

Finish. Zinc coating or cadmium plating.

Test method: Strength requirement shall be determined by applying a longitudinal force of 400 pounds to the hook end with the other end held by webbing capable of withstanding the load. Any evidence of deformation, cracks or breaks shall be classified as a defect.

PART NUMBER. Consists of the letter M, the specification sheet number, and a dash number from table I. Example. M43770/7-MIZ1.

Code Letters:

MIZ indicates malleable iron body (MI), zinc or cadmium plated (Z).

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:17Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-BQS
Natick, Massachusetts 01760

FOLD

55

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:17Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side, staple in corner, and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION Snap Hooks, Cast Body, Loop Eye Swivel MIL-S-43770/7

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:17Z
Check the source to verify that this is the current version before use.

MC

VALIDATION

MIL-S-43770/7
NOTICE 1
12 February 1988

MILITARY SPECIFICATION

SNAP HOOK, CAST BODY, LOOP EYE SWIVEL

Military Specification MIL-S-43770/7, dated 31 March 1972, has been reviewed and determined to be current.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Interested activities:

Army - AV, ME, MI, AT
Navy - MC, SA, CG
DLA - IS

Preparing Activity:

Army - GL

FSC 5340

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

☆U.S. GOVERNMENT PRINTING OFFICE 1988 - 505-633/80983

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:17Z
Check the source to verify that this is the current version before use.