INCH-POUND

MIL-T-43764A
25 July 1990
SUPERSEDING
MIL-T-43764
22 February 1972

MILITARY SPECIFICATION

TENTS, CABLE SPLICER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers frame supported cotton duck for sheltering cable splicers.

1.2 Classification. The tents shall be of the following types as specified (see 6.2).

Type I - Aerial tent and frame with wooden platform

Type II - Ground tent and frame

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

DD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
PPP-B-601	- Boxes, Wood, Cleated-Plywood

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams and Stitching

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF THE ARMY FIELD MANUAL

FM 10-16 General Repair of Tents, Canvas and Webbing

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

5-4-2330	- Tent, Cable Splicers, Type I, Aerial; Assembly Complete
5-4-2331	- Details
5-4-2332	- Details and Sections
5-4-2333	- Frame Assembly
5-4-2334	- Frame Details "A"
5-4-2335	- Frame Details "B"

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

5-4-2336	- Platform Assembly
5-4-2337	- Platform Detail I
5-4-2338	- Platform Detail II
5-4-2339	- Tent, Cable Splicers, Type II, Ground; Assembly Complete
5-4-2340	- Details
5-4-2341	- Sections
5-4-2342	- Frame Assembly and Details

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

D 3951 - Standard Practice for Commercial Packing

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall conform to the specifications, standards and drawings listed in section 2 and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Stitching, machine.

3.3.1.1 Types of stitching. All stitch types, except bartacking, shall conform to FED-STD-751 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

For all stitching except zig-zag stitching and stitching indicated by "Z" on drawings	- Type 301, 5 to 7 stitches per inch
For zig-zag stitching	- Type 304, 1/8 to 3/16 inch width, 10 to 14 stitches per inch
For stitching indicated by "Z" on drawings	- Type 401, 5 to 7 stitches per inch Chain portion of stitching shall not appear on outside of tent
For bartacking	- Bartack, 1/2 $\pm$ 1/16 inch long 1/8 inch wide (bight) and shall contain 28 stitches

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch in each direction at each break on stitch type 301; not less than 3/4 inch in each direction at each break on stitch type 304; and not less than 1-1/2 inches in each direction at each break on stitch type 401. Thread breaks in type 401 stitching may be overstitched with stitch type 301. Bartacks shall be free of thread breaks or loose stitching.

3.3.1.3 Stitching ends. The ends of type 301 stitching shall be overstitched not less than 1 inch except where ends are turned under in a hem or held down by other stitching. Where 301 stitching is performed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking, at least three or more tying, overlapping or backstitches shall be used to secure the ends of stitching. The ends of type 304 stitching shall be firmly secured by backstitching or overstitching or by increasing the number of stitches per inch for a minimum of 1/4 inch.

3.3.1.4 Skipped stitches. Two or more consecutively skipped stitches occurring in types 301 or 304 stitching shall be overstitched not less than 1 inch in each direction. Any skipped stitch in type 401 stitching shall be overstitched not less than 1-1/2 inches in each direction. Skipped stitches in type 401 stitching may be overstitched with type 301 stitching.

3.3.1.5 Lubrication of thread. The addition of any lubricant to the polyester thread prior to or during the sewing operation is prohibited.

3.3.1.6 Stitching margins. Unless otherwise specified, all stitching margins shall be 1/8 $\pm$ 1/16 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

3.3.2 Handstitching. Handstitching shall be accomplished where indicated on Drawings 5-4-2338 and 5-4-2341 with twine specified, using four strands twisted together. Each stitch shall be pulled tight and all ends of stitching secured.

3.3.3 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. Grommets shall be securely clinched without cutting the materials.

3.3.4 Setting of rivets. Rivets shall be securely set and neatly headed.

3.3.5 Welding. All welding shall be as specified on the drawings. Materials to be welded shall be clean and free from scale, corrosion, oil, water and other matter. Welds shall be sound, smooth, free from flash and shall show good fusion.

3.3.6 Repairs. Repairs whenever necessary and when authorized by the contracting officer shall be effected in accordance with Department of the Army Field Manual FM 10-16 except that handsewn or glued patches will not be acceptable.

3.3.7 Wicking of sewing thread (cup test). There shall be no dripping of water through the tent stitching when the tent is tested as specified in 4.4.5. The cup test is intended to insure that nonwicking thread has been utilized and that no lubrication has been added to the polyester thread during the sewing operation.

3.4 Marking. All marking and labels shall conform to DDD-L-20.

3.4.1 Direct marking. The letters "U.S." and special marking on the tents shall conform to type IV, class 9 in the size characters and in the locations shown on the applicable drawings. Class 9 marking shall be clearly legible after subjection to accelerated weathering.

3.4.2 Identification label. Identification labels shall conform to type VI class 6 and shall be 3-1/2 inches by 5-1/2 inches minimum with a blank space reserved at the bottom of the label for the Department of Defense inspector's stamp. Identification labels shall be stitched to the tents in the locations shown on the drawings.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears or cloth defects such as multiple floats or broken or missing yarns. Tape shall not have frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewed so that no run-offs, twists, pleats or open seams shall result. Care shall be taken in sewing to insure that no needle chews occur. All thread ends shall be trimmed to 1/2 inch or less. Metal components shall be free of burrs or sharp edges and shall not be broken

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:15Z
Check the source to verify that this is the current version before use.

or malformed. Welds shall not be cracked and shall be free from slag inclusion, undercut or flux deposits. The tent shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3.1, 4.4.3.2, 4.4.4 and tested for the characteristic specified in 4.4.5. Any nonconformance shall be cause for the rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the following requirements, operations, or assemblies to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts which cannot be corrected shall be removed from production.

a. That no lubrication is applied to the polyester thread prior to or during sewing operations for compliance with 3.3.1.5.

b. That holes punched to receive grommets are in compliance with 3.3.3.

c. That welds and welding are in compliance with 3.3.5 and applicable drawings.

4.4.3 End item visual examination.

4.4.3.1 Tent visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tents. The sample unit shall be one tent. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, of 6.5 for major defects, 15 for major and minor A defects combined, and 40 for total (major, minor A and B defects combined) defects.

TABLE I. End item tent visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Hole, (except drill hole) cut, or tear	101		
	Broken or missing yarn, multiple floats clearly visible at normal inspection distance	102		
Tape	Frayed or scalloped edge			301
Hardware	Broken	103		
	Malformed:			
	- fails to perform intended function	104		
	- will perform intended function		201	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item tent visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Hardware (cont'd)	Burr or sharp edge which may cause injury in handling or damage to fabric	105		
Grommets	Improperly set, two or more teeth exposed			302
	Clinched loosely, allowing grommet to rotate in hole			303
	Clinched excessively tight; i.e., cutting fabric	106		
Seams and stitching	Open seam on stitch type 301:			
	- 1/2-inch or less			304
	- more than 1/2-inch but not more than 1-inch		202	
	- more than 1-inch	107		
	Open seam on stitch type 401:			
	- one row of stitching open:			
	- for 1-inch or less			305
	- for more than 1-inch	108		
	- both rows of stitching open (not necessarily at same location)	109		
	NOTE: A seam shall be classified as open when one or more skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of a seam are open.			
	Raw edges caught in stitching:			
	- more than 1-inch but not more than 3-inches			306
	- more than 3-inches		203	
	Thread breaks:			
	- overstitched less than 1-1/2 inches on stitch type 401			307
	- overstitched less than 1-inch on stitch type 301			308
	- overstitched less than 3/4-inch on stitch type 304			309

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item tent visual defects (cont'd)

Examine		Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)	NOTE:	Thread breaks not overstitched shall be classified as open seams.			
		Needle chew resulting in cut, tear, or hole	110		
		Skipped stitches:			
		- overstitched less than 1-1/2-inches on stitch type 401		204	
		- overstitched less than 1-inch on stitch types 301 or 304 (where two or more consecutively skipped stitches occur)		205	
	NOTE:	Skipped stitches not overstitched shall be classified as open seams.			
Seam type		Wrong seam type	111		
Stitch type		Wrong stitch type	112		
Stitch tension		Loose, resulting in an exposed bobbin or top thread for more than 6-inches in length		206	
		Tight, as evidenced by puckering on seams for more than 6-inches in length			310
Stitches per inch		Less than minimum specified:			
		- one stitch			311
		- two or more stitches		207	
		More than maximum specified:			
		- one stitch			312
		- two or more stitches		208	
	NOTE:	Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning corners shall be classified as follows:			
		a. Within this minor "B" defect classification - no defect			

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item tent visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
Stitches per inch (cont'd)	b. Within the minor "A" defect classification - minor "B" defect			
Stitching gauge	Not as specified		209	
	NOTE: Applicable when double needle machine is used. When two rows of stitching are applied with a single needle machine, tolerances for stitching margin shall apply.			
Stitching margin	Larger than specified:			
	- for more than 2-inches but not more than 4-inches in length			313
	- for more than 4-inches in length		210	
Stitching ends	Overstitched less than 1-inch (except where ends are held down by other stitching, turned under in a hem or where stitching is performed automatically)			314
	Secured with less than three tying, overlapping or backstitches when automatic stitching is performed			315
Bartacking	Any bartacking less than specified length by more than 1/16-inch			316
Stitching indicated by "Z" on drawing	Chain portion of stitching shows on outside of tent		211	
Mends, darns or patches	Repairs not in accordance with Department of the Army Field Manual TM 10-16 or not authorized by the contracting officer (see 3.3.6)	113		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

Classification

TABLE I. End item tent visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Components and assembly	Any component not fabricated of applicable referenced material	114		
	Any component missing	115		
Rope components	Ends not finished as specified		212	
	Eye splices not accomplished as specified	116		
Marking; labels	Omitted, incorrect, illegible, misplaced or size characters not as specified			317
Cleanness	Grease or oil stains, thread ends not trimmed to 1/2-inch or less			318

4.4.3.2 Frame visual examinations. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of frame assemblies. The sample unit shall be one frame assembly. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, of 10 for major defects, 25 for major and minor A defects combined, and 40 for total (major, minor A and B defects combined) defects.

TABLE II. End item frame visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Components and assembly	Component missing	101		
	Any component not fabricated of applicable referenced material	102		
	Split, puncture, burr, rough or sharp edge, deformed	103		
	Any intended adjustment to movable frame components:			
	- impossible to accomplish	104		
	- difficult to accomplish		201	
Rivets and riveting	Rivet missing	105		
	Not specified type, size			301
	Rivet not peened; i.e., can be removed by hand	106		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

TABLE II. End item frame visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Welding	Missing, incomplete, cracked, porous, fractured or otherwise not fused		202	
	Not type specified, not smooth, flux not removed			302
Marking	Omitted, incorrect, illegible or misplaced			303

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tents or frame assemblies. The sample unit shall be one tent or frame assembly. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. The completely fabricated end items shall be tested as specified in 4.5.1 for conformance to the wicking requirements specified in 3.3.7. The lot size shall be expressed in units of tents. The sample size shall be one tent. The inspection level shall be S-3. Any test failure shall be cause for rejection of the lot.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as loose strapping
Content	Number per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Wicking of sewing thread (cup test). The tent shall be tested in three areas as follows: at the peaks, ridge or joining seam abutting the peaks or ridge; at an intersection of a horizontal and vertical seam such as at an intersection of a side wall and roof; and on a roof panel seam. Suspend the seamed section of the test fabric in the center of a 6 ± 1/8 inch diameter hoop and form a depression with the seamed fabric in the hoop to a depth of 1 ± 1/4 inch. Slowly pour 500 mL of water at 77°F ± 4°F into the cupped area (depression) and observe the under surface of the fabric for water penetration. Any wicking of water along the sewing thread, identified by a discoloration or darkening of the thread within 5 minutes after water is poured, shall constitute a test failure. Water leakage through the needle holes or between the plies of the lapped seamed fabric shall not be considered a failure (see 3.3.7).

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A preservation.

5.1.1.1 Aerial type.

5.1.1.1.1 Tent. The tent shall be folded in thirds to approximate 39 by 39 by 3-1/2 inches.

5.1.1.1.2 Frame. The knocked-down frame shall be so nested to approximately 50-1/2 by 38 by 4-3/4 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

5.1.1.1.3 Platform. No further preservation required.

5.1.1.2 Ground type.

5.1.1.2.1 Tent. The tent shall be laid out flat and folded in thirds lengthwise; then fold again in quarters to approximate dimensions of 30 by 30 by 5 inches.

5.1.1.2.2 Frame. The frame shall be laid out flat with curve facing up; the knocked-down legs shall be cross-diagonal placed within the square of frame, with all lines tucked in the square.

5.1.2 Commercial preservation. The tent, frame or platform shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. One complete ground type or aerial type tent or components of one type, preserved as specified in 5.1, shall be packed in a cleated plywood shipping container conforming to overseas type, style optional of PPP-B-601. Each box shall be closed and reinforced in accordance with PPP-B-601.

5.2.2 Level B packing. One complete ground type or aerial type tent or components of one type, preserved as specified in 5.1, shall be packed in a cleated plywood shipping container conforming to domestic type, style optional of PPP-B-601. Each box shall be closed and reinforced in accordance with PPP-B-601.

5.2.3 Commercial packing. Ground or aerial tents, preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), tents packed in fiberboard boxes as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The types I and II tents with matching frames are intended to provide protection from various weather conditions when used by aerial or ground (or below ground) electrical cable splicers.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Cover, protective
Electrical cables, shelters, and weather protection

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 82

Preparing activity:

Army - GL

(Project 8340-0528)

Review activities:

Navy - YD, MC

User activity:

Army - EL

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-43764A	2. DOCUMENT DATE (YYMMDD) 1990 July 25

3. DOCUMENT TITLE
TENTS, CABLE SPLICER

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME U.S. Army Natick RD&E Center	b. TELEPHONE (Include Area Code) (1) Commercial: 508-651-5221 (2) AUTOVON: 256-5221
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-ES Natick, MA 01760-5014	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil - Downloaded: 2025-10-21T22:15Z
Check the source to verify that this is the current version before use.