MIL-J-27028A(USAF)
13 April 1962
Superseding
MIL-J-27028(USAF)
29 December 1961

MILITARY SPECIFICATION

JACK KIT, HYDRAULIC, HAND KMU-128/E

1. SCOPE. This specification establishes the requirements for one type of Jack Kit designated as the KMU-128/E, hereafter referred to as the kit. The kit is intended for mating the MHU-29/C Clip-In Subassembly to its weapon. (See 6.1)

2. APPLICABLE DOCUMENTS. The following documents of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

JAN-P-100	Packing and Packaging for Overseas Shipment, General Specification
MIL-P-116	Preservation, Methods Of
MIL-E-4970	Environmental Testing, Ground Support Equipment, General Specification For
MIL-T-9107	Test Reports, Preparation Of
MIL-D-70327	Drawings, Engineering and Associated Lists

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Air Force

61J13120	Jack Kit, Hydraulic, Hand KMU-128/E
61C13128	Clamp, Assembly
61J13119	Chest Assembly - Jack Kit

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 PREPRODUCTION. This specification makes provisions for preproduction testing.

3.2 COMPONENTS. The kit shall consist of the following major components:

a. COMMERCIAL ITEMS. These components, or equal, shall be compatible with the components listed in 3.2.b.

	ITEM NAME	PART NUMBER	QUANTITY
(1)	Hydraulic Hand Pump	Blackhawk P-76	2
(2)	Gage	Blackhawk Z-721	2
(3)	Ram	Blackhawk R-151	2
(4)	Hose	Blackhawk Z-913	2
(5)	Adapter	Blackhawk P16.99	2

b. SPECIALLY DESIGNED COMPONENTS

	ITEM NAME	DRAWING NUMBER	QUANTITY
(1)	Clamp	61C13128	2
(2)	Chest Assembly	61 J 13119	1

3.3 DESIGN AND CONSTRUCTION. The jack kit shall be designed and constructed in conformance to drawing 61J13120 and subsidiary drawings.

3.3.1 CALIBRATION. The jack kit gages shall be calibrated in accordance with the procedures of drawing 61J13120.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.

3.4 INTERCHANGEABILITY. Parts functionally and dimensionally interchangeable shall be identified by the same part number. When parts are not interchangeable, the criteria listed in MIL-D-70327 shall apply and new drawings shall be made as required.

3.5 PERFORMANCE. The kit shall be capable of establishing the required tension in suspension bands of the MHU-29/C Clip-In Subassembly and maintaining the required tension until the bands are secured.

3.6 ENVIRONMENTAL REQUIREMENTS. The kit shall be capable of satisfactory operation during or after, as applicable, subjection to the following environmental conditions:

a. High temperature up to 71°C (160°F).

b. Low temperature down to -62°C (-80°F).

c. When properly packed, shock likely to be encountered in handling and transportation.

3.7 IDENTIFICATION OF PRODUCT. The kit, components, and assemblies shall be marked for identification in accordance with MIL-STD-130.

3.8 WORKMANSHIP. The kit shall be fabricated and finished in a manner such that criteria of appearance, fit, and adherence to specified tolerances shall be observed. These criteria shall apply to all external non-functioning parts (e.g., housings, cover plates, nameplates and marking) as well as to functional parts. Particular attention shall be given to marking of parts and assemblies, plating, welding, machine screw assemblage and freedom of parts from sharp edges which might damage adjacent equipment or injure personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 CLASSIFICATION OF TESTS. The inspection and testing of the kit and components shall be classified as follows:

a. Preproduction Tests

b. Acceptance Tests

4.2 PREPRODUCTION TESTING

4.2.1 PREPRODUCTION TEST SAMPLES. The preproduction test samples shall consist of items representative of the production equipment. They shall be tested at a laboratory designated by the procuring activity, or, when so stated in the contract, at the contractor's plant under the supervision of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.

4.2.2 PREPRODUCTION TEST REPORT. In the event that preproduction testing is performed at the contractor's plant, the contractor shall, after completion of the preproduction tests, prepare a preproduction test report according to MIL-T-9107 and furnish three complete copies of the report to the procuring activity.

4.2.3 PREPRODUCTION TESTS. Preproduction tests shall consist of all tests specified in this specification.

4.3 ACCEPTANCE TESTS. Acceptance tests shall consist of the following individual tests:

a. Examination of Product

b. Conformance to Drawings

c. Functional Test

4.3.1 REJECTION AND RETEST. When an item fails to satisfy the specified tests, no item still on hand or later produced shall be accepted until the extent and cause of failure is determined and resolved.

4.3.2 DEFECTS IN ITEM ALREADY ACCEPTED. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.4 TEST CONDITIONS. Test conditions shall be as described in each specific test in "4.5 TEST METHODS."

4.5 TEST METHODS

4.5.1 EXAMINATION OF PRODUCT. Each kit shall be examined visually to determine compliance with the requirements of this specification for which tests are not specified, including workmanship.

4.5.2 CONFORMANCE TO DRAWINGS. Each kit shall be inspected to determine conformance to the engineering drawings and all standards and specifications referenced therein.

4.5.3 FUNCTIONAL TEST. Each kit shall be tested for functional capability in the following manner:

a. Install each jack on a jig simulating service installation.

b. Operate the pump hand lever and gradually increase the pressure until gage reading is 3300 pounds. After a period of three minutes has elapsed, verify gage reading. An indicated pressure of less than 3000 pounds shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.

4.5.4 ENVIRONMENTAL TESTS. The requirement for operating equipment referred to in the environmental tests shall consist of the functional test. Failure to satisfy the functional test shall be considered failure to pass the environmental tests and cause for rejection.

4.5.4.1 Environmental testing of the kit shall consist of the following:

a. High Temperature

(1) STORAGE. Each jack shall be subjected to a storage high temperature test as described in Procedure II, MIL-E-4970.

(2) OPERATING. Each jack shall be subjected to an operating high temperature test as described in Procedure II, MIL-E-4970.

b. Low Temperature. Each jack shall be subjected to a low temperature test as described in Procedure II, MIL-E-4970.

c. The kit, in transport configuration, shall be subjected to a shock test as described in Procedure VII, MIL-E-4970. At the completion of this test, each jack shall be subjected to the functional test.

5. PREPARATION FOR DELIVERY

5.1 PACKAGING. The container for shipment and storage shall be the chest assembly, Drawing Number 61J13119. The containers internal bracing shall be in accordance with JAN-P-100.

5.2 SHIPPING. Shipping instructions and point of delivery will be furnished by the procuring activity.

5.3 MARKINGS. Marking of the shipping containers shall be in accordance with MIL-STD-129. The shipment marking nomenclature shall be:

JACK KIT, HYDRAULIC HAND KMU-128/E

6. NOTES

6.1 INTENDED USE. The Jack Kit, Hydraulic, Hand KMU-128/E is intended for applying the required tension to the suspension bands of the MHU-29/C single suspension clip-in subassembly. It cannot be used with any other clip-in subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.

6.2 ORDERING DATA. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Whether preproduction tests will be conducted by the procuring activity. (See 4.2.1)

c. Levels of preservation, packaging and packing.

6.2.1 PREPRODUCTION TEST SAMPLES. It is expected that the contract or purchase order will specify that two units representative of the production Jack Kit, Hydraulic, Hand KMU-128/E will be submitted to the procuring activity for test and evaluation. The invitation for bids, and the contract or purchase order should specify the point of inspection for these tests.

6.3 PRODUCTION DELIVERY. No production item should be delivered prior to approval of the preproduction samples.

6.4 DEFINITIONS

a. PREPRODUCTION TESTS. Preproduction tests are those tests performed prior to production on representative samples of the production equipment to demonstrate that the requirements meet the requirements of this specification.

b. ACCEPTANCE TESTS. Acceptance tests are those tests accomplished on representative samples of equipment submitted for acceptance under a contract to determine conformance to the requirements of this specification, and to determine that the equipment is equivalent to the performance and construction of the approved preproduction samples.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

SWVSC
MHJ/pfg

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:39Z
Check the source to verify that this is the current version before use.