
MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, HIGH DENSITY, QUICK DISCONNECT, ENVIRONMENT RESISTING: RECEPTACLE, FLANGE MOUNT, INDIVIDUAL RELEASE, CRIMP-TYPE CONTACTS. CLASS A, AND F. (SERIES 3).

THE COMPLETE REQUIREMENTS FOR PROCURING THE CONNECTOR DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF SPECIFICATION MIL-C-0081511.

THIS SPECIFICATION IS MANDATORY FOR USE BY ALL ACTIVITIES OF THE DEPARTMENT OF THE NAVY.



INCHES	MM	INCHES	MM	INCHES	MM
.003	.08	.073	1.85	.143	3.63
.005	.13	.075	1.91	.153	3.89
.006	.15	.090	2.29	.230	5.84
.010	.25	.094	2.39	.894	22.71
.015	.38	.116	2.95	.906	23.01
.016	.41	.125	3.18	1.298	32.97
.065	1.65	.126	3.20	1.318	33.48
.067	1.70	.200	5.08	1.327	33.71
.035	.89			1.347	34.21

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:34Z
Check the source to verify that this is the current version before use.

TABLE I.

SHELL SIZE	B DIA	D DIA	F THREAD	G	H	P DIA	AR° BSC	BR° BSC	CR° BSC	DR° BSC	FF RAD	EE° BSC POSITION 1	2	3	4	5	6
8	.553 (14.05) .547 (13.89)	.430 (10.92) .424 (10.77)	1/2-28 UNEF-2A	.820 (20.83) .804 (20.42)	.599 (15.21) .589 (14.96)	.640 (16.26) .630 (16.00)	105	140	215	265	.120 (3.05) .100 (2.54)	60	46	43	60	89	43
10	.678 (17.22) .672 (17.07)	.555 (14.10) .549 (13.94)	5/8-28 UN-2A	.945 (24.00) .929 (23.60)	.724 (18.39) .714 (18.14)	.765 (19.43) .755 (19.18)	95	141	208	236	.120 (3.05) .100 (2.54)	53	87	51	77	87	87
14	.928 (23.57) .922 (23.42)	.805 (20.45) .799 (20.29)	7/8-28 UN-2A	1.133 (28.78) 1.117 (28.37)	.911 (23.14) .901 (22.89)	1.015 (25.78) 1.005 (25.53)	95	141	208	236	.120 (3.05) .100 (2.54)	53	87	51	77	87	87
16	1.054 (26.77) 1.048 (26.62)	.930 (23.62) .924 (23.47)	1 - 28 UN-2A	1.258 (31.95) 1.242 (31.55)	.974 (24.74) .964 (24.49)	1.140 (28.96) 1.130 (28.70)	80	142	196	293	.150 (3.81) .130 (3.30)	98	98	98	98	98	98
18	1.178 (29.92) 1.172 (29.77)	1.055 (26.80) 1.049 (26.64)	1 1/8-28 UN-2A	1.351 (34.32) 1.335 (33.91)	1.067 (27.10) 1.057 (26.85)	1.265 (32.13) 1.255 (31.88)	80	142	196	293	.150 (3.81) .130 (3.30)	98	98	98	98	98	98
20	1.303 (33.10) 1.297 (32.94)	1.180 (29.97) 1.174 (29.82)	1 1/4-28 UN-2A	1.475 (37.47) 1.459 (37.06)	1.161 (29.49) 1.151 (29.24)	1.390 (35.31) 1.380 (35.05)	80	142	196	293	.160 (4.07) .130 (3.30)	98	98	98	98	98	98
22	1.428 (36.27) 1.422 (36.12)	1.305 (33.15) 1.299 (32.99)	1 3/8-28 UN-2A	1.570 (39.88) 1.554 (39.47)	1.255 (31.88) 1.245 (31.62)	1.515 (38.48) 1.505 (38.23)	80	142	196	293	.160 (4.07) .130 (3.30)	98	98	98	98	98	98
24	1.553 (39.45) 1.547 (39.29)	1.430 (36.32) 1.424 (36.17)	1 1/2-28 UN-2A	1.711 (43.46) 1.695 (43.05)	1.380 (35.05) 1.370 (34.80)	1.640 (41.66) 1.630 (41.40)	80	142	196	293	.160 (4.07) .130 (3.30)	98	98	98	98	98	98

NOTES:

1. DIMENSIONS ARE IN INCHES.
2. MILLIMETERS ARE IN PARENTHESES.
3. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
4. DIMENSIONS ARE AFTER PLATING.
5. NORMAL MATING KEYWAY POSITION SHOWN. FOR ALTERNATE POSITIONS SEE MIL-C-0081511, FIGURE 8.
6. COLOR BANDS: COLOR BLUE .100 MAX. WIDE, MUST BE VISIBLE WHEN MOUNTED.
7. ARRANGEMENTS CONTAINING SIZE 12 CONTACTS, INSERT PROTRUSION .070/.020.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

DIMENSIONS AND CONFIGURATION: SEE FIGURE AND TABLE I.

SERIES: 3

CLASSES: A AND F.

SHELL SIZE: SEE TABLE II.

INSERT ARRANGEMENT: SEE SUPPLEMENT FOR MS SHEET CORRESPONDING TO DESIRED SHELL SIZE.

CONTACTS: STYLE P OR S, CRIMP TYPE.

SHELL POLARIZATION: 1 THRU 6, KEY POSITION.

WEIGHT: SEE TABLE II.

MARKING: PART NUMBER ON SHELL.

MATING COUNTERPART: PLUG CONNECTORS SPECIFIED IN MIL-C-81511/26, /38, AND MIL-C-0081511/46.

INSERTION AND REMOVAL TOOL: AS SPECIFIED IN MS3160

PART NUMBER: THE PART NUMBER SHALL CONSIST OF M81511/41 TOGETHER WITH THE APPLICABLE CODES FOR CLASS, SHELL SIZE, INSERT ARRANGEMENT, CONTACT STYLE, AND KEY POSITIONS. INFORMATION CONCERNING THE FORMULATION OF THE PART NUMBER CAN BE FOUND IN MIL-C-0081511.

TABLE II.

SHELL SIZE	WEIGHT (REF) 1/ (POUNDS)
24 (CODE J)	
22 (CODE H)	
20 (CODE G)	
18 (CODE F)	TO BE DETERMINED
16 (CODE E)	
14 (CODE D)	
10 (CODE B)	
8 (CODE A)	

1/ REMOVABLE CRIMP CONTACTS NOT INCLUDED IN WEIGHT. (SEE CONTACT DRAWINGS FOR WEIGHT OF PIN AND SOCKET CONTACT.)

CUSTODIAN:
NAVY - AS

PREPARING ACTIVITY:
NAVY - AS

REVIEW ACTIVITY:
NAVY - EC

(PROJECT NO. 5935-N783-4)

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-703-020/207

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:34Z
Check the source to verify that this is the current version before use.