MIL-C-81511/51A(NAVY)
7 January 1977
SUPERSEDING
MIL-C-0081511/51(NAVY)
18 October 1971

MILITARY SPECIFICATION SHEET


CONNECTORS, ELECTRICAL, CIRCULAR, HIGH DENSITY, QUICK DISCONNECT, ENVIRONMENT RESISTING: RECEPTACLE, FLANGE MOUNT, INDIVIDUAL RELEASE, CRIMP-TYPE CONTACTS CLASS A, F AND W (SERIES 4)

Ⓐ

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-81511.

THIS SPECIFICATION INACTIVE FOR NEW DESIGN AFTER 30 APRIL 1975. SEE MIL-STD-1353.



INCHES	MM	INCHES	MM	INCHES	MM
.003	.08	.035	.89	.126	3.20
.005	.13	.073	1.85	.200	5.08
.006	.15	.075	1.91	.230	5.84
.010	.25	.090	2 29	.765	19.43
.015	.38	.094	2 39	.775	19.69
.016	.41	.116	2.95	1.167	29.64
.065	1.65	.175	3 18	1.187	30.15

Ⓐ denotes changes

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:34Z
Check the source to verify that this is the current version before use.

TABLE I.

SHELL SIZE	B DIA	D DIA	F THREAD	G	H	P DIA	AR° BSC	BR° BSC	CR° BSC	DR° BSC	FF RAD	EE° BSC POSITION					
												1	2	3	4	5	6
8	.553 (14.05) .547 (13.89)	.430 (10.92) .424 (10.77)	1/2-28 UNEF-2A	.820 (20.83) .804 (20.42)	.599 (15.21) .589 (14.96)	.640 (16.26) .630 (16.00)	128°				.120 (3.05) .100 (2.54)	40	40	40	40	40	40
10	.678 (17.22) .672 (17.07)	.555 (14.10) .549 (13.94)	5/8-28 UN-2A	.945 (24.00) .929 (23.60)	.724 (18.39) .714 (18.14)	.765 (19.43) .755 (19.18)	105°	140°	215°	265°	.120 (3.05) .100 (2.54)	60	46	46	60	89	60
14	.928 (23.57) .922 (23.42)	.805 (20.45) .799 (20.29)	7/8-28 UN-2A	1.133 (28.78) 1.117 (28.37)	.911 (23.14) .901 (22.89)	1.015 (25.78) 1.005 (25.53)	105°	140°	215°	265°	.120 (3.05) .100 (2.54)	60	46	46	60	89	60
16	1.054 (26.77) 1.048 (26.62)	.930 (23.62) .924 (23.47)	1 - 28 UN-2A	1.258 (31.95) 1.242 (31.55)	.974 (24.74) .964 (24.49)	1.140 (28.96) 1.130 (28.70)	105°	140°	215°	265°	.150 (3.81) .130 (3.30)	50	50	50	50	50	50
18	1.178 (29.92) 1.172 (29.77)	1.055 (26.80) 1.049 (26.64)	1 1/8-28 UN-2A	1.351 (34.32) 1.335 (33.91)	1.067 (27.10) 1.057 (26.85)	1.265 (32.13) 1.255 (31.88)	105°	140°	215°	265°	.150 (3.81) .130 (3.30)	50	50	50	50	50	50

NOTES:

1. DIMENSIONS ARE IN INCHES.
2. MILLIMETERS ARE IN PARENTHESES.
3. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
4. DIMENSIONS ARE AFTER PLATING.
5. NORMAL MATING KEYWAY POSITION SHOWN. FOR ALTERNATE POSITIONS SEE MIL-C-81511, FIGURE 4.
6. FOR SHELL SIZES 20, 22 AND 24 USE MIL-C-81511/21 OR MIL-C-81511/41.
7. COLOR BAND: COLOR BLUE .100 MAX. WIDE, MUST BE VISIBLE WHEN MOUNTED.
8. ARRANGEMENTS CONTAINING SIZE 12 CONTACTS, INSERT PROTRUSION .070/.020.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure and table I.

Series: 4.

Ⓐ Classes: A, F and W.

Shell size: See table II.

Insert arrangement. See supplement for MS sheet corresponding to desired shell size.

Contacts: Style P or S, crimp type.

Shell polarization: 1 thru 6, key position.

Weight: See table II.

Marking: Part number on shell.

Mating counterpart: Plug connectors specified in MIL-C-81511/6, /34, and /56.

Insertion and removal tool: As specified in MS3160.

Part number: The part number shall consist of M81511/51 together with the applicable codes for class, shell size, insert arrangement, contact style, and key positions. Information concerning the formulation of the part number can be found in MIL-C-81511.

TABLE II. Shell size and weight.

Shell size	Weight (ref) 1/ (pounds)
18 (Code F) 16 (Code E) 14 (Code D) 10 (Code B) 8 (Code A)	To be determined

1/ Removable crimp contacts not included in weight. (See contact drawings for weight of pin and socket contact.)

Custodian:
Navy - AS

Review activities:
Navy - EC, OS, SH
DSA - ES

User activities:
Navy - MC

Preparing activity:
Navy - AS

Agent.
DSA - ES

(Project 5935-N023-8)

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-81511/51A(Navy) Connectors, Electrical, Circular, High Density, Quick

NAME OF ORGANIZATION AND ADDRESS Disconnect

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:34Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

Naval Air Engineering Center
Lakehurst, NJ 08733

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID

DOD
316

Engineering Specification and Standards Department (Code
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:34Z
Check the source to verify that this is the current version before use.