MIL-L-52056D
AMENDMENT 1
29 April 1986

MILITARY SPECIFICATION

LIGHT, SIGNAL, SURVEYING: SELF-ILLUMINATED, WITH

CARRYING CASE, FOR USE WITH RANGE POLE

This amendment forms a part of MIL-L-52056D, dated 16 April 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under SPECIFICATIONS, MILITARY, add:

"MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant."

2.1.1, under STANDARDS, MILITARY, add:

"MIL-STD-130 - Identification Marking of U.S. Military Property."

PAGE 3

3.1, line 2, delete "in accordance with" and substitute "similar to".

3.1.1, delete and substitute: "3.1.1 Drawings. The drawings forming a part of this specification are information drawings (see 6.6)."

PAGE 4

3.6, delete and substitute: "3.6 Identification marking. The target light carrying case shall be identified in accordance with MIL-STD-130."

3.7, delete and substitute:

"3.7 Instruction plate. Each target light shall have an instruction plate. The plate shall state: REMOVE BATTERIES WHEN NOT IN USE OR WHEN OPERATING FROM AN EXTERNAL POWER SOURCE. The plate shall be attached by screws, bolts, rivets, or by adhesive conforming to MMM-A-134, epoxy resin, type I."

AMSC N/A FSC 6675
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.8, delete and substitute:

"3.8. Treatment and painting. Unless otherwise specified (see 6.2), the portions of the target light normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G as applicable. Unless otherwise specified (see 6.2) top coat color shall be camouflage green 383 conforming to MIL-C-46168."

PAGE 5

4.1.2, delete in its entirety.

4.3.1, delete the following words: "or for performing the disassembly inspection specified in 4.1.2."

4.3.2, delete the following words: "or for performing the inspection specified in 4.1.2."

4.4.2, line 2, delete "1.5 percent" and substitute "1.0 percent."

PAGE 6

4.5.1, defect 101, delete in its entirety.

Defect 111, delete "or fungus-resistant treatment".

Add defect 116 as follows:

"116. Color not as specified."

PAGE 8

4.6.1.2, add the following words: "AQL shall be 1.0 percent defective."

PAGE 9

6.2, after d. add:

"e. When painting shall be other than specified (see 3.8).
f. Color when other than as specified (see 3.8)"

After 6.5, add new paragraph:

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:06Z
Check the source to verify that this is the current version before use.

"6.6 Information drawings. The drawings forming a part of this specification are information drawings. However, no deviation from dimensions, tolerances, materials, or processes coded as quality assurance provisions (QAPs) and no deviation from specified materials is permissible without prior approval of the contracting officer. Drawings, except as noted above, are provided for reference only and may be deviated from at the discretion of the contractor. Any and all deviations made under this provision shall be totally at the contractor's risk and shall in no way relieve him from the responsibility to provide a target light which complies with all requirements of the contract and this specification, and the intended end use. Any data (including but not limited to shop drawings, layouts, flow sheets, and processing procedures) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative."

Custodian:
Army - ME

Preparing activity
Army - ME

Review activities:
Navy - MC
DLA - GS

Project 6675-0801

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:06Z
Check the source to verify that this is the currentversion before use.