QAT

MIL-P-63430(AR)
AMENDMENT 2
26 January 1982
SUPERSEDING
AMENDMENT 1
10 June 1981

MILITARY SPECIFICATION

PROJECTILE, 155MM, TEST, NON-HAZ, M718/M741 TYPES
LOADING, ASSEMBLING AND PACKING OF

This Amendment forms a part of Military Specification MIL-P-63430(AR), dated 1 December 1980, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

* Add paragraph 3.12 as follows:

"3.12: Shorting bar resistance. There shall be no more than one (1) ohm resistance to the shorting bar loop when measured between the output terminal to ground."

PAGE 9

4.4.1: Inspection lot formation.

* Subparagraph b., change wording to read: "Expulsion charge assemblies from one lot interfix, from one manufacturer."

* Subparagraph e., add; "-1 and -2 after "Electronic Assemblies".

PAGE 11

4.4.2.2: Electronic and primer assembly (M718)

* Major defect 102, change to read: "Bushing missing"

PAGE 12

* 4.4.2.3; Electronic and primer assembly (M741)

Major defect 102, change to read: "Bushing missing"

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:52Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.4: Battery check and insulator test point installation.

* Add major defect 104: "Resistance of shorting bar, improper, 100%, 3.12, 4.5.6"

PAGE 17

4.4.2.7; Mine, test, non-haz (during assembly) (M741)

* Major defect 113, change to read: "Retaining ring height improper"

PAGE 18

4.4.2.8: Mine, test, non-haz (during assembly) (M718)

* Major defect 113, change to read: "Retaining ring height improper"

PAGE 21

4.4.2.10, Projectile, 155MM, test, non-haz, M741 type (prior to inserting mines into projectile)

* Critical defect 1, change to read: "...being assembled into projectile..."

* Critical defect 2, change to read: "...being assembled into projectile..."

* Critical defect 3, change to read: "mine color code improper, or HE mine with non-haz color code"

PAGE 23

4.4.2.12: Projectile, 155MM, test, non-haz, M741 type (prior to assembling lifting plug)

* Major defect 108: Delete

PAGE 24

4.4.2.13: Projectile, 155MM, test, non-haz, M741 type

Critical defect 1, change wording,

from: "Nomenclature on body, letter in triangle and stamped number on base not consistent"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:52Z
Check the source to verify that this is the current version before use.

to: "Nomenclature on body and letter in triangle not consistent"

* Major defect 102, change to read: "Lifting plug missing or improper"

* Major defect 103, change as follows:

No. of sample units, delete: "See 4.4.3.5"
AQL, add: "0.40%"

* Minor defect 201, change to read: "...1/4 square inch"

PAGE 26

4.4.2.14: Projectile, 155MM, test, non-haz, M718 type (prior to inserting mines into projectile)

* Critical defect 1, change to read: "...being assembled into projectile..."

* Critical defect 2, change to read: "...being assembled into projectile..."

* Critical defect 3, change to read: "Mine color code improper, or HE mine with non-haz color code"

PAGE 29

4.4.2.17: Projectile, 155MM, test, non-haz, M718 type

Critical defect 1, change wording,

from: "Nomenclature on body, letter in triangle and stamped number on base not consistent"

to: "Nomenclature on body and letter in triangle not consistent"

* Major defect 102, change to read: "Lifting plug missing or improper"

* Major defect 103, change as follows:

No. of sample units, delete: "See 4.4.3.5"
AQL, add: "0.40%"

* Minor defect 201, change to read: "...1/4 square inch"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:52Z
Check the source to verify that this is the current version before use.

PAGE 31

4.4.2.18: Pellet (loaded)

* Major defect 201: Delete

PAGE 33

* 4.4.3.5, Lifting plug torque: Delete paragraph

* 4.4.3.7, Expulsion charge assembly: Delete paragraph in its entirety

PAGE 35

4.5.5, Radiographic examination of test mines:

* Change title to read: "Radiographic examination of test mines and projectiles"

* Change, "DRDAR-QAA-M" to "DRDAR-QAT-M"

* Add paragraph 4.5.6 as follows:

4.5.6: Shorting bar resistance. The resistance of each shorting bar circuit shall be measured between the test points E3 and TP9, using an approved ohmmeter. Observation shall be made for compliance with the requirement of 3.14.

PAGE 36

6.3: Submission of designs for approval.

* Change, "DRDAR-QAA-I" to "DRDAR-QAT-I"

6.4: Submission of test data and data cards.

* Change, "DRDAR-QAA-M" to "DRDAR-QAT-M"

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A628)

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:52Z
Check the source to verify that this is the current version before use.