MILITARY SPECIFICATION SHEET

ELECTRON TUBES, RECEIVING

TYPES 25L6GT AND 50L6GT

The complete requirements for procuring the electron tubes described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Amplifier, beam power

Outline	---	9-11 (EIA) or 9-41 (EIA)
Base	---	See note 1
Envelope	---	T9
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8
Element	---	nc	h	a	g2	g1	h	k, g3

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ik	Pp	Pg2	(B) Ehk	(B) Alt
Unit:	V	Vdc	Vdc	Vdc	mAdc	W	W	v	ft
Maximum:									
25L6GT:	27.5	220	---	125	125	11	1.4	100	See note 3
50L6GT:	55.0	220	---	125	125	11	1.4	100	See note 3
Minimum:									
25L6GT:	22.5	---	---	---	---	---	---	---	---
50L6GT:	45.0	---	---	---	---	---	---	---	---
TEST CONDITIONS:									
25L6GT:	25.0	200	-8	110	---	---	---	---	---
50L6GT:	50.0	200	-8	110	---	---	---	---	---

GENERAL:

Qualification - Not required

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:28Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
	Quality conformance inspection, part 1							
1266	Total grid current	See note 2	0.65	II	Ic1	0	-3.0	μAdc
1256	Electrode current (anode)		0.65	II	Ib	35	67	mAdc
1341	Power output	Esig = 5.6 Vac; Rp = 3,000 ohms (see note 2)	0.65	II	Po	3.2	---	W
1246	Audio frequency noise	Esig = 500 mVac; Rp = 2,000 ohms	0.65	II	EB	---	17	vu
1231	Emission	Eb = Ec1 = Ec2 = 30 Vdc	0.65	II	Is	180	---	mAdc
(B) 1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Ec1 = -13.5 Vdc; Rp = 2,000 ohms	---	---	Ep	---	1.000	mVac
1301	Heater current							
	Type 25L6GT		---	---	If	275	325	mA
	Type 50L6GT		---	---	If	138	162	mA
(B) 1336	Heater-cathode leakage		---	---	Ihk	---	75	μAdc
1256	Electrode current (screen)		---	---	Ic2	0.4	5.4	mAdc
1306	Transconductance		---	---	Sm	7,100	12,000	μmhos
(B) 1101	Secureness of base, cap, or insert		---	---	---	---	---	---
(B) 1111	Base pin solder depth		---	---	---	---	---	---
(B) 1211	Insulation of electrodes		4.0	S3	---	---	---	---
(B) 1126	Glass envelope strain		2.5	I	---	---	---	---
(B) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
---	Life-test provisions	Group A: Ehk = 100 V	---	---	---	---	---	---
---	Life-test end point (500 hours)	Power output	---	---	Po	2.1	---	W

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:28Z
Check the source to verify that this is the current version before use.

NOTES:

1. The base shall be phenolic and one of the following:

   (a) Intermediate shell octal 7-pin, B7-7
   (b) Intermediate shell octal 6-pin, B6-81
   (c) Short intermediate shell octal 7-pin, B7-59
   (d) Short intermediate shell octal 6-pin, B6-84

2. This test to be performed at the conclusion of the holding period.

3. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL
Navy -
Air Force - 11, 80
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-57)

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:28Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:28Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 20260-15T13:28Z
Check the source to verify that this is the current version before use.