MIL-E-1/617A
24 September 1968
SUPERSEDING
MIL-E-1/617
23 February 1954

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 35L6GT 1/

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Beam power amplifier

Outline	---	9-11 or 9-41 (EIA) (A)
Base	---	B6-81, B6-84, B7-7, or B7-59
Envelope	---	T9
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8
Element	---	nc	h	p	g2	g1	h	k, g3

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Pp	Pg2	Ehk	Alt
Unit:	V	Vdc	Vdc	Vdc	W	W	v	ft
Maximum:	38.5	220	---	125	9.3	1.1	100	10,000
Minimum:	31.5	---	---	---	---	---	---	---
TEST CONDITIONS:	35.0	200	-8	110	---	---	---	---

GENERAL:

Qualification - Required

1/ Formerly JAN-35A5, 35L6GT
(see note 1)

(A) denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR GROUP	SYMBOL	LIMITS		UNIT
						MIN.	MAX.	
	Quality conformance inspection, part 1							
1266	Total grid current	See note 2	0.65	II	Ic1	0	-3.0	μAdc
1256	Electrode current (anode)		0.65	II	Ib	30	52	mAdc
1341	Power output	Esig = 5.6 Vac; Rp = 4,500 ohms	0.65	II	Po	2.5	---	W
Ⓐ 1246	Audio frequency noise	Esig = 300 mVac; Rp = 2,000 ohms (see note 3)	0.65	II	---	---	---	---
1231	Emission	Eb = Ec1 = Ec2 = 20 Vdc (see note 2)	0.65	II	Is	90	---	mAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
---	Visual and mechanical inspection criteria		---	---	---	---	---	---
---								
---	Dimensions	Outlines 9-11 or 9-41; dimensions A thru D	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Ec1 = -15 Vdc; Rp = 2,000 ohms	6.5	S3	Ep	---	500	mVac
1301	Heater current		6.5	S3	If	138	162	mA
1336	Heater-cathode leakage		6.5	S3	Ihk	---	75	μAdc
1256	Electrode current (screen)		6.5	S3	Ic2	0.4	4.2	mAdc
1306	Transconductance		6.5	S3	Sm	4,400	7,400	μmhos
1101	Secureness of base and base insert		6.5	S3	---	---	---	---
1111	Base pin solder depth		6.5	S3	---	---	---	---
1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Life-test provisions (intermittent) (500 hours)	Group A; Ehk = 100 V	---	---	---	---	---	---
---	Life-test end points (intermittent) (500 hours)	Power output or Transconductance	--- ---	--- ---	Po Sm	1.6 3,850	--- ---	W μmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

NOTES:

1. Tube type 35A5 has been deleted from this tube specification sheet. Tubes for replacement purposes will be procured to EIA Release Number 152, type 35A5.
2. This test to be performed at the conclusion of the holding period.
3. The rejection level shall be set at the VU meter reading obtained during calibration.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME, AV
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2289-82)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.