MIL-E-1/626B
29 June 1970
SUPERSEDING
MIL-E-1/626A
21 January 1959

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 1U4

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, miniature, rf sharp cutoff

(B) Outline --- 5-2 (EIA)

Base --- E7-1

Envelope --- T5-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	-f, g3, sd	a	g2	nc	-f, g3, sd	g1	+f

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Ec1	Ec2	Eb	Ik	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	mAdc	ft
Maximum:	1.6	---	100	100	6.5	10,000
Minimum:	1.2	---	---	---	---	---
TEST CONDITIONS:	1.4	0	90	90	---	---

GENERAL:

Qualification - Not required

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:30Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	Ec1 = -2 Vdc; Eb = Ec2 = 135 Vdc (see note 2)	0.65	II	Ic1	0	-1.0	μAdc
1256	Electrode current (1) (anode)		0.65	II	Ib	1.0	2.1	mAdc
1306	Transconductance (2)	Ef = 1.1 Vdc (see note 2)	0.65	II	Sm	610	1,080	μmhos
1251	Audio frequency noise and microphonics	See note 1	0.65	II	EB	---	15	VU
(B)1201	Short and discontinuity detection		0.40	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Rp = 10,000 ohms	---	---	Ep	---	100	mVac
1301	Filament current		---	---	If	44	56	mA
1256	Electrode current (2) (anode)	Ec1 = -4.5 Vdc	---	---	Ib	0	30	μAdc
1256	Electrode current (screen)		---	---	Ic2	0.28	0.62	mAdc
1306	Transconductance (1)		---	---	Sm	720	1,080	μmhos
1211	Insulation of electrodes		4.0	S3	R	100	---	Meg
1331	Direct-interelectrode capacitance	Shield No. 316 Shield No. 316 Shield No. 316	---	---	Cgp Cin Cout	--- 2.6 6.0	0.01 4.1 8.6	pF pF pF
(B)1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
---	Life-test provisions	Group A; Ef = 1.4 Vac or Vdc with equivalent Ec	---	---	---	---	---	---
---	Life-test end point (500 hours)	Transconductance (1)	---	---	Sm	540	---	μmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

NOTES:

1. Ebb = Ecc2 = 135 Vdc; Rp = 1.0 Meg; Rg1 = 1.5 Meg; Rg2 = 4.7 Meg (by-passed with 0.1 μF capacitor to -f). Set amplifier gain for 50 mW output with Esig = 200 mVac.

2. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - EL
Navy -
Air Force - 11, 85
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Army - EL

Agent: DSA - ES

(Project 5960-2401-51)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-E-1/626B, ELECTRON TUBE, RECEIVING TYPE 1U4

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-PM 1068-68

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:30Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL-TD-SS
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:30Z
Check the source to verify that this is the current version before use.