MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 1U4

This amendment forms a part of Military Specification Sheet MIL-E-1/626B, dated 29 June 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Quality Conformance inspection, part 1, Method 1251, Audio frequency noise and microphonics:
Delete method 1251 and all columnar data and substitute:

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
1246	Audio frequency noise	Eca1 = 200 mVac = 50 mW; 0 vu = 420 mVac; Ec1 = -10.0 Vdc; Rg2 = 1.0 Meg bypassed by 0.1 µF; Rp = 0.2 Meg (see note 1)	1.0	II	EB	---	0	vu

Quality conformance inspection, part 1, Method 1201, Short and discontinuity detection, under conditions column: Add "40 G".

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG
Air Force - 11, 19

Preparing activity:
Army - EL

Agent:
DLA - ES

(Project 5960-3149)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.