MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

(D) TYPE 2AS15

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the electron tube described herein shall consist of this specification sheet and the latest issue of MIL-E-1.

DESCRIPTION: Diode, emission limited

Outline	---	9-7 or 9-11 (EIA)
Base	---	B8-6 or B8-46
Envelope	---	T9
Cathode	---	Tungsten filament

Base connections:

(D)

Pin No.	---	1	2	3	4	5	6	7	8
Element (see note 1)	---	nc	f	Jumper between 3 and 4		a	nc	f	nc

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ebb	ib	Ib	i(surge)	Alt
Unit:	V ac	V dc	kV dc	ma	mA dc	ma	ft
Maximum:	2.0	300	1.5	2.0	0.5	10	(see note 2)
Minimum:	1.5	---	---	---	---	---	---
TEST CONDITIONS:	1.8	500	---	---	---	---	---

GENERAL:

Qualification - Not required

(D) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:30Z
Check the source to verify that this is the current version before use.

	METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
		Quality conformance inspection, part 1						
	1256	Electrode current (1) (anode)	3		Ib	410	900	µA dc
	1256	Electrode current (2) (anode)	3,4	Eb = 300 V dc	Ib	310	680	µA dc
	1201	Short and discontinuity detection	5		---	---	---	---
		Quality conformance inspection, part 2						
(D)	1041	Shock		500G; No voltages applied	---	---	---	---
	1301	Heater current		Ef either ac or dc	If	310	345	mA
	1211	Insulation of [illegible]	6		---	---	---	---
	1126	Glass envelope strain	7		---	---	---	---
	1101	Secureness of base, cap, or insert			---	---	---	---
	1111	Base pin solder depth			---	---	---	---
	1105	Permanence of marking			---	---	---	---
(D)	1216	Base material insulating quality			---	---	---	---
		Quality conformance inspection, part 3						
	1501	Intermittent life		Group C	---	---	---	---
	---	Intermittent life-test end point (500 hours)						
	1256	Electrode current (1) (anode)			Ib	400	---	µA dc

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

(D) NOTES:

1. Safety feature between filament and anode. At parting of filament, filament shorts to anode.
2. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage in MIL-E-1.
3. The AQL (percent defective) shall be 0.65, inspection level II.
4. The ratio of anode current at Eb = 500 V dc to anode current at Eb = 300 V dc shall be less than 5 to 3.
5. The AQL (percent defective) shall be 0.4, inspection level II.
6. The AQL (percent defective) shall be 4.0, inspection level S3.
7. The AQL (percent defective) shall be 4.0, inspection level I.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Navy - AS, OS, MC, CG
Air Force - 11, 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3334)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1984 — 708-040, A2808

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.