MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6K7

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Pentode, RF remote cutoff

Outline	---	8-4 (EIA)
Base	---	B7-22
Cap	---	C1-4, miniature
Envelope	---	MT8
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8	Cap
Element	---	sh	h	a	g2	g3	h	k	g1

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Esh	Pp	Pg2	Ehk	Alt
Unit:	V	Vdc	Vdc	Vdc	Vdc	Vdc	W	W	v	ft
Maximum:	6.9	330	---	140	0	0	3.0	0.4	100	Note 1
Minimum:	5.7	---	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	250	-3	100	0	---	---	---	---	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1266	Total grid current	2		0.65	II	Ic1	0	-1.0	µAdc
1256	Electrode current (anode)	-		0.65	II	Ib	4.9	9.1	mAdc
1306	Transconductance (1)	-		0.65	II	Sm	1,200	1,700	µmhos
1231	Emission	2	Eb = Ec1 = Ec2 = Ec3 = 30 Vdc	0.65	II	Is	45	---	mAdc
1201	Short and discontinuity detection	-		0.4	II	---	---	---	---
	Quality conformance inspection, part 2								
1031	Low-frequency vibration	-	Rp = 10,000 ohms	---	---	Ep	---	200	mVac
1301	Heater current	-		---	---	If	275	325	mA
1336	Heater-cathode leakage	-		---	---	Ihk	---	20	µAdc
1331	Direct-interelectrode capacitance	-	Without shield	---	---	Cgp	---	0.005	pF
						Cin	5.8	8.2	pF
						Cout	9.0	15.0	pF
1101	Secureness of base, cap, or insert	-		---	---	---	---	---	---
1111	Base pin solder depth	-		---	---	---	---	---	---
1211	Insulation of electrodes	-		4.0	S3	---	---	---	---
1256	Electrode current (screen)	-		---	---	Ic2	0.9	2.4	mAdc
1306	Transconductance (2)	-	Ec1 = -35 Vdc	---	---	Sm	1	30	µmhos
1105	Permanence of marking	-		---	---	---	---	---	---
	Quality conformance inspection, part 3								
1501	Intermittent life	-	Group A; Ehk = 100 V	---	---	---	---	---	---
---	Intermittent life-test end point (500 hours)								
1306	Transconductance (1)	-		---	---	Sm	950	---	µmhos

NOTES:

1. See "Reduced pressure (altitude) rating" paragraph in the basic document.
2. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - MU
Navy - AS, OS, MC, CG, SH

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-2903)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:30Z
Check the source to verify that this is the current version before use.