MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 9002

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Triode, miniature, UHF

Outline	---	5-1 (EIA), except height equals 1-13/16 inches maximum (B)
Base	---	E7-1
Envelope	---	T5-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	p	k	h	h	p	g	k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Pp	Ehk	Alt
Unit:	V	Vdc	Vdc	W	v	ft
Maximum:	6.9 (see note 1)	275	0	1.8	90	(see note 2) (B)
Minimum:	5.7	---	---	---	---	---
TEST CONDITIONS:	6.3	250	-7	---	---	---

REQUIREMENT OR TEST:

GENERAL

3.2	Qualification - Required	E-50.3	Preheating
E-50.2	Holding period	5.	Preparation for delivery

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:31Z
Check the source to verify that this is the current version before use.

MIL-STD-750 method	Requirement or test	Conditions	AQL (percent defective)	Inspection level or code	Symbol	Limits min	Limits max	Unit
	Quality conformance inspection, part 1							
1266	Total grid current	See note 3	0.65	II	Ic	0	-1.0	µAdc
1256	Electrode current (1) (anode)		0.65	II	Ib	3.6	8.6	mAdc
1256	Electrode current (2) (anode)	Ec = -50 Vdc; Eb = 150 Vdc	0.65	II	Ib	0	50	µAdc
1306	Transconductance (1)		0.65	II	Sm	1,700	2,800	µmhos
1231	Emission current	Eb - Ec = 15 Vdc (see note 3)	0.65	II	Is	20	---	mAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
Appendix D, 20(a), 30	Visual and mechanical inspection criteria		---	---	---	---	---	---
Appendix D, 20(b)	Dimensions	Outline 5-1; dimensions A, C, D, and E (C = 1-13/16 inch max)	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
1301	Heater current		6.5	L6	If	140	160	mA
(B) 1336	Heater-cathode leakage		6.5	L6	Ihk	---	20	µAdc
1311	Anode resistance		6.5	L6	rp	8,400	14,800	ohms
1306	Transconductance (2)	Ef = 5.5 V	6.5	L6	Sm	1,450	---	µmhos
1331	Direct-interelectrode capacitance	Shield No. 316 Without shield Without shield	6.5	Code E	Cgp Cin Cout	1.1 0.95 0.75	1.6 1.8 1.45	pf pf pf
1121 and 4.3.2	Base strain		---	---	---	---	---	---
2126	Glass strain		4.0	I	---	---	---	---
1031	Low-frequency vibration	Rp = 10,000 ohms	6.5	L6	Ep	---	300	mVac
1211	Insulation of electrodes		4.0	L6	R	10	---	Meg
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501 and 4.7	Life-test provisions (intermittent)	Group A, Ehk = 90 Vdc	---	---	---	---	---	---
4.7.3	Life test end point (intermittent) (500 hours)	Transconductance (1)	---	---	Sm	1,460	---	µmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:31Z
Check the source to verify that this is the current version before use.

NOTES:

1. Operation of type 9002 in series with other types on supply voltage exceeding 32 volts is not recommended due to the excessive filament surge voltages which will appear on tubes of this type.
2. See 6.5.2.3 for reduced pressure (altitude) rating, and for altitude, maximum peak voltage. (B)
3. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2211-25)

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:31Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:31Z
Check the source to verify that this is the current version before use.