MILITARY SPECIFICATON

MICROCIRCUITS, DIGITAL, HIGH SPEED, CMOS BUS TRANSCEIVERS WITH THREE-STATE OUTPUTS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/655, dated 30 September 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, add new case outlines as follows:

"D	F-2 (14-lead, 1/4" x 3/8"), flat package
"K	F-6 (24-lead, 3/8" x 5/8"), flat package
"S	F-9 (20-lead, 1/4" x 1/2"), flat package".

PAGE 2

1.3, delete and substitute:

" 1.3 Absolute maximum ratings.

Supply voltage (V_{CC})	-0.5 V dc +7.0 V dc
DC input voltage (V_{IN})	-0.5 V dc to V_{CC} +0.5 V dc
DC output voltage (V_{OUT})	-0.5 V dc to V_{CC} +0.5 V dc
Clamp diode current (I_{IK}, I_{OK})	±20 mA
DC output current per pin (I_{OUT})	±35 mA
DC V_{CC} or GND current per pin (I_{OC})	±70 mA
Storage temperature range (T_{STG})	-65°C to +150°C
Maximum power dissipation (P_D)	300 mW
Lead temperature (soldering, 10 seconds)	+300°C
Thermal resistance, junction-to-case (θ_{JC}): Cases C, D, L, K, R, S, 2, and 3	(See MIL-M-38510, appendix C)
Junction temperature (T_J)	+175°C "

PAGE 3

3.2.2: Delete "and logic equations".

3.6.1: Delete "and 4.5.4 herein".

PAGE 4

4.3, second sentence, delete and substitute the following: "Inspections to be performed shall be those specified in 5005 of MIL-STD-883 and herein for groups A, B, C, and D inspections (see 4.4.1 through 4.4.4)."

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
23	Reprinted without change
24	24
25	25
26	Reprinted without change
29	29
30	30
39	39
40	40
71	71
72	72

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

PAGE 5

4.4, second sentence, delete and substitute the following: "Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, and D inspections (see 4.4.1 through 4.4.4)."

4.4.1b, and 4.4.1c, delete and substitute:

"b. Subgroups 5 and 6 of table I of method 5005 of MIL-STD-883 shall be omitted.

"c. Subgroup 4 ($C_{I/O}$ and C_C) shall be measured only for initial qualification and after process or design changes which may affect capacitance. Capacitance shall be measured between the designated terminal and V_{SS} at a frequency of 1 MHz."

PAGE 8

TABLE I, Control capacitance test, Max Limits column: Delete "10" and substitute "15".

TABLE I, I_{CC_A} symbol, conditions column, delete and substitute:

"V_{IL} = 0.4 V, V_{IH} = 2.4 V
Test pin(s) at V_{IN} = 2.4 V
Control pin(s) at V_{IN} = 0.4 V
Other pin(s) at V_{CC} or GND
I_O = 0 V (see table III)."

PAGE 11

TABLE IA, title: Delete "figures" and substitute "values".

PAGE 12

TABLE II, line 10, columns "Table III subgroups": Add "6/".

Bottom of page, add the following new footnote:

"6/ Subgroups 7 and 8 do not apply to device types 02, 03, and 53."

PAGE 13

FIGURE 1: Delete "Case C" and substitute "Cases C, D".

PAGE 14

FIGURE 4, title, delete and substitute:

"FIGURE 1. Logic diagrams and terminal connections (top view) - Continued.

PAGES 15 AND 16

FIGURE 1: Delete "Case R" and substitute "Cases R and S".

PAGE 18

FIGURE 1: Delete "Case L" and substitute "Cases L and K".

PAGES 19 AND 20

FIGURE 1, NOTE: Delete "case L" and substitute "cases L and K".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

PAGES 31 THROUGH 38

TABLE III, heading: Delete "Case C" and substitute "Cases C, D".

PAGES 33 AND 34

TABLE III, t_{PZH1} and t_{PHZ1}: Delete "10/".

TABLE III, t_{PZL1} and t_{PLZ1}: Delete "9/".

PAGES 37 AND 38

TABLE III, t_{PZH1} and t_{PHZ1}: Delete "10/".

TABLE III, t_{PZL1} and t_{PLZ1}: Delete "9/".

PAGES 41 THROUGH 54

TABLE III, heading: Delete "Cases 2, R" and substitute "Cases 2, R, S".

PAGES 41 THROUGH 44

TABLE III: Renumber tests 90 through 308 to 91 through 309.

PAGE 41

TABLE III, test numbers 123 through 138, subgroup 1, Max Limits column: Delete ".1" and substitute ".2".

PAGE 42

TABLE III, test numbers 139 through 154, subgroup 1, Max Limits column: Delete "-.1" and substitute "-.2".

TABLE III, test numbers 175 and 176, subgroup 1, Max Limits column: Delete "10" and substitute "15".

PAGE 44

TABLE III, test numbers 286 through 293, pin 1 column: Delete "6 V" and substitute "4.5 V".

TABLE III, t_{PZH1} and t_{PHZ1}: Delete "10/".

TABLE III, t_{PZL1} and t_{PLZ1}: Delete "9/".

PAGE 49

TABLE III, t_{PHZ2} and t_{PZH2}: Delete "10/".

TABLE III, t_{PLZ2} and t_{PZL2}: Delete "9/".

PAGE 54

TABLE III, t_{PHZ2} and t_{PZH2}: Delete "10/".

TABLE III, t_{PLZ2} and t_{PZL2}: Delete "9/".

PAGES 55 THROUGH 70

TABLE III, heading: Delete "Case L" and substitute "Cases L, K".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

PAGE 61

TABLE III, t_{PZH2} and t_{PHZ2}: Delete "10/".

TABLE III, t_{PZL2} and t_{PLZ3}: Delete "9/".

PAGES 73 THROUGH 76

TABLE III, heading: Delete "Cases 2, R" and substitute "Cases 2, R, S".

TABLE III: Renumber tests 94 through 312 to 95 through 313.

PAGE 73

TABLE III, test numbers 127 through 141, subgroup 1, Max Limits column: Delete ".1" and substitute ".2".

PAGE 74

TABLE III, test numbers 143 through 157, subgroup 1, Max Limits column: Delete "-.1" and substitute "-.2".

TABLE III, test numbers 179 and 180, subgroup 1, Max Limits column: Delete "10" and substitute "15".

PAGE 76

TABLE III, t_{PZH1} and t_{PHZ1}: Delete "10/".

TABLE III, t_{PZL1} and t_{PLZ1}: Delete "9/".

TABLE III, test numbers 290 through 297, pin 1 column: Delete "6 V" and substitute "4.5 V".

Footnote 2/, delete and substitute as follows:

"2/ Three-state output conditions are required. For I_{OZL}, set output to high state. For I_{OZH}, set output to low state. Set input pins to $V_{IL} = V_{IL}(max)$ or to $V_{IH} = V_{IH}(min)$ as required for each test."

Add new footnote 8/ as follows:

"8/ f_{MAX} minimum limit specified is the frequency of the input pulse. The output frequency shall be one-half the input frequency. The f_{MAX} requirement is considered met if proper output state changes occur with the pulse repetition period set to that given in the limits columns."

PAGE 77

4.4.5 and 4.5.4: Delete in their entirety.

PAGE 78

TABLE V and TABLE VI: Delete in their entirety.

PAGE 79

FIGURE 5: Delete in its entirety.

PAGE 80

TABLE VII: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, OC, MC, SH

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1086)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

nce test. moisture of the resistors, except of the moisture-resista

Device type 08

Inputs						Data I/O*		Operation or function
G	DIR	CAB	CAB	SAB	SBA	A1 thru A8	B1 thru B8	
H H	X X	H or L	H or L	X X	X X	Input	Input	Isolation store A and B data
L L	L L	X X	X H or L	X X	L H	Output	Input	Real time B data to A bus store B and A data
L L	H H	X H or L	X X	L H	X X	Input	Output	Real time B data to A bus store A and B data
X X	X X	↑ X	X ↑	X X	X X	Input not specified	Not specified input	Store A, B undefined Store B, A undefined

H = High Level L = Low Level X = Irrelevant ↑ = Low-to-high level transition
*The data output functions may be enabled or disabled by various signals at the G and DIR inputs. Data input functions are always enabled, i.e., data at the bus pins will be stored on every low-to-high transition on the clock inputs.

Device type 09

Inputs						Data I/O*		Operation or function
G	DIR	CAB	CAB	SAB	SBA	A1 thru A8	B1 thru B8	
H H	X X	H or L	H or L	X X	X X	Input	Input	Isolation store A and B data
L L	L L	X X	X H or L	X X	L H	Output	Input	Real time B data to A bus store B and A data
L L	H H	X H or L	X X	L H	X X	Input	Output	Real time B data to A bus store A and B data
X X	X X	↑ X	X ↑	X X	X X	Input not specified	Not specified input	Store A, B undefined Store B, A undefined


H = High Level L = Low Level X = Irrelevant ↑ = Low-to-high level transition
*The data output functions may be enabled or disabled by various signals at the G and DIR inputs. Data input functions are always enabled, i.e., data at the bus pins will be stored on every low-to-high transition on the clock inputs.

FIGURE 2. Truth tables - Continued.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:57Z
Check the source to verify that this is the current version before use.

Device types 01, 02, 03, 06, 07 and 53




NOTES:
1. For static burn-in I, all inputs shall be connected to GND. Outputs shall be open or connected to $V_{CC}/2$. Resistors are optional on outputs if open. Resistors are required on inputs, and required on outputs connected to $V_{CC}/2$. R = 470Ω to 47 kΩ.
2. For static burn-in II, all inputs shall be connected through the resistors to V_{CC}. Outputs shall be open or connected to $V_{CC}/2$. Resistors are optional on outputs if open. Resistors are required on inputs, and required on outputs connected to $V_{CC}/2$. R = 470Ω to 47 kΩ.
3. For dynamic burn-in, all inputs shall be connected through the resistors in parallel to a common CP. Outputs shall be connected to $V_{CC}/2$ ±.5 V through the resistors. R = 680Ω ±5 percent for outputs, 470Ω to 47 kΩ for inputs.
4. CP = 25 kHz to 1 MHz square wave; duty cycle = 50 ±15 percent; V_{IH} = 4.5 V to V_{CC}; V_{IL} = 0 ±.5 V, transition time ≤ 0.5 µs.
5. V_{CC} = 6.0 V +0.0 V, -0.5 V. V_{CC} = 5.5 V +0.0 V -0.5 V for device 53.

FIGURE 3. Burn-in and life test circuits.

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:57Z
Check the source to verify that this is the current version before use.


Device types 08 and 09



NOTES:
1. For static burn-in I, all inputs shall be connected to GND. Outputs shall be open or connected to $V_{CC}/2$. Resistors are optional on outputs if open. Resistors are required on inputs, and required on outputs connected to $V_{CC}/2$. R = 470Ω to 47 kΩ.
2. For static burn-in II, all inputs shall be connected through the resistors to V_{CC}. Outputs shall be open or connected to $V_{CC}/2$. Resistors are optional on outputs if open. Resistors are required on inputs, and required on outputs connected to $V_{CC}/2$. R = 470Ω to 47 kΩ.
3. For dynamic burn-in, all inputs shall be connected through the resistors in parallel to a common CP. Outputs shall be connected to $V_{CC}/2$ ±.5 V through the resistors. R = 680Ω ±5 percent for outputs, 470Ω to 47 kΩ for inputs.
4. CP = 25 kHz to 1 MHz square wave; duty cycle = 50 ±15 percent; V_{IH} = 4.5 V to V_{CC}; V_{IL} = 0 ±.5 V, transition time ≤ 0.5 µs.
5. V_{CC} = 6.0 V +0.0 V, -0.5 V.

FIGURE 3. Burn-in and life test circuits - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.




NOTES:
1. R_L = 1kΩ ±5%.
2. C_L = 50 pF ±10% including probe and jig capacitance.
3. The pulse generators have the following characteristics:
   V_{gen} = 4.5 V, PRR ≤ 1 MHz, t_{THL} ≤ 6 ns, Z_{OUT} = 50Ω.
4. Clock pulse characteristics: t_p (CLK) = 18 ns, t_{setup} = 20 ns, t_{hold} = 5 ns.
5. Output connected to V_{CC} for t_{PLZ} and t_{PZL}; and to GND for t_{PHZ} and t_{PZH}, see figure 4.
6. The input signal for the 53 device type (HCT) will be 0-3 volts; however, the 50% V_{CC} measure point is 1.3 volts for input and output signals. The 10% V_{CC} and 90% V_{CC} points are, 3 V and 2.7 V, respectively.

FIGURE 4. Switching time test circuit and waveforms.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:57Z
Check the source to verify that this is the current version before use.




VOLTAGE WAVEFORMS

PROPAGATION DELAY AND TRANSITION TIMES

NOTES:
1. Inputs pulse shall have the following characteristics: $t_r = t_f \leq 6$ ns; PRR $\leq$ 1 MHz; duty cycle = 50 percent.
2. For unused pin conditions, see table III, footnote 1/.
3. $t_{THL1} - t_{THL2} = t_{THL}$; $t_{TLH2} - t_{TLH1} = t_{TLH}$.

FIGURE 4. Switching time test circuit and waveforms - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.



NOTE:
$t_r = t_f \leq 6$ ns.

Enable and disable times, three-state outputs, all device types.

FIGURE 4. Switching time test circuit and waveforms - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:57Z
Check the source to verify that this is the currentversion before use.

TABLE III. Group A inspection for device type 03

Terminal conditions 1/

Symbol	MIL-STD-883 method	Cases 2, 3, 5, 6 test no.	1 DIR	2 A1	3 A2	4 A3	5 A4	6 A5	7 A6	8 A7	9 A8	10 GND	11 B8	12 B7	13 B6	14 B5	15 B4	16 B3	17 B2	18 B1	19 G	20 V_{CC}	Measured terminal	Limits	Subgroup 1 T_C = +25°C Min	Subgroup 1 T_C = +25°C Max	Subgroup 2 T_C = +125°C Min	Subgroup 2 T_C = +125°C Max	Subgroup 3 T_C = -55°C Min	Subgroup 3 T_C = -55°C Max	Unit
V_{IC} (I_{OS})		1	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	GND	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	6 V	DIR								
		2	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A1								
		3	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A2								
		4	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A3								
		5	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A4								
		6	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A5								
		7	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A6								
		8	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A7								
		9	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A8								
		10	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B8								
		11	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B7								
		12	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B6								
		13	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B5								
		14	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B4								
		15	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B3								
		16	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B2								
		17	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B1								
		18	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	G								
		19	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	V_{CC}								
V_{IC} (I_{OS})		20	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	DIR								
		21	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A1								
		22	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A2								
		23	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A3								
		24	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A4								
		25	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A5								
		26	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A6								
		27	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A7								
		28	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A8								
		29	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B8								
		30	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B7								
		31	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B6								
		32	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B5								
		33	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B4								
		34	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B3								
		35	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B2								
		36	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B1								
		37	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	G								
		38	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	V_{CC}								
V_{IC} (I_{INEX})		39	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	GND	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	-1 mA	6 V	DIR								
		40	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A1								
		41	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A2								
		42	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A3								
I_{CC}		43	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A4								
		44	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A5								
		45	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A6								
		46	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A7								
		47	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A8								
		48	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B8								
		49	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B7								
		50	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B6								
		51	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B5								
		52	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B4								
		53	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B3								
		54	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B2								
		55	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B1								
		56	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	G								
		57	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	V_{CC}								
I_{CC1}		58	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	DIR								
		59	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A1								
		60	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A2								
		61	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A3								
		62	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A4								
		63	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A5								
		64	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A6								
		65	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A7								
		66	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	A8								
		67	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B8								
		68	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B7								
		69	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B6								
		70	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B5								
		71	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B4								
		72	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B3								
		73	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B2								
		74	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	B1								
		75	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	G								
		76	GND	6 V	6 V	6 V	6 V	6 V	6 V	6 V	6 V		GND	6 V	6 V	6 V	GND	6 V	GND	6 V	6 V	6 V	V_{CC}								

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-01-21T14:57Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 01 - Continued.

Symbol	MIL-STD-883 test method	Limit 2/ R, S	Test no.	Terminal conditions 1/ 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	Measured terminal	Test limits Subgroup 1 (TC = +25°C) Min	Max	Subgroup 2 (TC = +125°C) Min	Max	Subgroup 3 (TC = -55°C) Min	Max	Unit
				D1R	A1	A2	A3	A4	A5	A6	A7	A8	GND	B8	B7	B6	B5	B4	B3	B2	B1	G	V_{CC}								
I_{OHS}	3006	1	41	1.2 V	20 µA							4.2 V												A1	5.95						V
			42			20 µA																		A2							
			43				20 µA																	A3							
			44					20 µA																A4							
			45						20 µA															A5							
			46							20 µA														A6							
			47								-20 µA													A7							
			48									20 µA												A8							
			49											4.2 V										B8							
			50												4.2 V									B7							
			51													4.2 V								B6							
			52														4.2 V							B5							
			53															4.2 V						B4							
			54																4.2 V					B3							
			55																	4.2 V				B2							
			56																		4.2 V			B1							
			57																			4.2 V		G							
			58																				4.2 V	V_{CC}							
I_{OHS}	3006	1	59	1.2 V	7.8 mA							4.2 V												A1	5.48						V
			60			7.8 mA																		A2							
			61				7.8 mA																	A3							
			62					7.8 mA																A4							
			63						7.8 mA															A5							
			64							7.8 mA														A6							
			65								-7.8 mA													A7							
			66									7.8 mA												A8							
			67											4.2 V										B8							
			68												4.2 V									B7							
			69													4.2 V								B6							
			70														4.2 V							B5							
			71															4.2 V						B4							
			72																4.2 V					B3							
			73																	4.2 V				B2							
			74																		4.2 V			B1							
			75																			4.2 V		G							
			76																				4.2 V	V_{CC}							
I_{OLS}	3007	1	77	1.2 V	20 µA							1.2 V												A1	5.48						V
			78			20 µA																		A2							
			79				20 µA																	A3							
			80					20 µA																A4							
			81						20 µA															A5							
			82							20 µA														A6							
			83								20 µA													A7							
			84									1.2 V												A8							
			85											1.2 V										B8							
			86												1.2 V									B7							
			87													1.2 V								B6							
			88														1.2 V							B5							
			89															1.2 V						B4							
			90																1.2 V					B3							
																				1.2 V				B2							
																					1.2 V			B1							
																						1.2 V		G							
																							1.2 V	V_{CC}							

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 53.

Symbol	MIL-STD-883 method	Cases 2, 3, 8 test no.	Terminal conditions 1/ 1 DIR	2 A1	3 A2	4 A3	5 A4	6 A5	7 A6	8 A7	9 A8	10 GND	11 B8	12 B7	13 B6	14 B5	15 B4	16 B3	17 B2	18 B1	19 E	20 VCC	Measured terminal	Subgroup 1 TC = +25°C Min	Subgroup 1 TC = +25°C Max	Subgroup 2 TC = +125°C Min	Subgroup 2 TC = +125°C Max	Subgroup 3 TC = -55°C Min	Subgroup 3 TC = -55°C Max	Units
$I_{IC(pd)}$		1	1 mA																			GND	DIR	0.4 1/	1.5					
		2		1 mA																			A1							
		3			1 mA																		A2							
		4				1 mA																	A3							
		5					1 mA																A4							
		6						1 mA															A5							
		7							1 mA														A6							
		8								1 mA													A7							
		9									1 mA												A8							
		10	1/																				GND							
		11											1 mA										GND							
		12												1 mA									B7							
		13													1 mA								B6							
		14														1 mA							B5							
		15															1 mA						B4							
		16																1 mA					B3							
		17																	1 mA				B2							
		18																		1 mA			B1							
		19																			1 mA		E							
		20	GND																				VCC							
		21																												
		22																												
		23																												
		24																												
		25																												
		26																												
		27																												
		28																												
		29																												
		30																												
		31																												
		32																												
		33																												
		34																												
		35																												
		36																												
$I_{IC(neg)}$		37	GND																											
		38	GND																											
		39	6 V																											
		40	6 V																											
		41	GND																											
		42	2.4 V																											
		43	0.8 V																											
		44	0.8 V																											
		45	2.4 V																											
I_{IC}	MIL-STD-883	37	GND																				VCC	5.5 V						
		38	GND																											
		39	6 V																											
		40	6 V																											
I_{IL2}		41	GND																											
I_{ILC}		42	2.4 V																					GND						
		43	0.8 V																					5.5 V						
		44	0.8 V																					0.8 V						
		45	2.4 V																					2.4 V						
																								5.5 V						

1/ See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 53 - Continued.

Terminal conditions 1/

Test no.	Symbol	MIL-STD-883 test method	Limits 2/		1 DIR	2 A1	3 A2	4 A3	5 A4	6 A5	7 A6	8 A7	9 A8	10 GND	11 B8	12 B7	13 B6	14 B5	15 B4	16 B3	17 B2	18 B1	19 G	20 V_{CC}	Measured (terminal)	Test Limits Subgroup 1 (T_C = +25°C) Min	Subgroup 1 (T_C = +25°C) Max	Subgroup 2 (T_C = +125°C) Min	Subgroup 2 (T_C = +125°C) Max	Subgroup 3 (T_C = -55°C) Min	Subgroup 3 (T_C = -55°C) Max	Unit
					0.8 V	20 µA	2.0 V	20 µA	6.0 mA	2.0 V	20 µA	6.0 mA	2.0 V	GND	20 µA	2.0 V	6.0 mA	2.0 V	20 µA	6.0 mA	2.0 V	20 µA	0.8 V	4.5 V								
46	I_{IH}	3010	Group A, subgroups 1, 2, and 3																												
47																															
48																															
49																															
50																															
51																															
52																															
53																															
54																															
55																															
56																															
57																															
58																															
59																															
60																															
61																															
62	I_{IH}	3010	Group A, subgroups 1, 2, and 3																												
63																															
64																															
65																															
66																															
67																															
68																															
69																															
70																															
71																															
72																															
73																															
74																															
75																															
76																															
77																															
78	I_{IL}	3009	Group A, subgroups 1, 2, and 3																												
79																															
80																															
81																															
82																															
83																															
84																															
85																															
86																															
87																															
88																															
89																															
90																															
91																															
92																															
93																															

1/ Footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.