NOT MEASUREMENT SENSITIVE

MIL-B-14632/5C
12 January 1995
SUPERSEDING
MIL-B-14632/5B
25 June 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, FLIGHT TRAINING GRADUATE, ROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-14632.

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall): 23/32 inch (1.83 cm) (REF)
WIDTH (Overall): 2-1/2 inches (6.35 cm) (REF)
THICKNESS (At Thickest Point): 0.105 inch ± 0.005 inch (0.266 ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:40Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the horizontal line passing through the center of the circle, equidistant from each end and 2 inches ± 1/32 inch (5.08 cm ± 0.08 cm) apart.

3. A mock forcer may be made used to bring up the design on the circle portion only.

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-0793)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:40Z
Check the source to verify that this is the current version before use.