A-A-50970
April 10, 1984

COMMERCIAL ITEM DESCRIPTION

ARBORS, DRILL CHUCK, TAPER SHANK WITH TANG

The General Services Administration has authorized the use of this commercial item description in preference to the Style A arbors covered by Federal Specification GGG-C-350.

This description covers solid taper shank arbors which are used to adapt a drill chuck having a tapered mount hole to a drilling machine having a tapered mount hole.

Salient characterisitics:

Size. The size of arbors covered by this description shall be as listed in Table I and is based on the number and type taper on the shank end of the arbor and the number and type taper on the mounting end of the arbor.

Material. The arbors shall be made from high grade steel entirely suitable for the purpose included. Each taper shall be precision ground and shall conform to dimensions and tolerances of ANSI B5.10.

Finish. Surfaces shall be smoothly ground, free from wheel and chatter marks and other imperfections which may affect their accuracy, appearance or serviceability.

Markings. Each arbor shall be marked in a legible manner with the manufacturer's name, model number, and taper number.

Roundness. Each arbor shall be round within 0.001 inch total indicator reading.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the CID where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

FSC 3460

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:49Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes.

Size	Number & Type Shank Taper	Number & Type Mount Taper
1	0 Morse	0 Jacobs
2	0 Morse	3 Jacobs
3	0 Morse	33 Jacobs
4	1 Morse	0 Jacobs
5	1 Morse	1 Jacobs
6	1 Morse	2 Jacobs
7	1 Morse	3 Jacobs
8	1 Morse	4 Jacobs
9	1 Morse	6 Jacobs
10	1 Morse	33 Jacobs
11	2 Morse	0 Jacobs
12	2 Morse	1 Jacobs
13	2 Morse	2 Jacobs
14	2 Morse	3 Jacobs
15	2 Morse	4 Jacobs
16	2 Morse	5 Jacobs
17	2 Morse	6 Jacobs
18	2 Morse	33 Jacobs
19	3 Morse	1 Jacobs
20	3 Morse	2 Jacobs
21	3 Morse	3 Jacobs
22	3 Morse	4 Jacobs

Size	Number & Type Shank Taper	Number & Type Mount Taper
23	3 Morse	5 Jacobs
24	3 Morse	6 Jacobs
25	3 Morse	33 Jacobs
26	4 Morse	2 Jacobs
27	4 Morse	3 Jacobs
28	4 Morse	4 Jacobs
29	4 Morse	5 Jacobs
30	4 Morse	6 Jacobs
31	4 Morse	33 Jacobs
32	5 Morse	2 Jacobs
33	5 Morse	3 Jacobs
34	5 Morse	4 Jacobs
35	5 Morse	5 Jacobs
36	5 Morse	6 Jacobs
37	7 Brown & Sharpe	2 Jacobs
38	7 Brown & Sharpe	3 Jacobs
39	7 Brown & Sharpe	6 Jacobs
40	9 Brown & Sharpe	3 Jacobs
41	9 Brown & Sharpe	4 Jacobs
42	9 Brown & Sharpe	6 Jacobs
43	10 Brown & Sharpe	3 Jacobs
44	10 Brown & Sharpe	4 Jacobs

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:49Z
Check the source to verify that this is the current version before use.

Acceptance inspection. The supplier shall randomly select the number of samples specified in Table II that is applicable to the quantity of items being purchased. Each sample shall be visually inspected and tested by the supplier to determine conformance with all the salient characteristics and the roundness test specified herein. Any sample failing to meet these requirements shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, Number Defective", column in Table II, the supplier shall replace the defective samples with acceptable items, and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, Number Defective" column of Table II, the entire lot shall be considered defective.

TABLE II. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance number defective	Rejection number defective
8 and under	2	0	1
9 to 15	3	0	1
16 to 25	5	0	1
26 to 50	8	1	2
51 to 90	13	1	2
91 to 150	20	2	3
151 to 280	32	3	4
281 to 500	50	5	6

Roundness test. Each of the sample arbors selected in accordance with Table II shall be checked for roundness specified herein.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes: Purchaser should specify quantity and size arbors required for specific procurement.

American National Standards Institute ANSI B5.10, "Machine Tapers", is available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:49Z
Check the source to verify that this is the currentversion before use.

MILITARY INTEREST:

Custodian

Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activity

Army - AL

CIVIL AGENCY COORDINATNG ACTIVITY:

GSA - FSS

PREAPRING ACTIVITY:

DLA - IP

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:49Z
Check the source to verify that this is the current version before use.