INCH-POUND

FF-O-601F
March 30, 1990
SUPERSEDING
FF-O-601E
August 5, 1971

FEDERAL SPECIFICATION

OPENERS, CAN, HAND AND MOUNTED

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers hand held, wall mounted, and table mounted manually operated can openers.

1.2 Classification. The can openers shall be of the following types, classes, and grades as specified (see 6.2).

Type I - Hand, household, portable

Class 1 - Lever operated, with corkscrew and bottle opener
Class 2 - Wing operated feed wheel

Type II - Wall mounted with magnetic lid lifter

Type III - Table mounted, heavy duty, with cutting wheel

Grade A - Standard commercial quality
Grade B - Corrosion-resisting steel

Type IV - Table mounted, heavy duty, standard commercial quality, with cutting blade

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

Federal Specifications:

A-A-203	-	Paper, Kraft, Untreated
QQ-A-225/5	-	Aluminum Alloy 2017, Bar, Rod and Wire; Rolled, Drawn, or Cold Finished
QQ-A-601	-	Aluminum Alloy Sand Castings
QQ-B-626	-	Brass, Leaded and Nonleaded: Rod, Shapes, Forgings, and Flat Products with Finished Edges (Bar and Strip)
QQ-S-698	-	Steel Sheet and Strip, Low Carbon
QQ-S-700	-	Steel Sheet and Strip, Medium and High Carbon
QQ-Z-363	-	Zinc-Base Alloy, Die Castings
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes Set-Up
PPP-C-96	-	Cans, Metal, 28 Gauge and Lighter
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing

Federal Standards

FED-STD-66	-	Steel: Chemical Composition and Hardenability
FED-STD-123	-	Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards, commercial item descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

(Single copies of this specification, and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes, are available without charge from General Services Administration Business Service Center in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:47Z
Check the source to verify that this is the currentversion before use.

Military Specifications:

MIL-P-116	-	Preservation, Methods of
MIL-B-117	-	Bags, Sleeves and Tubing
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)

A 48	-	Gray Iron Castings
A 513	-	Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing
A 519	-	Seamless Carbon and Alloy Steel Mechanical Tubing
D 3951	-	Standard Practice for Commercial Packaging
E 18	-	Methods of Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials
E 384	-	Standard Test Method for Microhardness of Materials
E 1077	-	Standard Test Methods for Estimating the Depth of Decarburization of Steel Specimens

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

3.2 Standard product. The can openers delivered under this specification shall be the manufacturer's current commercial standard product except for any changes necessary to comply with specification requirements.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer in fabricating his standard commercial can openers provided the completed items comply with all provisions of this specification. Unless otherwise specified herein, commercial tolerances shall apply to material thicknesses and diameters. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Carbon steel.

3.3.1.1 Low carbon, sheet and strip. Low carbon sheet and strip shall conform to cold rolled, commercial quality (sheet) or cold rolled, quarter-hard temper (strip) steel No. 1009, 1015, 1018, or 1020 of QQ-S-698.

3.3.1.2 Medium carbon, sheet. Medium carbon steel sheet shall conform to cold rolled, annealed, and skin passed (temper rolled), steel No. 1035, 1045, or 1050 of QQ-S-700.

3.3.1.3 Tube. Carbon steel tube shall be square, seamless, condition CW conforming to ASTM A 519 or welded and conforming to ASTM A 513.

3.3.2 Aluminum.

3.3.2.1 Bar and rod. The aluminum alloy bar and rod shall be composition 2017-O conforming to QQ-A-225/5.

3.3.2.2 Sand castings. Aluminum alloy sand castings shall conform to alloy 43 of QQ-A-601.

3.3.3 Gray iron castings. Gray iron castings shall be class 25 or better conforming to ASTM A 48.

3.3.4 Zinc alloy castings. Zinc alloy castings shall conform to alloy AG40A of QQ-Z-363.

3.3.5 Corrosion-resisting steel. Corrosion-resisting steel shall conform to the chemical composition of any corrosion-resisting steel in the 300 series of FED-STD-66.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.3.6 Brass bar or rod. Brass bar or rod shall conform to the chemical composition requirements of copper alloy numbers 230, 240, 260, 268, 342, or 360 of QQ-B-626.

3.4 Design and construction. The openers shall be type I, class 1 or 2, grade A or B; type II, grade A or B; type III, grade A or B; or type IV as stated in 1.2 and shall be of the design and construction specified herein. The design and construction shall be such that all parts that come in contact with, or may be contaminated by, food are easily cleanable and capable of being sanitized. The blades, feed wheels, cutting wheels, and the gear shall conform to the applicable material requirements specified in table I. When tested for hardness as specified in 4.4.2 the blades, feed wheels, cutting wheels, and gears shall conform to the applicable hardness requirements specified in table I. Hardness scale values specified in table I are inclusive. The openers shall open round, square, and oblong or pear shaped cans, conforming to the requirements for type I, open top, double seamed ends specified in PPP-C-96. Can sizes are standard commercial sizes and are as specified herein. The type I, class 2 and the type II, III, and IV openers shall operate freely without binding when tested as specified in 4.5.2.2, 4.5.2.3, or 4.5.2.4 as applicable.

TABLE I. Blade, feed wheel, cutting wheel, and gear material and hardness

Opener Classification	Materials		Hardness		
	Blade	Feed and/or cutting wheels	Blade	Feed and/or cutting wheels	Gears
Type I, class 1, grade A	Steel (manufacturer's standard blade)	None	Rockwell C 46-52	None	None
Type I, class 1, grade B	Corrosion-resisting steel	None	Rockwell C 46-52	None	None
Type I, class 2	None	Feed wheel/free machining low or medium carbon steel or tool/alloy steel	None	Feed wheel/ case hardened to a depth of 0.008 inch or greater: Rockwell 15-N hardness of 89.0-90.0	None

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE I. Blade, feed wheel, cutting wheel, and gear material and hardness (cont'd)

Opener Classification	Materials		Hardness		
	Blade	Feed and/or cutting wheels	Blade	Feed and/or cutting wheels	Gears
Type I, class 2 (cont'd)	None	Cutting wheel/ free machining low or medium carbon steel ASTM 600 or ASTM 681	None	Cutting wheel/ case hardened to a depth of 0.006 inch or greater; Knoop hardness ranges as follows: 0.002 inch = 600-700 0.004 inch = 550-700 0.006 inch = 500-700	None
Type II	None	Carbon steel	None	Case hardened 0.010 inch Rockwell 15-N 89.0-90.0	Case hardened 0.010 inch Rockwell 15-N 83.0-85.5
	None	ASTM 600 or ASTM 681	None	Rockwell C 50-56	Rockwell C 45-50
Type III	None	ASTM 600 or ASTM 681	None	Rockwell C 53-58	Rockwell C 45-50
Type IV	Steel or cast tool steel	ASTM 600 or ASTM 681	Rockwell C 56-61	Rockwell C 58-62	Rockwell C 58-62

3.4.1 Type I, class 1 opener. The type I, class 1 openers shall be grade A or B and shall be hand operated by leverage. The openers shall have a corkscrew, a blade, a cap opener, a handle, and a can bead guide. The overall length of the openers shall be 5-1/2 inches ± 1/4 inch.

3.4.1.1 Corkscrew. The corkscrew shall be hinged or pinned so as to fold into the handle when not in use. The corkscrew for grade A shall be the manufacturer's standard product. The corkscrew for grade B shall be of corrosion-resisting steel specified in 3.3.5.

3.4.1.2 Blade. The blade shall have a point for piercing can tops and a straight, bevelled cutting edge with an effective cutting length of not less than 7/8 inch and shall be permanently attached to the handle by welding or by a minimum of two rivets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.4.1.3 Cap opener. The cap opener shall be constructed and permanently attached to the opener in accordance with the manufacturer's current standard practice. The cap opener may be an integral part of the blade or handle, or a separate component permanently joined to the blade or handle.

3.4.1.4 Handles. The handle for grade A openers shall be fabricated of either low or medium carbon steel specified in 3.3.1.1 or 3.3.1.2. The handle for the grade B opener shall be fabricated of corrosion-resisting steel specified in 3.3.5. The handle or plier device shall have rounded surfaces to provide confortable operation.

3.4.1.5 Bead guide. The bead guide shall fit over the can bead, hold the opener in position, and guide the opener during the cutting operation. The bead guide shall be an integral part of the handle and so located that the blade penetrates the can top to a depth of not less than 3/16 inch before the bead guide contacts the can bead.

3.4.1.6 Performance. The type I, class 1 openers shall open all size cans up to and including No. 10 round, 7-inch square, and 7-inch oblong or pear shaped. The opener shall show no evidence of breaking, parts separation, or permanent deformation when load and performance tested as specified in 4.5.2.1.

3.4.2 Type I, class 2 opener. The type I, class 2 openers shall be hand operated by turning a wing-operated feed wheel to force the can top against the cutting wheel. The opener shall consist of a body with a can guide, a wing-operated feed wheel, a cutting wheel, and a plier-type pressure device to force the cutting wheel through the can top and hold the can in the cutting position while pressure is applied. The opener shall have an integral bottle cap opener. The handle thickness shall be a minimum of 0.4 inch. The handles shall have rounded surfaces to provide comfortable operation. The handle padding material shall be fully enclosed around the opener and have no open gaps which allow food accumulation.

3.4.2.1 Body and guide. The body and can guide of the grade A opener shall be fabricated of either low or medium carbon steel specified in 3.3.1.1 or 3.3.1.2. The body and can guide of the grade B opener shall be fabricated of corrosion-resisting steel specified in 3.3.5. The can guide shall be an integral part of the body and shall guide the can against the cutting wheel during the cutting operation.

3.4.2.2 Feed wheel. The feed wheel shall have sharp teeth or serrations equally spaced around the wheel circumference to force the can top against the cutting wheel when the feed wheel is turned. The feed wheel shall be permanently attached to the wing type handle by a metal shaft passing through the opener body.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T11:47Z
Check the source to verify that this is the current version before use.

3.4.2.3 Cutting wheel. The cutting wheel shall be chamfered to a sharp cutting edge and shall exhibit an angle of 20 to 30 degrees when viewed from the plane of the feed wheel to the adjacent surface of the cutting edge. The cutting wheel shall be mounted on a plier or cam-type pressure device so as to penetrate the can top when pressure is applied by turning the feed wheel or by squeezing the handle.

3.4.2.4 Performance. The type I, class 2 opener shall remove the tops from all size cans up to and including No. 10 round, 7-inch square, and 7-inch oblong or pear shaped cans, and shall support cans weighted up to 20 pounds in the cutting position. The opener shall show no evidence of parts separation, breaking, or permanent deformation and shall remove the tops from cans without producing metal slivers or chips or jagged or irregular edges when load and performance tested as specified in 4.5.2.2. No contact between the feeder wheel and the cutting wheel edge shall be observed when the following is done to the opener. Turn opener on its side, wing down, and with one handle held stationary, rotate the other handle until the can opener closes.

3.4.3 Type II opener. The type II opener shall be grade A or B as stated in 1.2, and shall be wall mounted and operated by a hand crank. The opener shall consist of a wall mounting bracket, an extension arm, a geared cutting wheel, a geared feed wheel, a cutting wheel lever, and a magnetic lid lifter.

3.4.3.1 Wall mounting bracket. The wall mounting bracket for grade A openers shall be fabricated of carbon steel sheet or strip specified in 3.3.1.1 or 3.3.1.2. The wall mounting bracket for grade B openers shall be fabricated of corrosion-resisting steel specified in 3.3.5. The bracket shall have a thickness of not less than 0.080 inch and a length and width of not less than 1-1/2 inches. The bracket shall be a separate part and shall have a dovetail slot or a metal pin to receive and hold the extension arm. The bracket shall be reinforced and shall support the opener at right angles to the wall in a horizontal position. The bracket shall have not less than three screw holes and shall be furnished with a wood screw for each of the holes.

3.4.3.2 Extension arm. The extension arm for grade A openers shall be fabricated of carbon steel sheet or strip specified in 3.3.1.1. The extension arm for grade B openers shall be fabricated of corrosion-resisting steel specified in 3.3.5. The extension arm shall have a thickness of not less than 0.080 inch. The extension arm shall be the body of the opener and shall be 6 inches $\pm$ 1/8 inch long and not less than 1-1/4 inches wide.

3.4.3.3 Cutting wheel. The cutting wheel shall be geared to mesh with the geared feed wheel. There shall be a clearance of not more than 0.005 inch between the feed and cutting wheels.

3.4.3.4 Feed wheel. The feed wheel shall be geared to mesh with the geared cutting wheel.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:47Z
Check the source to verify that this is the currentversion before use.

3.4.3.5 Crank. The crank for the grade A opener shall be fabricated of carbon steel sheet or strip specified in 3.3.1.1 or 3.3.1.2. The crank for the grade B opener shall be fabricated of corrosion-resisting steel specified in 3.3.5. The crank shall be reinforced at the feed wheel shaft and shall be 4 inches ± 1/8 inch long. The crank handle shall be fabricated of metal or of molded plastic and shall be joined to the crank by, and rotate, on a steel spindle.

3.4.3.6 Cutting wheel lever. The cutting wheel lever for the grade A opener shall be fabricated of carbon steel specified in 3.3.1.1 or 3.3.1.2. The cutting wheel lever for the grade B opener shall be fabricated of corrosion-resisting steel specified in 3.3.5. The cutting wheel lever shall be hinged or pinned to the extension arm so as to force the cutting wheel through the can top when the lever is forced down.

3.4.3.7 Magnetic lid lifter. The magnetic lid lifter shall be of sufficient magnetic strength, and so located as to lift the cut-off lid and hold it away from the can opening.

3.4.3.8 Performance. The type II opener shall meet the performance characteristics specified for type I in 3.4.2.4 when tested in accordance with 4.5.2.3.

3.4.4 Type III opener. The type III openers shall be grade A or B as stated in 1.2 and shall be table mounted and operated by a hand crank. The opener shall consist of a body, a feed wheel, a cutting wheel, a can holder, a crank, a can guide, a vertical shaft, a table clamping bracket, an instruction plate, and when required (see 3.4.4.9), a magnetic lid lifter. The feed and cutting wheels may be geared or ungeared at the option of the manufacturer. Drive gears, when used, shall be solid or laminated. When laminated drive gears are used, the laminations shall be aligned and secured to each other to prevent slippage of the laminations.

3.4.4.1 Body. The body of the grade A openers shall be a gray iron casting specified in 3.3.3, a zinc alloy casting specified in 3.3.4, or any material which will allow for successful performance as specified in 3.4.4.11. The body of the grade B opener shall be corrosion-resisting steel specified in 3.3.5.

3.4.4.2 Feed wheel. The diameter of the feed wheel shall be not less than 7/8 inch and the wheel shall have equally spaced sharp teeth or serrations around the wheel circumference to force the can top against the cutting wheel when the feed wheel is turned. The feed wheel shall be easily removable for replacement. When the feed wheel and cutting wheels are geared, a stamped or rolled gripping surface is acceptable on the feed wheel in lieu of the sharp teeth or serrations. When the feed wheel is geared, it shall mesh with the cutting wheel gear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.4.4.3 Cutting wheel. The cutting wheel shall be sharp, have a diameter of not less than 3/4 inch, and be easily removable for replacement. The wheel shall be geared or ungeared at the option of the manufacturer. When geared, the cutting wheel shall mesh with the feed wheel gear. The cutting wheel shall be mounted on a floating shaft so as to penetrate the can top on the inside of the can bead when pressure is applied by an eccentric lever or by a spring loaded device.

3.4.4.4 Can holder. The can holder may be eccentric or spring loaded type. When an eccentric device is used, it shall be fabricated of cold-rolled steel or brass and the eccentric bushing shall be fabricated of corrosion-resisting steel provided the eccentric and the bushing materials are not similar. Brass, when used, shall conform to 3.3.6.

3.4.4.5 Crank and knob. The knob shall be located on the crank not less than 4-3/4 inches from the center line of the feed wheel. The knob shall pivot on the crank. The crank and knob shall be secured to the can opener, and made of a material which will allow for successful performance as specified in 3.4.4.11.

3.4.4.6 Can guide. The can guide shall be constructed and located on the body of the opener so as to ride the top of the can bead and hold the can in position during the cutting operation.

3.4.4.7 Vertical shaft. The vertical shaft for the grade A opener shall be constructed of square tube specified in 3.3.1.3, cast iron conforming to 3.3.3, or any material which will allow for successful performance as specified in 3.4.4.11. The cast iron shaft shall be H-form. The vertical shaft for the grade B opener shall be of corrosion-resisting steel specified in 3.3.5. The shaft shall fit the table clamping bracket. The shaft length shall be not less than 15-3/4 inches from the lower part of the can guide to the end of the shaft.

3.4.4.8 Table clamping bracket. The table clamping bracket for the grade A opener shall be a gray iron casting specified in 3.3.3, or any material which will allow for successful performance as specified in 3.4.4.11. The table clamping bracket for the grade B opener shall be of corrosion-resisting steel specified in 3.3.5. The table clamping bracket shall incorporate a clamping device which will enable the bracket to be securely attached to a table edge having a maximum thickness of 3 inches. The bracket shall have provisions for holding the vertical shaft of the opener at any desired height.

3.4.4.9 Lid lifter. When specified (see 6.2), the type III openers shall have a magnetic lid lifter conforming to 3.4.3.7.

3.4.4.10 Instruction plate. A corrosion-resisting metal instruction plate shall be permanently fastened to each type III opener or, at the option of the manufacturer, the instructions may be indented on an exterior surface of the opener. Instructions shall include procedure for replacing cutting and feed wheels, procedure for lubrication, location of all lubrication points and, when applicable, method of adjusting clearance between the cutting and feed wheels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.4.4.11 Performance. The type III opener shall remove the tops from all size cans up to and including No. 12 round, 9-1/2 inches square, and 9-1/2 inches oblong or pear shaped cans and shall support cans weighted to 25 pounds in the cutting position. The opener shall show no evidence of parts separation, breaking, or permanent deformation and shall remove the tops from cans without producing metal slivers or chips or jagged or irregular edges when load and performance tested as specified in 4.5.2.4. The cast metal base plate of the table clamping bracket shall not crack, bend, chip, or break when impact tested as specified in 4.5.3.

3.4.4.12 Spare parts for type III. Three additional sets of cutting wheels and feed wheels shall be furnished with each opener. Where cutting wheel studs are used, three of these studs shall be furnished. All spare parts shall be attached securely to the clamping bracket.

3.4.5 Type IV opener. The type IV opener shall be standard commercial quality and shall be table mounted and operated by a hand crank. The opener shall consist of a body, a feed wheel, a reversible cutting blade, a can holder, a can guide, a crank, a vertical shaft, a table mounting bracket, and an instruction plate.

3.4.5.1 Body. The body of the type IV opener shall be a gray iron casting specified in 3.3.3 or a zinc alloy casting specified in 3.3.4, or any material which will allow for successful performance as specified in 3.4.4.11. The body may be a separate part or may be integral with the cast metal vertical shaft specified in 3.4.5.6.

3.4.5.2 Feed wheel. The feed wheel shall be not less than 1-1/2 inches in diameter and shall have equally spaced sharp serrations around the wheel circumference to force the can top against the cutting blade when the wheel is turned.

3.4.5.3 Cutting blade. The cutting blade shall be the bayonet type with two cutting edges and shall be removable and reversible.

3.4.5.4 Can holder and guide. The can holder and guide shall be in accordance with the manufacturer's standard practice.

3.4.5.5 Crank and knob. The crank shall be a gray iron casting specified in 3.3.3 or medium carbon steel specified in 3.3.1.2, or any material which will allow for successful performance as specified in 3.4.4.11. The crank knob shall be in accordance with the manufacturer's standard practice.

3.4.5.6 Vertical shaft. The vertical shaft shall be an H-form casting of material specified in 3.3.3 or 3.3.4 or a square tube fabricated of the material specified in 3.3.1.3, or any material which will allow for successful performance as specified in 3.4.4.11. Cast metal shafts may be separate parts or may be integral with the body specified in 3.4.5.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:47Z
Check the source to verify that this is the current version before use.

3.4.5.7 Table mounting bracket. The table mounting bracket shall be a gray iron casting specified in 3.3.3 or a zinc alloy casting specified in 3.3.4. The bracket shall be provided with not less than three 1/4-inch holes and mounting screws for attaching to table tops or may have a clamping device capable of clamping to a table edge up to 3 inches in thickness.

3.4.5.8 Instruction plate. A corrosion-resistant metal instruction plate shall be permanently fastened to each type IV opener, or the instructions may be indented on an exterior surface of the opener. Instructions shall include procedure of replacing and reversing cutting blades, replacing feed wheel, and lubrication procedures.

3.4.5.9 Performance. Performance of the type IV opener shall be as specified in 3.4.4.11.

3.4.5.10 Spare parts for type IV. Three additional sets of cutting blades and feed wheels shall be furnished with each opener. Where cutting blade studs are used, three of these studs shall be furnished. All spare parts shall be attached securely to the mounting bracket.

3.5 Marking for identification. Marking for identification shall be in accordance with the manufacturer's standard commercial practice.

3.6 Finish. All carbon steel components, except the feed wheels, cutting wheels, blades, and gears, shall be chromium plated, nickel plated, or nickel and chromium plated in accordance with the manufacturer's standard commercial practice. All exposed surfaces of corrosion-resisting steel components shall have a 2B (100 grit) finish or better. All other metal parts shall be finished in accordance with the manufacturer's commercial practice.

3.7 Workmanship. The finished openers shall be clean and free of rust, slivers, die marks, deformities, and fractures. All sharp edges and corners, except cutting edges and feed wheel serrations shall be removed. The cutting wheels and blades shall be sharp and free of burrs and slivers. Sharp edges on the gear teeth shall be removed. Feed wheel serrations, or teeth, shall be sharp, uniform in shape, equally spaced, and burrs and slivers shall be removed. The openers shall conform to the quality of product established by this specification.

3.7.1 Plating. Plating shall be free of blisters, peeling, chipping, areas of no coverage, and imbedded foreign matter.

3.7.2 Castings. Castings shall be complete and free of porosity, cracks, blow holes, and deformities.

3.7.3 Welds. Welds shall be sound, smooth, and free from pits, fractures, burn through, or fissures. All scale or flux shall be removed. Spot welds shall be free of flashes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:47Z
Check the source to verify that this is the currentversion before use.

3.7.4 Rivets. All burrs shall be removed from rivet holes. Rivet heads and peened ends shall be round and in full contact with the joined metal. There shall be no missing rivets.

3.7.5 Threaded fasteners. Threaded fasteners shall be drawn tight and shall not be stripped or cross threaded. Washers, lockwashers, and bushings shall be provided where required in accordance with standard commercial practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.4.5. Any nonconformance shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In process inspection. The blade of the type I, class 1, and the type IV openers and the cutting wheels, the feed wheels and, when applicable, the gears of the type I, class 2, and the type II, III, and IV openers, shall be tested for hardness in accordance with 4.5.1. The case hardness depth of the cutting wheel of the type I, class 2 opener shall be tested in accordance with 4.5.4. The lot shall be all blades, feed wheels, cutting wheels, and gears when applicable, of one type, class, and grade or of one type and grade of opener offered for inspection at one time. The sample unit shall be one completely fabricated blade, feed wheel, cutting wheel, or gear, as applicable. The inspection level shall be S-3 and the Acceptable Quality Level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of all openers of one type, class, and grade, or all openers of one type and grade offered for inspection at one time. The sample unit shall be one completely fabricated opener. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 6.5 for total (major and minor combined) defects.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Finish (general)	Dirty, rust, scale	101	
	Pits, scratches	102	
	Not finished in accordance with manufacturer's standard commercial practice	103	
Carbon steel components (except feed wheels, cutting wheels and gears)	Not nickel plated, chromium plated, or nickel and chromium plated	104	
	Areas of no coverage	105	
	Blisters, peeling, chipping, imbedded foreign matter	106	
Corrosion-resisting steel	Not a 2B (100 grit) or better finish (grade B)	107	
Construction and workmanship (general)	Deformities, fractures, sharp edges, or corners (except cutting edges)	108	
	Die marks, burrs, or slivers	109	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Castings	Porosity, cracks, deformities, incomplete, blowholes	110	
Cutting wheels, blades, feed wheels, gears (where applicable)	Cutting wheels or blades not sharp	111	
	Sharp edges of gear teeth not removed	112	
	Feed wheel serrations not sharp, not uniform in shape, not equally spaced	113	
Welds (where applicable)	Fissures, fractures, burn through	114	
	Not smooth, scale or flux deposits not removed, flashes on spot welds	115	
Cleanability	Parts that may come in contact with or be contaminated by food not easily accesible for cleaning and sanitizing	116	
Rivets (where applicable)	Burrs not removed from rivet holes	117	
	Rivet heads and peened ends not round or not in full contact with joined metal surfaces	118	
	Missing	119	
Metal fasteners (where applicable)	Stripped or crossed threads	120	
	Lockwashers or bushings not provided where required	121	
	Loose or missing	122	
Spare parts	Missing, not securely attached	123	
Construction and workmanship			
Type I, class 1	Corkscrew missing or is not hinged or pinned to fold into handle when not in use	124	
	Cutting blade not straight, beveled edge, point not sharp	125	
	Bead guide or metal can opener missing	126	
	Cutting blade not secured by welding or with at least 2 rivets	127	
	Handle not rounded	128	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd)			
Type I, class 2	Does not have a cutting wheel	129	
	Not wing-operated	130	
	Not plier- or cam-pressure type	131	
	Absence of bottle cap opener	132	
	Handle padding material not enclosed around handle fully		201
	Cutting wheel chamfer not as specified	133	
	Cutting wheel contacts feed wheel gear when handles are closed		202
	Chamfer of cutting wheel not evident	134	
	Handle not rounded	135	
Type II	Not crank operated or wall mounted	136	
	Mounting screws missing or less than specified quantity		203
	Cutting wheel not geared	137	
	Feed wheel not geared	138	
	Wall mounting bracket missing or does not have reinforced flanges or other means of reinforcing	139	
	Dovetail slot or mounting pin not provided (when wall mounting bracket is separate piece)	140	
	Crank not reinforced at the feed wheel shaft	141	
	Crank handle does not rotate freely on handle spindle	142	
	Crank handle not fabricated of metal or plastic	143	
	Magnetic lid lifter missing	144	
	Not table mounted or crank operated	145	
	Body not fabricated as specified	146	
Type III	Feed wheel or cutting wheel not removable	147	
	Can holding device missing or not type specified	148	
	Crank and knob not fabricated as specified	149	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd)			
Type III (cont'd)	Can guide missing or not located on opener housing	150	
	Vertical shaft not fabricated as specified	151	
	Table clamping bracket not fabricated as specified	152	
	Table clamping bracket does not have provisions for holding the vertical shaft and adjusting height of vertical shaft	153	
	Instruction plate missing or instructions not indented in surface of opener	154	
	Instructions not as specified	155	
	Instruction plate not of corrosion-resistant metal	156	
	Magnetic lid lifter missing (when specified)	157	
	Not table mounted or crank operated	158	
	Body not gray iron or zinc alloy casting	159	
	Body not fabricated as specified	160	
Type IV	Feed wheel does not have equally spaced serrations around the circumference	161	
	Cutting blade not bayonet type, does not have two cutting edges, or is not removable or reversible	162	
	Can holder missing or not manufacturer's standard	163	
	Can guide missing or not manufacturer's standard	164	
	Crank not gray iron casting or carbon steel. Crank knob missing or not manufacturer's standard	165	
	Table mounting bracket not gray iron or zinc alloy casting	166	
	Mounting holes and screws or clamping device missing	167	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd)			
Type IV (cont'd)	Instruction plate missing or instructions not indented in surface of opener	168	
	Instruction plate not of corrosion-resistant metal	169	
	Instructions not as specified	170	
Marking for identification	Missing, illegible		204

4.4.4 End item dimensional examination. The end items shall be examined for the defects listed in section 3. The lot size shall be expressed in units of all openers of one type, class, and grade, or all openers of one type and grade offered for inspection at one time. The sample unit shall be one completely fabricated opener. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. The end items shall be tested as specified in 4.5.1 through 4.5.4, as applicable. The inspection level shall be S-2. Failure of any sample unit to pass any test shall be cause for rejection of the lot.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Hardness test. The components specified in 4.4.2 shall be tested in accordance with ASTM E 18 for Rockwell hardness requirements and ASTM E 384 for Knoop microhardness requirements. The Knoop testing shall be performed using a 400 gram force load. The Knoop microhardness test shall be performed at a point midway between the wheel edge and center of the wheel.

4.5.2 Load and performance test. All cans specified in this paragraph shall comply with PPP-C-96.

4.5.2.1 Type I, class 1. The opener handle shall be clamped in a holding device at a 45 degree angle from the horizontal. A weight or a force of not less than 20 pounds shall then be applied directly against the blade in a vertical downward direction for not less than 1 minute. The opener shall then be removed from the holding device and used to open three No. 10 round, three 7 inch square, and three 7 inch oblong or pear shaped cans. The opener shall then

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

be examined to determine compliance with the parts separation, breaking, and permanent distortion requirements of 3.4.1.6. Inability of the opener to meet requirements shall constitute failure of this test.

4.5.2.2 Type I, class 2. The opener shall be placed in the cutting position on an open can and the wing clamped in a holding device. A weight or a force of not less than 20 pounds shall then be applied to the bottom inside of the can in a vertical downward direction for not less than 1 minute. The opener shall then be removed from the can and the holding device and the opener used to open nine cans as specified in 4.5.2.1. During the openings, the opener shall be observed to determine compliance with the nonbinding requirements of 3.4. After all cans have been opened, they shall be examined to determine compliance with the metal sliver or chip and jagged or irregular edge requirements of 3.4.2.4. The opener shall then be examined to determine compliance with the parts separation, breaking, and permanent distortion requirements of 3.4.2.4. Inability of the opener to meet requirements shall constitute failure of this test.

4.5.2.3 Type II. The opener shall be secured to a wall or holding device by the wall mounting bracket and an open No. 10 round can placed in the cutting position. The opener shall then be tested as specified in 4.5.2.2 to determine conformance with 3.4 and 3.4.2.4. Inability to meet requirements shall constitute failure of this test.

4.5.2.4 Types III and IV. The opener shall be placed in operating position on a table or bench and an open No. 12 round can placed in the cutting position. A weight or a force of not less than 25 pounds shall then be applied to the inside bottom of the can in a vertical downward direction for not less than 1 minute. The can shall then be removed from the opener and three No. 12 round cans, three 9-1/2 inch oblong cans, and three rectangular cans 13-3/4 inches high by 9-1/2 inches square shall be opened. In addition, four No. 10 round cans, commercially packed four to a case, weighing not less than 6 pounds each shall be dented by dropping the case from a height of not less than 2 feet onto a flat concrete surface. The case shall be dropped once on each of the six sides and once on each of the four diagonal corners. The dented cans shall also be opened. The opener shall be observed while opening the cans to determine compliance with the operation and binding requirements of 3.4. The opened cans shall be examined to determine compliance with the metal slivers or chips and the jagged or irregular edge requirements of 3.4.4.11. The opener shall then be examined to determine compliance with the parts separation, breaking, and permanent deformation requirements of 3.4.4.11. Inability of the opener to meet requirements shall constitute failure of this test.

4.5.3 Impact test, type III, grade A and type IV. A 3 pound ± 1/4 pound round steel ball shall be dropped vertically from a height of not less than 1 foot onto the center of the base plate of the table clamping bracket. The base plate shall then be examined to determine compliance with the nondeformation requirements of 3.4.4.11. Inability of the base to meet requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

4.5.4 Case depth test. The depth of the case hardening of the cutting wheel of the type I, class 2 opener shall be microscopically determined in accordance with ASTM E 1077. The determination shall be made at a point midway between the wheel edge and center of the wheel.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2)

5.1.1 Level A preservation.

5.1.1.1 Preservation application. Each can opener shall be cleaned by process C-1 and dried in accordance with MIL-P-116. The blade or feed and cutting wheels, magnet, and exposed uncoated ferrous metal surfaces shall be coated with preservative conforming to type P-14 of MIL-P-116. Coated surfaces of the type II and III openers from which preservative might be removed by contact with packaging material, shall be covered or wrapped with grease-proof barrier material conforming to type II, grade A of MIL-B-121. The barrier material shall be secured in place with tape conforming to type III, grade B of PPP-T-45.

5.1.1.2 Lubrication. All points of the can opener requiring lubrication shall be lubricated to capacity with the manufacturer's recommended food service equipment grade lubricant, which will not cause food contamination.

5.1.1.3 Unit packing.

5.1.1.3.1 Type I, classes 1 and 2 openers. Each opener, preserved as specified in 5.1.1.1, shall be placed in a snug fitting bag conforming to type I, class C of MIL-B-117.

5.1.1.3.2 Type II openers. Each complete opener, preserved and lubricated as specified in 5.1.1.1 and 5.1.1.2, shall have the wood screws, lid lifter, and wall screw plate, when detachable, placed in a snug fitting end opening style envelope made of 30 pound basis weight kraft paper conforming to A-A-203. The envelope shall be closed and taped to the extension arm. Each opener shall then be unit packed in a snug fitting or set-up paperboard box conforming to variety 1, style III, type G, class i or style IV, type J, class i of PPP-B-566 or type I, variety 1, class A or B, style 4 of PPP-B-676, respectively. Closure shall be in accordance with the appendix of the applicable box specification.

5.1.1.3.3 Type III and type IV openers. Each complete opener, preserved and lubricated as specfied in 5.1.1.1 and 5.1.1.2, shall have the operational feed, cutting wheel, and blade parts secured in place. The base of each opener and, when provided, the lid lifter shall be detached from the unit and placed on edge over the shaft flush with the bottom and secured in that position. Each opener shall then be unit packed in a snug fitting fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Fiberboard

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

pads of the same material as the box shall be used to secure the opener in a fitted position within the box. Box closure shall be in accordance with the appendix of PPP-B-636.

5.1.1.4 Intermediate packing. Fifty type I, class 1, grade A or fifty type I, class 1, grade B openers, unit packed as specified in 5.1.1.3.1, shall be packed in an intermediate snug-fitting full telescope box as specified in 5.1.1.3.2.

5.1.2 Commercial preservation. The can openers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Six hundred type I, class 1, grade A or B; or fifty type I, class 2, grade A or B openers; sixty type II, grade A or B openers; six type III, grade A or B openers; or six type IV openers preserved as specified in 5.1, shall be packed in a snug fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Six hundred type I, class 1, grade A or B; fifty type I, class 2, grade A or B openers; sixty type II, grade A or B openers; six type III, grade A or B openers; or six type IV openers, preserved as specified in 5.1, shall be packed in a snug fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Openers preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), openers, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means C and D or film bonding F or G. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract or purchase order, interior packs and shipping containers shall be marked in accordance with FED-STD-123 or ASTM D 3951, as applicable.

5.4.2 Military requirements. In addition to any special marking required by the contract or purchase order, interior packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The can openers are intended to open round, square, and oblong standard food cans. The type I, classes 1 and 2 and the type II openers are used for opening all cans up to and including No. 10 cans. The type III and type IV openers are used for opening all cans up to and including No. 12 cans. The grade A openers are used for general use. The grade B openers are used on ships and in areas where severe corrosive conditions prevail.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type, class, and grade required (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. When a magnetic lid lifter is required on the type III opener (see 3.4.4.9).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be an initial production sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing.

Food cans
Kitchen utensils

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Navy - MS
Air Force - 84

User activities:

Navy - CG, MC, YD

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

Army - GL

(Project 7330-0614)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	FF-0-601F	90/03/30

3. DOCUMENT TITLE
OPENERS, CAN, HAND AND MOUNTED

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
U.S. Army Natick Research, Development, and Engineering Center ATTN: SIRNC-ES	(508)651-5221	8-256-5221
c. ADDRESS (Include Zip Code) Kansas Street Natick, MA 01760-5014	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 Previous editions are obsolete 198-290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.