DATA ITEM DESCRIPTION
Title: ELECTROMAGNETIC INTERFERENCE TEST REPORT (EMITR)

Number: DI-EMCS-80200D
AMSC Number: 10705
DTIC Applicable: No
Preparing Activity: **11** (AFLCMC/EZAC)
Applicable Forms: None

Approval Date: 20261013
Limitation: N/A
GIDEP Applicable: No
Project Number: EMCS-2026-003

Use/Relationships: The EMITR provides the data and information necessary to evaluate compliance of an equipment or subsystem with its electromagnetic interference (EMI) control requirements based on MIL-STD-461, including the discussion of recommended corrective actions, if needed.

a. This Data Item Description (DID) contains the format, content, and intended use information for the data deliverable resulting from the work task described for the EMITR in 5.1 of MIL-STD-461.

b. This DID is related to DI-EMCS-80199D, Electromagnetic Interference Control Procedures (EMICP), and DI-EMCS-80201D, Electromagnetic Interference Test Procedures (EMITP). (Copies of this document are available online at https://quicksearch.dla.mil.)

c. DI-EMCS-80200D supersedes DI-EMCS-80200C.

Requirements:

1. Reference documents. The applicable issue of the documents cited herein, including their approval dates and dates of any applicable amendments, notices, and revisions, shall be as specified in the contract.

2. Format. Contractor format is acceptable.

3. Content. The EMITR shall contain the following:

3.1 Administrative data. The EMITR shall contain an administrative section covering the following:

a. Contract number.

b. Authentication and certification of performance of the tests by a qualified representative of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:35Z
Check the source to verify that this is the current version before use.

c. Disposition of the Equipment Under Test (EUT).

d. Description of the EUT, including its function, characteristics, intended installation, actual cable types (characteristics and construction details - see 4.3.8.6 of MIL-STD-461), and electrical current usage on each power input line.

e. EUT modes of operation for each test, including operating frequencies (where applicable), and rationale for selection. The rationale shall include how it was determined that the EUT is operating in its most emissive and most susceptible modes (see 4.3.9 of MIL-STD-461).

f. List of tests performed with pass/fail indications.

g. Any approved deviations from contractual test procedures or limits previously authorized.

h. Identification of Non-Developmental Items (NDI) and Government Furnished Equipment (GFE) that may be part of the EUT.

i. Traceability of test equipment calibration.

j. Provide an embedded approved EMITP or a reference for it.

3.2 Detailed results. A separate appendix shall be prepared for each test. If deviations from an approved test procedure occurred during the test program, an additional appendix shall be provided with the “as run” procedures showing all red-lines and procuring activity concurrence. A separate appendix shall be provided for log sheets. Each test appendix shall contain the following factual data:

a. Test equipment nomenclature, serial numbers, version of software used (if any), and calibration due date.

b. Photographs or diagrams of the actual test set up and EUT, with identification.

c. Transfer-impedance of current probes.

d. Antenna factors.

e. Impedance values of Line Impedance Stabilization Networks (LISN).

f. Identification of any suppression devices used to meet the contractual requirements, including schematics, performance data, and drawings.

g. Sample calculations, such as conversions of measured levels for comparison against the applicable limit.

h. The ambient radiated and conducted electromagnetic emission profile of the test facility, when necessary.

i. Data, and data presentation, as specified in the “data presentation” sections of the individual test procedures of MIL-STD-461. Emissions data cannot be provided on one single sheet (plot). Provide a minimum frequency resolution of 1% or twice the measurement receiver bandwidth, whichever is less stringent, and a minimum amplitude resolution of 1 dB for each plot.

j. Scan speeds.

k. Measurement receiver bandwidths.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:35Z
Check the source to verify that this is the current version before use.

l. Antenna polarization.

m. Power line voltages, frequencies, and power-factor.

n. Low-noise amplifiers (LNA) compression points.

o. Test susceptibilities and deviations from normal performance are not acceptable. However, when susceptibility indications or deviations from normal performance are noted in the EUT operation, a threshold level shall be determined where the susceptible condition or deviation is no longer present. These thresholds need to be documented for further assessment.

3.3 Conclusions and recommendations. Conclusions and recommendations shall be provided, including results of the tests in brief narrative form, a discussion of any remedial actions already initiated, and proposed corrective measures required (if necessary) to assure compliance of the equipment or subsystem with the contractual EMI requirements.

End of DI-EMCS-80200D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:35Z
Check the source to verify that this is the current version before use.