MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED SCHOTTKY TTL,
FLIP-FLOPS, CASCADABLE, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/341E, dated 28 April 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete and substitute as printed above.

PAGE 3

Setup time J, K, or D low to clock pulse, device type 02: Delete and substitute as follows:

"Device type 02 - 4.0 *ns minimum*"

PAGE 6

TABLE I, I_{IL1}, minimum limits column: Delete "-0.3" and substitute "0.0".

TABLE I, I_{IL2}, minimum limits column: Delete "-0.9" and substitute "0.0".

TABLE I, I_{IL3}, minimum limits column: Delete "-.12" and substitute "0.0".

PAGE 51

TABLE III, device type 03, test number 92, J_1 and J_2 columns: Delete "„" and substitute "A".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1295)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:21Z
Check the source to verify that this is the current version before use.