INCH-POUND

MIL-M-38510/341E
AMENDMENT 2
17 June 1993
SUPERSEDING
AMENDMENT 1
26 October 1992

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED SCHOTTKY TTL,
FLIP-FLOPS, CASCADABLE, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/341E, dated 28 April 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete and substitute as printed above.

PAGE 3

Setup time J, K, or D low to clock pulse, device type 02: Delete and substitute as follows:

"Device type 02 - 4.0 ns minimum"

PAGE 6

TABLE I, I_{IL1}, minimum limits column: Delete "-0.3" and substitute "0.0".

TABLE I, I_{IL2}, minimum limits column: Delete "-0.9" and substitute "0.0".

TABLE I, I_{IL3}, minimum limits column: Delete "-.12" and substitute "0.0".

PAGE 45

* TABLE III, device type 01, footnote 8/: Add the following: "f_{MAX} shall be measured only under the conditions of initial qualification and after process or design changes which may affect this parameter. For all other conditions, f_{MAX} shall be guaranteed, if not tested, to the limits specified in table III, herein."

PAGE 51

* TABLE III, device type 03, test number 91, J_1 and J_2 columns: Delete "„" and substitute "A".

TABLE III, device type 03, test number 92, J_1 and J_2 columns: Delete "„" and substitute "A".

PAGE 56

* TABLE III, device type 04, footnote 7/: Add the following: "f_{MAX} shall be measured only under the conditions of initial qualification and after process or design changes which may affect this parameter. For all other conditions, f_{MAX} shall be guaranteed, if not tested, to the limits specified in table III, herein."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:21Z
Check the source to verify that this is the current version before use.

PAGE 63

* TABLE III, device type 05, footnote 5/: Add the following: "f_{MAX} shall be measured only under the conditions of initial qualification and after process or design changes which may affect this parameter. For all other conditions, f_{MAX} shall be guaranteed, if not tested, to the limits specified in table III, herein."

PAGE 71

* TABLE III, device type 06, footnote 5/: Add the following: "f_{MAX} shall be measured only under the conditions of initial qualification and after process or design changes which may affect this parameter. For all other conditions, f_{MAX} shall be guaranteed, if not tested, to the limits specified in table III, herein."

PAGE 74

* TABLE III, device type 07, footnote 7/: Add the following: "f_{MAX} shall be measured only under the conditions of initial qualification and after process or design changes which may affect this parameter. For all other conditions, f_{MAX} shall be guaranteed, if not tested, to the limits specified in table III, herein."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, correction, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1346)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:21Z
Check the source to verify that this is the current version before use.