INCH-POUND
MIL-DTL-3971/2D
24 January 2001
SUPERSEDING
MIL-M-3971/2C
13 December 1985

DETAIL SPECIFICATION SHEET

METERS, TIME TOTALIZING, NON-HERMETICALLY SEALED, ELECTRICAL: TYPE II, 120V, 60CPS AND 120V, 400CPS GRADES A AND B, 2 HOLE AND 3 HOLE FLANGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring meters described herein shall consist of this document and the issue in effect of MIL-DTL-3971.



FIGURE 1. Meter with 3 hole flange.

AMSC N/A FSC 6645

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:11Z
Check the source to verify that this is the current version before use.



FIGURE 2. Meter with 2 hole flange.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:11Z
Check the source to verify that this is the current version before use.

TABLE I. Specification data for type II meters.

DASH NO.	FIG	A	B	C	D	E	F	G	Grade	Hz	Range	Readout
1	1	2.695	1.220	.125	2.210	3.00	—	—	A	60	100,000	99999.9
2	1	3.500	1.580	.150	2.625	3.00	—	—	A	60	100,000	99999.9
3	1	2.875	1.265	.150	2.210	3.00	—	—	A	400	10,000	9999.9
4	1	3.500	1.580	.150	2.625	3.00	—	—	A	400	10,000	9999.9
5	1	2.695	1.220	.125	2.210	3.00	—	—	B	60	100,000	99999.9
6	1	3.500	1.580	.150	2.625	3.00	—	—	B	60	100,000	99999.9
7	1	2.875	1.265	.150	2.210	3.00	—	—	B	400	10,000	9999.9
8	1	3.500	1.580	.150	2.625	3.00	—	—	B	400	10,000	9999.9
9	2	2.120	1.750	.045	.936	1.950	1.020	1.450	A	60	100,000	99999.9
10	2	2.120	1.750	.045	.936	1.950	1.020	1.450	B	60	100,000	99999.9

Notes:

1. Dimensions are in inches (in.).

2. Tolerances: Dimensional ± 0.015 in., bolt holes ± .005 in. unless otherwise indicated. Angular ± 0.5°.

3. Range and readout are in hours and tenths of hours.

1. REQUIREMENTS

1.1 Dimensions of case. See figures 1 and 2 and table I as applicable.

1.2 Colors, elapsed time indicator:

Hours: White on black background

Tenths: Black on white background

1.3 Power consumption. Not applicable.

1.4 Dielectric strength. Voltage – Dash numbers 1,2,5,6,9 & 10 – 1000 volts rms
– Dash numbers 3,4, 7 & 8 – 500 volts rms

Frequency – 60 Hz

Potential – ac

Points of application – Terminals and case

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:11Z
Check the source to verify that this is the current version before use.

1.5 Weight. 1.00 lb. maximum.

1.6 Starting. Energize for 60 seconds at +22°C (±2°C), de-energize for 180 seconds, repeat 5 times. The meter shall start within 10 seconds.

1.7 Stopping. The meter shall stop within 120 seconds after being de-energized.

1.8 Power supply tolerance. 60 Hz meters – one-half hour at 115 volts, 50 Hz

one-half hour at 128 volts, 70 Hz

400 Hz meters – one-half hour at 115 volts, 300 Hz

one-half hour at 128 volts, 500 Hz

1.9 Part number. The part number consists of the basic number of this specification sheet and a dash number taken from table I.

Example:

M3971/2-1

Basic number

Specification sheet number

Dash number from Table I

Custodians:
Army – AR
Navy – SH
Air Force – 99

Preparing activity:
DLA-GS

(Project 6645-0504)

Reviewers:
Army – AT, CR
Navy – AS, SA, MC, EC
Air Force – 11

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1,2,3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4,5,6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractural requirements.

I RECOMMEND A CHANGE	1.DOCUMENT NUMBER MIL-DTL-3971/2D	2.DOCUMENT DATE *(YYMMDD)* 010124

3.DOCUMENT TITLE METERS, TIME TOTALIZING, NON HERMETICALLY SEALED, ELECTRICAL: TYPE II, 120V, 60CPS AND 120V, 400CPS GRADES A AND B, 2 HOLE AND 3 HOLE FLANGE

4.NATURE OF CHANGE*(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5.REASON FOR RECOMMENDATION

6.SUBMITTER

a.NAME *(Last, First, Middle Initial)*	b.ORGANIZATION	
c.ADDRESS *(Include Zip Code)*	d.TELEPHONE (Include Area Code) (1)Commercial (2)DSN(If applicable)	7.DATE SUBMITTED *(YYMMDD)*

8.PREPARING ACTIVITY

a.NAME L. Craig Hammond	b.TELEPHONE *(Include Area Code)* (1) Commercial (804) 279-5019 (2) DSN 695-5019
c.ADDRESS *(Include Zip Code)* ATTN: DSCR-VBD Defense Supply Center Richmond Richmond, VA 23297-5610	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:11Z
Check the source to verify that this is the current version before use.