MILITARY SPECIFICATION SHEET

WAVEGUIDE ASSEMBLIES, RIGID, CAST, 45-DEGREE H-PLANE BEND, FULL CORRAL AND SELF-JIGGING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the waveguide assemblies described herein shall consist of this document and the latest issue of Specification MIL-W-3970.





FIGURE 1 Dimensions for self-jigging waveguide assembly, for dash number 001

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.




OPTIONAL CONFIGURATION

INCHES	MM	INCHES	MM
.003	08	400	10 16
004	.10	502	12 75
010	25	60	15 2
01	.3	750	19.05
.018	.46	900	22 86
.03	8	1 002	25 45
04	1 0	1 16	27 9
06	1 5		

NOTES·
1 Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm

FIGURE 1 Dimensions for self-jigging waveguide assembly, for dash number 001 - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
003	08	400	10 16
004	10	502	12 75
010	.25	.60	15 2
01	3	.750	19 05
018	46	900	22 86
03	8	1 002	25 45
04	1 0	1 16	27 9
.06	1 5		

NOTES
1 Dimensions are in inches.
2 Metric equivalents are given for general information only and are based upon 1 00 inch = 25 4 mm.

FIGURE 2 Dimensions for full corral configuration, for dash number 002

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Physical characteristics
Dimensions and configuration See figures 1 and 2.
Operating temperature range -55° to +300°C.
Body material D712.0, temper F, aluminum alloy per QQ-A-601 or C712.1 per QQ-A-371.
Surfaces (sandblasting after machining permissible)
Internal $63\sqrt{}$ microinches per ANSI B46.1.
External $125\sqrt{}$ microinches per ANSI B46.1

Fungus resistance Materials nutrient to fungus shall not be used.

Pressurization 45 lb_f/in^2 gage maximum.

Penetrant inspection No indication of any cracks at any location when tested per MIL-I-6866, type I, method B.

Electrical characteristics
Frequency range 8.2 to 12.4 GHz.
VSWR 1.05 1 maximum.
Power
Peak - 250 kW.
Average - 10 kW.

Part number M3970/26- (dash number from figures 1 and 2).

NOTE The mating waveguides are M85/1-077, -078, and -178.

Custodians
Army - EL
Navy - EC
Air Force - 85

Review activities
Army - MI,
Navy - EC, OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR
Navy - MC, CG, AS
Air Force - 14, 19

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5985-0881-6)

☆U.S. GOVERNMENT PRINTING OFFICE 1978—603 222/4753

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22 R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE
MIL-W-3970/26

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:09Z
Check the source to verify that this is the current version before use.