INCH-POUND
MIL-PRF-52308J
AMENDMENT 1
20 March 2003

PERFORMANCE SPECIFICATION

FILTER-COALESCER ELEMENT, FLUID PRESSURE

This Amendment forms a part of MIL-PRF-52308J, dated 27 July 2002, and is approved for use by the U.S. Army Tank-automotive and Armaments Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Paragraph 2.2 - Under "AMERICAN PETROLEUM INSTITUTE (API)", at the end of title: "API 1581" delete: "Fourth Edition."

PAGE 5

Paragraph 4.3.2 – Delete and substitute:

"4.3.2 Sampling. Sampling for examinations and tests shall consist of elements randomly selected from production lots. Randomly, one out of every five production lots shall be selected for conformance testing. A total of eight elements shall be submitted from each production lot that is selected for conformance testing. All eight of the submitted samples shall be subjected to 4.5.1, Examination, three of the submitted samples shall be subjected to 4.5.2, Structural Strength, and one shall be subjected to 4.5.3, Differential Pressure/Operational Performance."

PAGE 5

Paragraph 4.4.1 – Delete and substitute:

"4.4.1 Test facility. The test facility shall be in accordance with API 1581, section 4.2.1, Test Apparatus. Testing shall be conducted at a site selected by the Government in the contract or order (see 6.2). Both single element and full-scale tests shall be conducted using the military vessel configuration of concentric, vertical elements and separators. The single element test vessel shall be a uniform standard, single element vessel constructed by the Government. The full-scale test vessel shall be a military standard 50 GPM filter-separator vessel, LIN H51915. The full-scale vessel, having four elements, shall be operated at 80 GPM, or 100% of rated flow per element. Both the single element and full-scale test vessels may be made available to the contractor upon request, for preliminary qualification testing. The facility shall contain calibrated and certified measuring equipment."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

PAGE 7

Paragraph 4.5, table I – Delete table and substitute:

TABLE I. Inspection requirements.

Inspection	First Article (9+ samples)			Conformance
	FAT, set 1 (3+ samples)	FAT, set 2 (2+ samples)	FAT, set 3 (4+ samples)	(8 samples)
Examination, 4.5.1	X	X	X	X (all samples)
Structural strength, 4.5.2	X			X (3 samples)
Differential pressure, operational performance, 4.5.3		X		X (1 sample)
Transit drop, 4.5.4.1			X	
Resistance to fuel, high temp, 4.5.4.2			X	
Resistance to fuel, low temp, 4.5.4.3			X	
Resistance to salt water, 4.5.4.4			X	
Post-environmental performance, 4.5.4.5			X	

PAGE 9

Paragraph 6.2(g) - Delete and substitute: "Test site location (see 4.4.1)."

Custodians:
Army – AT
Navy – AS
Air Force – 11

Preparing activity:
Army - AT

(Project 4330-0164)

Review activities:
Army – AV, MI
Navy - MC
Air Force – 68, 99
DLA – CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.