INCH-POUND

MIL-PRF-52348D
01 February 1999
SUPERSEDING
MIL-P-52348C
26 July 1989

PERFORMANCE SPECIFICATION

PACKING KIT, HOSELINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a packing kit used as an aid in repackaging the hose assemblies of a collapsible hoseline system.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in section 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specification, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

MIL-PRF-52262 – Hose Assembly, Elastomeric: Lightweight, Collapsible, 4-inch

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available, from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

Beneficial comments, recommendations, additions, deletions, and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-D/210, Warren, MI 48397-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3835

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The hoseline packing kit (hereinafter called “kit”) shall contain the items necessary to repackage the hose assembly, as defined in MIL-PRF-52262. The components shall be contained in a container for storage, ease of handling, and transport.

3.2 First article. Unless otherwise specified (see 6.2), a kit shall be subjected to first article inspection in accordance with 4.2.

3.3 Operational characteristics.

3.3.1 Kit components. The kit shall be composed of items, and quantities, as listed in table I.

TABLE I. Hoseline packing kit components.

Item	Description	Ref. para.	Quantity
a	Compression component.	3.3.3	1
b	Hose retaining device, set.	3.3.4	2
c	Pressure device.	3.3.5	1

3.3.2 Hoseline assembly repackaging. The kit shall repackage the hoseline, in accordance with the prescribed procedures of the flaking box loading plan in MIL-PRF-52262.

3.3.3 Compression component. The compression component shall function, in conjunction with a flaking box (MIL-PRF-52262), and components identified herein to compress the hose assembly for repackaging. The compression component shall not twist or rotate, nor shall it cause the hose to twist or rotate. The compression components shall also provide a straight, full width and height, compression of the hose.

3.3.4 Hose retaining device. A retaining clamp, or similar device, shall be used to secure the compressed segments of hose assembly in the flaking box during compression. The device shall hold the compressed segment when the compressing force is removed. Each device shall be provided to hold against approximately 750 pounds of force. The device shall not require tools to install or remove. Two complete sets of the hose-retaining device shall be required.

3.3.5 Pressure device. A pressure device shall be used to apply force to the compression component. The force to be applied shall be not less than 1500 pounds. The force shall be applied evenly to the compression component as the hose assembly is being compressed. The pressure device shall not interfere with the flaking of hose assembly and be easily removable for reuse or return to the storage container.

3.3.6 Container. A container shall be provided for storage and transport of the kit components. The container shall not exceed 22 inches in height. The container shall be sufficiently strong to support all components when lifted. The container shall have bins, cradles, or blocking to prevent component damage during shipment and handling. The container shall have a cover and a means to secure the cover in the closed position. The cover shall open to expose the contents of the container without separating from it. The cover shall be self-supporting in the open. A loading diagram shall be fixed to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

the inside of the cover, visible to the operator while loading. The diagram shall provide pictorial/verbal instruction for loading the kit components into the container. Handles shall be provided in sufficient number to permit lifting by personnel, based on a 40-pound lift capability per handle.

3.4 Environment.

3.4.1 Operating temperature. The packing kit shall meet requirements specified when operated in temperatures ranging from 25 °F to 120 °F.

3.4.2 Storage temperature. The packing kit shall not be damaged or specified performance degraded by extended storage in temperatures ranging from -45 °F to 165 °F.

3.5 Interface.

3.5.1 Hose assembly. The packing kit components shall interface with the components of the MIL-PRF-52262 hose assembly, dimensionally and functionally, to accomplish repackaging of the hoseline.

3.5.2 Government furnished property. The government shall make available MIL-PRF-52262 flaking boxes and hose assemblies (see 6.2) for use in first article testing.

3.6 Support and ownership requirements.

3.6.1 Materials. Materials shall be selected by the contractor and shall be subject to all provisions of this specification. The container and component of the kit shall be fabricated from compatible materials, inherently corrosion resistant, or treated to provide protection against the various forms of corrosion or deterioration.

3.6.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion (see 6.5.2).

3.6.1.2. Recovered materials. The components, pieces, and parts incorporated into the kit may be newly fabricated from recovered materials (see 6.5.3) to the extent practicable, provided that the packing kit produced meets all other requirements of this specification. Used, rebuilt, or re-manufactured components, pieces and parts shall not be incorporated into the kits.

3.6.2 Color and marking. Color and markings of the container and components shall be as specified by the contract or order (see 6.2).

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First article inspection. When specified in the contract or order, the first article inspection shall be performed on a minimum of one kit (see 3.2 and 6.2). This inspection shall include the examinations of table II and first article tests indicated in table III. Non-conformance to any specified requirement, the failure of any test, or the presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection. Conformance inspection shall be performed on all kit production units and shall include the examinations indicated in the conformance column of table II. Non-conformance to any specified requirement, the failure of any test, or the presence of one or more defects shall be cause for rejection.

4.4 Examination. The first article kit shall be examined as specified in table II. "Accept" criterion is an item that conforms to the requirements in the referenced paragraph; the "reject" criterion" is an item that does not conform to the referenced paragraph.

TABLE II. Examination schedule

Exam	First article	Conf.	Examination description	Ref. para.	Method of inspection
101	X	X	Kit components not in quantities as specified.	3.3.1	Visual \ Doc
102	X		Compression component not as specified.	3.3.3	Visual \ SIE
103	X		Hose retaining device not as specified.	3.3.4	Visual \ SIE
104	X		Pressure device not as specified.	3.3.5	Visual \ Doc
105	X	X	Container not as specified.	3.3.6	Visual \ SIE
106	X		Materials not as specified.	3.6	Visual \ Doc
107	X	X	Color and marking not as specified.	3.6.2	Visual \ Doc

Doc = Documentation, SIE = Standard Inspection Equipment

4.5 Tests. Testing shall be conducted as specified in table III.

TABLE III. Test schedule.

Test	Description	Ref. para.	Test para.
101	Hose assembly repackaging.	3.3.2	4.5.1
102	Compression component.	3.3.3	4.5.1
103	Hose retaining clamps.	3.3.4	4.5.1
104	Pressure device.	3.3.5	4.5.1
105	Container.	3.3.6	4.5.1
106	Low temperature.	3.4	4.5.2
107	High temperature.	3.4	4.5.3

4.5.1 Kit test. From a complete hose assembly (MIL-PRF-52262) packed in a flaking box, extract the hose assembly to full length and remove all additional components. Utilizing the kit, the kit manufacturer's procedures, and the flaking box loading diagram, repackage the hose assembly and components into the flaking box. Failure to properly compress the hose assembly to fit within the flaking box shall constitute failure of this test. Failure of the kit components to be repackaged according to the flaking box loading diagram shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

4.5.2. Low temperature. Place a flaking box, with hose assembly, and a packing kit in a controlled temperature chamber. Lower the temperature to -45 ±2 °F and maintain for 24 hours. At the end of 24 hours, while maintaining a -45 ±2 °F temperature, conduct a visual examination of the packing kit for damage or deformation. Raise the chamber temperature to 25 ±2 °F and maintain for 12 hours. While maintaining a 25 ±2 °F temperature, perform a kit test (see 4.5.1). Damage or deformation from exposure to low temperature storage shall constitute cause for rejection. Failure of the packing kit components to perform as specified herein at the low operating temperature shall constitute failure of this test.

4.5.3 High temperature. Place a flaking box, with hose assembly, and a packing kit in a controlled temperature chamber. Raise the temperature to 160 ±2 °F and maintain for 24 hours. At the end of 24 hours, while maintaining a 160 ±2 °F temperature, conduct a visual examination of the packing kit for damage or any deformation. Lower the chamber temperature to 120 ±2 °F and maintain for 12 hours. While maintain a 120 ±2 °F perform a kit test (see 4.5.1). Showing signs of damage, or deformation, at the high storage temperature shall constitute cause for rejection. Failure of the packing kit components to perform as specified herein at the high operating temperature shall constitute failure of this test.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The hoseline packing kit is to be used in the repackaging of a dispensed hose assembly and components into a flaking box as defined in MIL-PRF-52262. The item is military unique in that there are no equivalent flaking sub-systems used in commercial applications. Further, like commercial systems, that may be adapted, will not withstand the diversity of environments and field conditions in which the kit is to be used.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

a. Title, number, and date of this publication.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1).
c. When and if first article is required, number of units required, and time frame for submission (see 3.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

d. Source of the government loaned property and whether the government loaned property will be provided for first article (see 3.5.2 and 6.4).

e. Color and markings required (see 3.6.2).

f. Packaging requirements (see 5.1).

6.3 First article. When a first article inspection is required, the item should be a first article production unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first test results, and disposition of the first article.

6.4 Government furnished property. The contracting officer should include specific instructions on obtaining and returning the government furnished property.

6.5 Definitions.

6.5.1 Flaking box A container for the storage, transport, dispensing, and recovery of a hose assembly as defined by MIL-PRF-52262.

6.5.2 Dissimilar metals. For its purpose, this document considers metals dissimilar when two specimens in contact with each other promote accelerated galvanic corrosion (see 3.6.1.1).

6.5.3 Recovered materials. Recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials (see 3.6.1.2).

6.6 Data requirements. The requirement for technical manuals should be considered when this specification is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DoD 5010.12 L, Acquisition Management Systems and Data Requirements Control List should be listed on a separate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals should be acquired under a separate contract line item in the contract.

6.7 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including special tools), and instructions on shipment of the kit.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

6.9 Subject term (key word) listing.

Compression component
Flaking box
Hose retaining device

Custodian: Preparing activity:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

Army – AT
Navy – YD2

Review Activities:
DLA – CC

Army – AT

(Project 3835-5002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter must be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-52348D	2. DOCUMENT DATE (YYMMDD) 990201

3. DOCUMENT TITLE
PACKING KIT, HOSELINE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME USA TARDEC, AMSTA-TR D/210 (IPDS)	b. TELEPHONE (Including Area Code) (1) Commercial (810)574-4126 (2) DSN 786-4126
C. ADDRESS (Include Zip Code) US Army Tank-automotive and Armaments Command Attn: AMSTA-TR-D/210 Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 681-9340 DSN 761-9340

Source: https://assist.dla.mil - Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.