MILITARY SPECIFICATION

BODY SECTION, TRAINING, ATOMIC PROJECTILE, FRONT

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of front body section for M423 Projectile.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 ----- Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 --- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 -- Lot Numbering of Ammunition
MIL-STD-1169 -- Packaging, Packing and Marking for Shipments of Inert Ammunition

FSC 1110

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8787194 -------	Body Section, Training, Atomic Projectile, Front
8808268 -------	Ring, Forward
8808269 -------	Ring, Rear
8808270 -------	Cylinder, Training
8808362 -------	Packing and Marking for Storage and Shipments
8811089 -------	Carton, Packing, Ammunition, for Body Section, Front: Training
ET-8787194 ----	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in accordance with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The body section shall comply with all requirements specified on the drawing (dwg) 8787194, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.4 Serialization. The contractor shall assign serial numbers as required by drawings.

3.4.1 Unclassified items. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.4.2 Classified items. Production quantities shall not be revealed. Random serial numbers shall be selected by the contractor in a manner which has been approved by the procuring agency. These numbers shall not be duplicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.1.2 Inspection lot. A lot or batch and its formation, size and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Tables I and II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II

Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Ring, forward (see dwg 8808268) covering a detail of dwg 8787194.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Rear internal diameter, max.	Gage
102.	Material (see 3.1)	Visual
Minor		
201.	Diameter of undercut, max.	Gage
202.	Length of undercut, max.	Gage
203.	Length from rear end to forward face of undercut, max.	Gage
204.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.2 Ring, rear (see 8808269) covering a detail of dwg 8787194.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Forward internal diameter, max.	Gage
102.	Material (see 3.1)	Visual
Minor		
201.	Diameter of undercut, max.	Gage
202.	Length of undercut, max.	Gage
203.	Length from forward end to rear face of undercut, max.	Gage
204.	Workmanship (see 3.4)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Cylinder, training (see dwg 8808270) covering a detail of dwg 8787194.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Concentricity of small diameter	Gage
102.	Location of 4 threaded holes	Gage
103.	Pitch diameter of thread of 4 small holes	Gage
104.	Minor diameter of thread of 4 small holes	Gage
105.	Depth of counterbore in bottom of rear cavity, min.	Gage
106.	Small diameter of 4 small holes, min.	Gage
107.	Counterbore diameter of 4 small holes, min.	Gage
108.	Length of thread and counterbore of 4 small holes, min.	Gage
109.	Length of thread and counterbore, including runout of 4 small holes, max.	Gage
110.	Depth of counterbore of 4 small holes, min.	Gage
111.	Large outside diameter	Gage
112.	Material (see 3.1)	Visual
Minor		
201.	Location of face holes and large thread holes	Gage
202.	Pitch diameter of large thread	Gage
203.	Minor diameter of large thread, max.	Gage
204.	Depth from rear end to bottom of large cavity	Gage
205.	Total length	Gage
206.	Distance from rear end to front external shoulder, min.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

207.	Distance from rear end to rear external shoulder, max.	Gage
208.	Diameter of face holes, min.	Gage
209.	Diameter of counterbore in bottom of rear cavity, min.	Gage
210.	Outside diameter of forward end, max.	Gage
211.	Outside diameter of rear end, max.	Gage
212.	Large diameter of ring grooves around 4 small holes, min.	Gage
213.	Small diameter of ring grooves around 4 small holes, max.	Gage
214.	Rear internal diameter	Gage
215.	Bore diameter	Gage
216.	Length from rear end to internal chamfer	Gage
217.	Depth of ring grooves, min.	Gage
218.	Angularity of chamfer at both ends	Gage
219.	Radius present and correct	Visual
220.	Stamping complete, correct, identifiable and not mislocated (prior to plating)	Visual
221.	Serialization (see 3.3)	Visual
222.	Proper protective finish no bare spots	Visual
223.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.4 Body section, training, atomic projectile, front (see dwg 8787194).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Pitch diameter of forward thread	Gage
102.	Minor diameter of forward thread	Gage
103.	Pitch diameter of rear thread	Gage
104.	Minor diameter of rear thread, max.	Gage
105.	Rear outside diameter	Gage
106.	Forward outside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

Minor

201.	Distance from rear end to bottom of large cavity, min.	Gage
202.	Location of rear pin holes	Gage
203.	Location of forward pin holes	Gage
204.	Depth of two rear pin holes	Gage
205.	Depth of two forward pin holes, max.	Gage
206.	Depth of rear and forward thread reliefs, max.	Gage
207.	Diameter of rear thread relief, max.	Gage
208.	Diameter of forward thread relief, max.	Gage
209.	Location of wrench slots, min.	Gage
210.	Width of wrench slots	Gage
211.	Total length	Gage
212.	Large outside diameter	Gage
213.	Angle at forward end present	Visual
214.	No pin loose or missing	Visual/Manual
215.	Raised metal caused by drilling or stamping removed	Visual/Manual
216.	Any pin below flush with periphery of ring body	Visual/Manual
217.	Components mate correctly	Visual/Manual
218.	No pin hole broken thru internal diameter of training cylinder	Visual
219.	Serialization (see 3.3)	Visual
220.	Stamping complete, correct, identifiable and not mislocated	Visual
221.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.5 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection

Critical: None defined

Major

101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169	Visual/Manual

Minor: None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Carton, packing, ammunition, for body section, front: training (see dwg 8811089 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Carton sealed properly	Visual
102.	Contents tight in carton	Manual
103.	Corners of carton blunted	Visual/Manual
104.	Bag sealed properly	Visual
105.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual
106.	Packaging material (see 3.1)	Visual
Minor		
201.	Marking	Visual
202.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.7 Packing and marking for storage and shipments (see dwg 8808362 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Gross load weight, max.	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Package material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor		
201.	Marking	Visual
202.	Workmanship (see 3.4)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions and calibration instructions specified on the Equipment Lists (EL's). EL's for assemblies are listed on the Equipment Tabulation, ET-8787194. When either of the conditions listed below exists, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The body section shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The body section shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The body section shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The body section shall be packaged in accordance with dwgs 8811089 and 8808362, using the specified moisture barrier.

5.2.1.2 Level C. The body section shall be packaged in accordance with dwgs 8811089 and 8808362, except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Levels A and C. The body section shall be packed in accordance with dwgs 8811089 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8811089 and 8808362, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number and date of this specification.

b. Production or repair parts.

c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirments (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-N-I.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1110-A037

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-B-50892(MU) Body Section, Training, Atomic Projectile, Front

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.