MIL-F-48048C(AR)
29 October 1982
SUPERSEDING
MIL-F-48048B(PA)
17 October 1975

MILITARY SPECIFICATION

FLEXIBLE CABLE ASSEMBLY FOR M247 HEAT WARHEAD, ASSEMBLY AND PACKING

This specification is approved for use by the U. S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements and provides quality assurance provisions for the fabrication of parts, assembly and packing of one type of Flexible Printed Circuit which is intended for use in the Warhead, 2.75 Inch Rocket, HEAT.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provision, General Specification for

FSC: 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

STANDARDS

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9259235 - Flexible Cable Assembly

* (Copies of specifications, standards, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

* 2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

* 3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing (dwg.) 9259235 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Lamination of flexible printed circuit. There shall be no unbonded sections in the lamination of the flexible printed circuit when viewed under seven (7) power magnification.

* 3.4 Dielectric strength. The cable shall show no evidence of breakdown when subjected to a potential of 1500 volts alternating current when tested as specified in 4.5.1. (Breakdown shall be defined as a leakage current in excess of 20 microamperes).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

3.5 Insulation resistance. The insulation resistance between conductors shall not be less than 10^2 megohms when tested as specified in 4.5.2.

3.6 Conductor resistance. The resistance of each conductor circuit shall not exceed .5 ohms when tested as specified in 4.5.3.

3.7 Assembly force of base of the nose cap connector to the ogive. The base shall assemble to a fixture representing the nominal opening in the ogive and cross section form of the opening. The base shall not break or crack during assembly and shall be capable of being removed without breaking or cracking and shall withstand a disassembly force of 2 pounds minimum.

3.8 Assembly of flexible cable assembly to simulated fuze base assembly. The fuze end of the flexible cable assembly shall assemble to a simulated fuze base connector assembly with a force of five (5) pounds minimum and thirty-two (32) pounds maximum. Both socket connectors shall assemble at the same time and shall seat fully to the fixture and shall not exhibit cracked solder joints, cracked or delaminated cable when viewed under seven (7) power magnification. Thje electrical resistance between each pin of the simulated fuze base connector assembly and the contact in the nose cap connector shall not exceed 0.5 ohms.

3.9 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.10 Workmanship. The flexible cables furnished under this specification shall be manufactured and processed in a careful manner, and the workmanship shall be in accordance with good design and sound practice. The soldering shall be free from scratches, roughness, sharp edges, dullness, looseness, blistering, foreign matter and other evidence of poor workmanship that will render the assemblies unsuitable for the purposes intended. The flexible cables shall meet all requirements of this specification.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspections. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the Contractor may use his own or any other facilities suitable for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

of the inspection requirements specified herein, unless disapproved the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

4.2 Classification of inspections. Unless otherwide specified herein, or in the contract, the following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Contact, Nose Cap Connector Assembly	9278719	50
Retainer, Nose Cap Connector Assembly	9278720	50
Base, Nose Cap Connector Assembly	9278721	50
Cover, Nose Cap Connector Assembly	9278722	50
Flexible Printed Circuit	9259236	20
Cap, Base Connector	9259271	25
Socket, Connector	9259267	50
Flexible Cable Assembly	9259235	20

4.3.2 Inspections to be performed. See MIL-A-48078 and Tables I and II specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-F-48048C(AR)

PARAGRAPH	TITLE: Flexible Cable Assembly and Components		SHEET 1 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Contact, Nose Cap Connector Assembly (Dwg. 9278719)				
	Examination for defects	50		3.2	4.4.2.1
	Retainer, Nose Cap Connector Assembly (Dwg. 9278720)				
	Examination for defects	50		3.2	4.4.2.2
	Base, Nose Cap Connector Assembly (Dwg. 9278721)				
	Examination for defects	50		3.2	4.4.2.3
	Cover, Nose Cap Connector Assembly (Dwg. 9278722)				
	Examination fo defects	50		3.2	4.4.2.4
	Flexible Printed Circuit (Dwg. 9259236)				
	Examination for defects	20		3.2/3.3	4.4.2.5
	Dielectric strength test	10		3.4	3.5.1

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-F-48048C(AR)

PARAGRAPH	TITLE: Flexible Cable Assembly and Components (Continued)		SHEET 2 OF 2		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap, Base Connector (Dwg. 9259271)				
	Examination for defects	25		3.2	See Table II
	Socket, Connector (Dwg. 9259267)				
	Examination for defects	50		3.2	4.4.2.6
	Flexible Cable Assembly (Dwg. 9259235)				
	Examination for defects	20		3.2	4.4.2.7
	Insulation resistance test	20		3.5	4.5.2
	Conductor resistance test	20		3.6	4.5.3
	Assembly force tests	20		3.7/3.8	4.5.4/4.5.5

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE: Cap, Base Connector		SHEET 1 OF 1		DRAWING NUMBER: 9259271
					NEXT HIGHER ASSEMBLY: 9259235
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of connector recess		0.40%	3.2	Gage
102	Diameter of recess		0.40%	3.2	Gage
103	Depth of recess		0.40%	3.2	Gage
104	Length of connector max		0.40%	3.2	Gage
105	Width of connector, max		0.40%	3.2	Gage
106	Location of chamfer		0.40%	3.2	Gage
Minor					
201	Radius missing or incorrect		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Flexible Cable Assemblies shall contain component parts with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Contact, Nose Cap Connector Assembly	1 OF 1	9278719
			NEXT HIGHER ASSEMBLY: 9278723

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Opening between contact prongs, max.		0.40%	3.2	Gage
102	Protective finish missing, damaged or incomplete exposing base metal		0.40%	3.2	Visual
103	Component incomplete, missing or improperly assembled		0.40%	3.2	Visual
Major					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Retainer, Nose Cap Connector Assembly				9278720
					NEXT HIGHER ASSEMBLY
					9278723
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of contact wells		0.40%	3.2	Gage
102	Width of contact wells, min.		0.40%	3.2	Gage
103	Thickness of retainer, max.		0.40%	3.2	Gage
104	Diameter within contact wells		0.40%	3.2	Gage
105	Diameter of retainer, max.		0.40%	3.2	Gage
106	Width of retainer between flats		0.40%	3.2	Gage
107	Length of contact wells, min.		0.40%	3.2	Gage
108	Location of mating holes		0.40%	3.2	Gage
109	True position between mating holes		0.40%	3.2	Gage
110	Diameter of mating holes, min.		0.40%	3.2	Gage
Minor					
201	3° chamfer missing		0.65%	3.2	Visual
202	Component incomplete		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Base, Nose Cap Connector Assembly	1	1	9278721
				NEXT HIGHER ASSEMBLY 9259235

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of contact wells		0.40%	3.2	Gage
102	Width of contact wells, min.		0.40%	3.2	Gage
103	Dameter across retention legs, min.		0.40%	3.2	Gage
104	Location of mating holes		0.40%	3.2	Gage
105	True position between mating holes		0.40%	3.2	Gage
106	Diameter of mating holes, min.		0.40%	3.2	Gage
Minor					
201	Component incomplete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cover, Nose Cap Connector Assembly				9278722
					NEXT HIGHER ASSEMBLY 9278723
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of contact holes		0.40%	3.2	Gage
102	Diameter of contact holes, min.		0.40%	3.2	Gage
Minor					
201	Component incomplete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE	SHEET / OF	DRAWING NUMBER
4.4.2.5	Flexible Printed Circuit	1 1	9259236
			NEXT HIGHER ASSEMBLY 9259235

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Conductor width, min.		0.40%	3.2	Gage
102	Distance between adjacent conductors		0.40%	3.2	Gage
103	Length between holes, fuze end		0.40%	3.2	Gage
104	Cable width, max.		0.40%	3.2	Gage
105	Cable length		0.40%	3.2	Gage
106	Location of connector assembly interface connection		0.40%	3.2	Gage
107	Lamination of flexible printed circuit		0.40%	3.3	Visual
108	Dielectric strength	20		3.4	4.5.1
Minor					
201	Distance from edge of cable to conductor, min.		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.6	Socket, Connector				9259267
					NEXT HIGHER ASSEMBLY 9259235
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside Diameter of shoulder		0.40%	3.2	Gage
102	True position of outside shoulder to center cylindrical section		0.40%	3.2	Gage
103	Thickness of shoulder		0.40%	3.2	Gage
104	Outside diameter of central cylindrical section		0.40%	3.2	Gage
105	Inside diameter of end opposite shoulder		0.40%	3.2	Gage
106	Outside dimater of end opposite shoulder		0.40%	3.2	Gage
107	True position of outside end opposite shoulder with outside center cylindrical section		0.40%	3.2	Gage
108	Thickness of end opposite shoulder surface		0.40%	3.2	Gage
109	Inside diameter of cyclindrical section		0.40%	3.2	GAge
110	True position of inside cyclindrical section with outside center cylindrical section		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.6	Socket, Connector (Continued)				9259267
					NEXT HIGHER ASSEMBLY 9259235
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
111	Overall length		0.40%	3.2	Gage
112	Length of end opposite shoulder to outside step		0.40%	3.2	Gage
113	Width between contact points		0.40%	3.2	Gage
114	Inner inside diameter of end opposite shoulder		0.40%	3.2	Gage
115	True position of inner inside diameter of end opposite shoulder with outside center cylindrical section		0.40%	3.2	Gage
116	Radius missing		0.40%	3.2	Visual
Minor					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48048C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Flexible Cable Assembly				9259235
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inadequate solder present around socket connectors of base connector		0.40%	3.10	Visual
102	Outside diameter of socket connectors (not flange diameter)		0.40%	3.2	Gage
103	Insulation resistance	50		3.5	4.5.2
104	Conductor Resistance	50(a)		3.6	4.5.3
105	Assembly force of base of nose cap connector to ogive	50(b)		3.7	4.5.4
106	Assembly force of flexible cable assembly to base connector assembly.	50		3.8	4.5.5
107	Improper assembly of cover, nose cap connector assembly to flexible printed circuit.		0.40%	3.2	Visual
Minor					
201	Cap, Base connector missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:
(a) The fifty cable assemblies are from Test 4.5.2.
(b) A sample of five bases shall be selected from each batch produced by each mold cavity.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:11Z
Check the source to verify that this is the current version before use.

* 4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

* 4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test method and procedures.

4.5.1 Dielectric strength. Compress the cable between two plates with a 1.7 to 2 lb. force. While in the compressed condition, the sample is to be exposed to a temperature of 200°F + 10 degrees for a period 30 + 5 minutes. A test potential of 1500 volts root mean square 60 Hz at a rate of 500 volts per second is applied between one electrode to the two plates and one electrode to the positive lead. All readings should be taken at ambient condition and within ten (10) seconds after reaching the 1500 volt level. Any cable that fails to comply with the requirement shall be classed defective and removed from the lot. If one (1) or more fail the test as specified, the lot shall be rejected.

4.5.2 Insulation resistance. The flexible cable assembly shall be assembled in the test fixture and the resistance measured when five hundred (500) volts D.C. is applied to each mutually adjacent pair of conductors for ten (10) seconds, minimum. An assembly that fails to comply with the specified requirement shall be classed defective and removed from the lot. If two (2) or more fail the test as specified, the lot shall be rejected.

4.5.3 Conductor resistance. The flexible circuit assembly shall be assembled in the test fixture and each conductor circuit resistance measured. Any assembly that fails to comply with the specified requirement shall be classed defective and removed from the lot. If two (2) or more fail the test as specified, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

4.5.4 Assembly force of base to ogive. The test equipment shall represent the small end of the ogive and the opening shall represent the mid-range of the dimensional extremes. Assembly of the base may be initiated by compressing the retentive legs and starting the legs into the simulated ogive opening. The equipment shall use a dead load to attempt removal from the fixture. Observation shall be made for complete assembling. The removal force or dead load to remove the base shall be applied and observation made of results. The base shall be examined for cracks or broken segments. The base shall be classed defective if it fails to fully assemble, or if it is withdrawn by the specified force, or if the base is cracked or broken. The batch shall be rejected if one (1) or more bases are classed defective.

4.5.5 Assembly force of flexible cable assembly to simulated fuze base connector assembly The fuze and connector assembly shall be asembled in a test fixture. Place the fuze end of the cable assembly without the cap over the base connector assembly fixture so that the two sockets of the cable asembly are placed over the two pins of the fixture. Using a regulated load and a fixture simulating the cap base connector, apply the load evenly and without shock over the two sockets of the cable assembly. Record maximum load required to assemble the two parts together. Measure resistance of each wire to the pin of the base connector. The lot shall be rejected if two (2) or more flexible cable assemblies are classed defective. Test equipment test and calibration procedures must be approved by ARRADCOM prior to use.

5. PACKAGING

5.1 Packaging, packing and marking. The flexible printed circuit shall be packaged, packed and marked in accordance with MIL-STD-1169

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the M247 Warhead, 2.75 Inch Rocket.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, ARRADCOM, ATTN: DRDAR-QAF-T, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

* 6.4 First article. When a first article is required for inspection and approval, see 3.9 and 4.3.

* 6.5 Source control and specification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

* 6.6 Changes from previous issue. The margins of this specificatin are marked with asterisks or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and Contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1340-A633)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAF
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-48048C FLEXIBLE CABLE ASSEMBLY FOR M247 HEAT WARHEAD, ASSEMBLY AND PACKING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.