MILITARY SPECIFICATION

GRENADE (GP), LINER FOR

This Specification is approved for use by the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, provides quality assurance provisions, and packaging for one type of liner for general purpose grenades.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

9206200	-	Box, Fiber, for Cone
9345266	-	Grenade liner

(Copies of specifications, standards, handbooks, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Grenade liner. The grenade liner shall comply with all requirements specified on Drawing (Dwg) 9345266 and with all requirements specified in applicable specifications.

3.3 First article testing. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All liners shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.
b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Grenade liner	9345266	50

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-G-70464 (AR)

PARAGRAPH	TITLE: Grenade Liner		SHEET 1 OF 1		DRAWING NUMBER: 9345266
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Grenade Liner Examination for defects	50	--	3.2	4.4.2.1 (Note a)

NOTES:

(a) A sample of ten (10) grenade liners shall be inspected for outside surface profile.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9345266
4.4.2.1	Grenade Liner				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length to smaller basic diameter		0.40%	3.2	Gage
103	Distance between basic diameters		0.40%	3.2	Gage
104	Length to largest basic diameter		0.40%	3.2	Gage
105	Total length		0.40%	3.2	Gage
106	Wall thickness variation between planes max (360°)		0.40%	3.2	Gage
107	Wall thickness outside datums		0.40%	3.2	Gage
108	Runout skirt diameter		0.40%	3.2	Gage
109	Runout skirt face		0.40%	3.2	Gage
110	Part cracked or dented		0.40%	3.2	Visual
111	Outside surface profile	(a)		3.2	4.5.1
Minor					
201	Radius between outside diameter and junction with conical surface		0.65%	3.2	Gage
202	Finish improper (stain or unusual discoloration)		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES: (a) Sampling per para 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70464 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206200
4.4.2.2	Tube (Sealed and prior to insertion in fiber box)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Tube damaged to the extent that contents are exposed		0.40%	3.2	Visual
102	Closure missing or not fully seated		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Visual
202	Marking missing, incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.3	Box, Fiber, Sealed		1 OF 1		9206200
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Box damaged to the extent that tubes are exposed		0.40%	3.2	Visual
102	Sealing strip incomplete, badly wrinkled or missing		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Visual
202	Marking missing, incorrect or unidentifiable including incorrect color code		0.65%	3.2	Visual
203	Label missing or badly wrinkled (when applicable)		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Outside surface profile. The sample parts shall be inspected for conformance to the requirements of Dwg 9345266. Ten (10) parts shall be inspected to qualify each machine for production prior to use. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production from each machine. An additional three (3) parts shall be inspected after each minor machine adjustment. The last two groups of samples are for machine control during production.

4.4.3.1.1 Qualification of machines. If any defective parts are found during qualification of the machine, the machine producing the defective part shall not be used in production.

4.4.3.1.2 Rejection of machines and parts. If any defective parts are found when inspection is performed for machine control, the machine that produced the defective part shall be removed from production. Further, that portion of production since the last machine control check shall be rejected.

4.4.3.1.3 Requalification of machines. All machines removed from production because of some fault may, after adjustment or rework, be returned to production provided they pass the qualification test above.

4.4.3.1.4 Parts inspection. Parts shall be inspected in accordance with paragraph 4.5.1.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Outside surface profile. The samples selected for this test shall be measured for the outside surface profile along one conical element. This inspection shall be performed using a Bendix Formax Model 6060 with a ball radius of .0004 inches or other equivalent equipment. The equipment, procedures and calibration procedures shall be submitted in accordance with para 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging. The liners shall be preserved and packaged in accordance with Dwg 9206200.

5.2 Marking. Marking of the boxes shall be in accordance with Dwg 9205200.

5.3 Shipping. When shipments of more than one lot are made at one time, such as in a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing in transit.

6. NOTES

6.1 Intended use. The liner covered by this specification is intended for use on grenades, general purpose; M42 and M46.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, US Army Armament Research and Development Center (ARDC), ATTN: DRSMC-QAR-I(D), Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the headings US Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A202)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-70464	GRENADE (GP), LINER FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil – Downloaded: 2026-03-29T06:26Z
Check the source to verify that this is the current version before use.