MILITARY SPECIFICATION

MODULES, GENERAL SPECIFICATION FOR

1. SCOPE

1.1 This specification covers general requirements, general quality assurance provisions and preparation for delivery criteria for modules used with the Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 Detail modules. See detail specifications (see 6.2) for applicable documents relating to individual module assembly.

2.2 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Method of
MIL-S-19500/41 - Semi Conductor Device, Transistor, PNP, Germanium Switching Types 2N425, 2N426, 2N427

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-810 - Environmental Test Methods
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8826168 - Base Board, Module
8826288 - Contact Pin
8826290 - Potting Data, Modules
8826307 - Eyelet
8826308 - Guide Pin, Module
8826313 - Insulation, Paper

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

8826340 - Insulation Tubing
8836476 - Eyelet
8866640 - Guide Pin Module
8883539 - Bag, Packing, for Repair Parts

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Detail requirements. The individual requirements shall be as specified herein and in accordance with the applicable detail specifications. In the event of any conflict between requirements of this specification and the detail specifications, the latter shall govern (see 6.1 and 6.2).

3.2 Materials. The contractor shall furnish objective evidence (see 6.3) that the material complies with the specifications listed on the applicable drawing.

3.3 Assembly. The assembly of the module shall comply with all requirements specified on applicable drawing (dwg.) in the detail specification (see 6.2) with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.4 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.5 Insulation resistance. The insulation resistance of any circuit specified in the detail specification (see 6.2) shall not be less than 20 megohms when subjected to a potential of 500 ± 50 volts direct current (vdc) with the current limited to 5 milliamperes (ma) when tested as specified in 4.4.1.

3.6 Environmental testing. The item shall comply with 4.3.3.2 and 3.5 before and after each environmental test when tested as specified in 4.4.2. Tests shall be conducted in the order specified.

3.6.1 Low temperature. The item shall withstand exposure to a storage temperature of -65°F and shall comply with 4.3.3.2 and 3.5 while at -65°F when tested as specified in 4.4.2.1.

3.6.2 High temperature. The item shall withstand exposure to a temperature of +160°F and shall comply with 4.3.3.2 and 3.5 while at +160°F. when tested as specified in 4.4.2.2.

3.6.3 Temperature shock. The item shall withstand sudden changes in temperature when tested as specified in 4.4.2.3.

3.6.4 Vibration. The item shall withstand vibration when tested as specified in 4.4.2.4.

3.6.5 Humidity. The item shall withstand exposure to a humid atmosphere when tested as specified in 4.4.2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

3.7 Workmanship.

3.7.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristics.

3.7.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.7.3 Burrs. Parts shall be free from burrs.

3.7.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.7.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.7.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 12 complete assemblies (see drawing in detail specification (see 6.2) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

TABLE I

First Article Inspections and Tests

Examination or test	Contractor's Inspection permissable before submission	Destructive	Non-Destructive	Parts	Sub-Assemblies	Assemblies
1. Classification of Characteristics (see 4.3.2.1)	X		X	X	X	X
2. Operation (see 4.3.3.2)	X		X			X
3. Insulation Resistance (see 3.5)	X		X			X
4. Low temperature (see 3.6.1)	X		X			X
5. High temperature (see 3.6.2)	X		X			X
6. Temperature shock (see 3.6.3)	X		X			X
7. Vibration (see 3.6.4)	X		X			X
8. Humidity (see 3.6.5)		X				X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2, shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Major characteristic table II

Lot size	Sample size
1- 155	100% inspection
156- 200	155
201- 250	175
251- 300	190
301- 350	200
351- 400	210
401- 450	220
451- 500	225
501- 550	230
551- 600	235
601- 650	240
651- 700	243
701- 750	247
751- 800	250
801- 900	254
901-1000	258
1001-1100	261
1101-1200	264
1201-1300	266
1301-1400	268
1401-1500	270
1501-1600	272

Minor characteristic table III

Lot size	Sample size
1- 25	100% inspection
26- 30	25
31- 35	26
36- 40	27
41- 45	28
46- 50	29
51- 55	30
56- 60	31
61- 65	32
66- 70	33
71- 75	34
76- 85	35
86- 95	36
96- 110	37
111- 130	38
131- 156	39
157- 190	40
191- 240	41
241- 340	42
341- 520	43
521-1120	44
1121 and over	45

4.3.2.1 Classification of characteristics. Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as specified in the detail specification (see 6.2) and herein.

4.3.2.1.1 Transistor 2N425 (see MIL-S-19500/41); insulation tubing (see 8826340); eyelet (see dwgs 8826307 and 8836476).

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Major:
101. Objective evidence (see 6.3) available for part in accordance with applicable specification or drawing.....Visual

Minor: None defined.

4.3.2.1.2 Insulation paper (see dwg 8826313) Baseboard, module (see dwg 8826168) covering details of plug-in modules.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Material (see 3.2).....Visual

Minor: None defined.

4.3.2.1.3 All plug-in type modules (see dwg in detail specification (see 6.2)).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Height of molded portion of module.....*Measure
102. Length of guide pin.....*Measure
103. Length of contact pin.....Gage
104. Width of molded portion of module, max.....Gage
105. Location of all pins.....Gage
106. Length of molded portion of module, max.....Gage
107. Diameter of contact pins (see dwg 8826288).....Gage
108. Diameter of guide pins (see dwg 8826308 or 8866640).....Gage
109. Materials (see 3.2).....Visual
110. Objective evidence (see 6.3) available for potting data in accordance with dwg 8826290.....Visual
111. Workmanship (see 3.7).....Visual/Manual

* Measure with suitable scale.

Minor:
201. Marking.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Preparation for delivery production items only (see 5.1).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual/Manual
Minor: None defined.		

4.3.2.1.5 Bag, Packing, for Repair Parts (see dwg 8883539) covering dwg part number 8883539-3&4 as applicable (see detail spec) and section 5.2).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Material (see 3.2)	Visual
102.	Length before packing, min	*Measure
103.	Width before packing, min	*Measure
104.	Objective evidence (see 6.3) available for heat seal test in accordance with MIL-P-116	Visual
105.	Properly packed	Visual
106.	No tear, split, or crack in bag	Visual

* Measure with suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.7)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Packing and Marking for Storage and Shipments (see dwg 8808362 and section 5.2).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Gross load weight, max.	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Package material (see 3.2)	Visual
Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.7)	Visual/Manual

* Determine weight with a suitable scale.

4.3.3 Testing. All the tests specified in this paragraph shall be performed. Tests do not have to be performed in the order specified.

Test	Test classification
a. Operation	Critical
b. Insulation resistance	Critical
c. High temperature	Major
d. Low temperature	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Insulation resistance (see 3.5). Each module (see detail specification (see 6.2) shall be tested in accordance with 4.4.1. If any module fails to conform with 3.5, the module shall be rejected and removed from the lot.

4.3.3.2 Operation (all modules). Each module (final assembly) shall be tested in accordance with 4.4.3. If any module fails to comply with the drawing requirement, the module shall be rejected and removed from the lot.

4.3.3.3 High temperature (see 3.6.2) and low temperature (see 3.6.1). One module selected at random from each 50 modules or less produced shall be tested in accordance with 4.4.2. If the module fails to comply with 3.6.1 and 3.6.2, the lot shall be rejected.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Equipment Lists (EL). EL's for assemblies are listed on the Equipment Tabulation (ET) when required. ET's and EL's as applicable shall be specified in the detail specification (see 6.2). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.4 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Insulation resistance (see 3.5). The insulation resistance shall be measured with approved insulation resistance measuring equipment in accordance with the table in the detail specification (see 6.2).

4.4.2 Environmental testing (see 3.6).

4.4.2.1 Low temperature (see 3.6.1). The item shall be tested in accordance with MIL-STD-810, Method 502.

4.4.2.2 High temperature (see 3.6.2). The item shall be tested in accordance with MIL-STD-810, Method 501.

4.4.2.3 Temperature shock (see 3.6.3). The item shall be tested in accordance with MIL-STD-810, Method 503. The item shall not be operated during this test.

4.4.2.4 Vibration (see 3.6.4). The item shall be mounted on an approved fixture and shall be tested in accordance with MIL-STD-810, Method 514, Procedure X. Test curve shall be AB, Fig. 514-6. The item shall not be operated during the test.

4.4.2.5 Humidity (see 3.6.5). The item shall be tested in accordance with MIL-STD-810, Method 507, Procedure III. The item shall not be operated during the test.

4.4.3 Operation (see 4.3.3.2). The item shall be tested on approved equipment which contains the test circuitry as depicted on the applicable drawing.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

5.1 Production modules.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The module shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The module shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The module shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair modules.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The modules shall be preserved and packaged in accordance with drawings specified in the detail specification (see 6.2).

5.2.1.2 Level C. The modules shall be preserved and packaged in accordance with drawings specified in the detail specification (see 6.2) except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and Level C. The modules shall be packed in accordance with the drawings specified in the detail specification (see 6.2).

5.2.3 Marking. Marking shall be as specified on drawings specified in the detail specification (see 6.2).

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

a. Title number and date of the detail specification (see 6.2).
b. Selection of the applicable level of packaging and packing.

6.2 Individual specifications. The modules covered under this basic specification have individual specifications assigned to each module such as MIL-M-50276/1 for Module, Plug-in Basic Timer. Supplement No. 1 to this specification lists the detail specifications numerically.

6.3 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.4 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

6.5 Supersession data. This specification includes the requirements of Purchase Description, PA-PD-1894, dated 24 January 1966.

Custodian:
Army - MU

Preparing activity:
Army - MU
Project No. 1125-A005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

MILITARY SPECIFICATION

MODULES, GENERAL SPECIFICATION FOR

MIL-M-50276/1(MU) - Module, Plug-in Basic Timer (see dwg 8826129)
MIL-M-50276/2(MU) - Module, Plug-in One Shot Multivibrator (see dwg 8826130)
MIL-M-50276/3(MU) - Module, Plug-in Line Amplifier (see dwg 8836556)
MIL-M-50276/4(MU) - Module, Plug-in M-1 (see dwg 8836557)
MIL-M-50276/5(MU) - Module, Plug-in Code Check (see dwg 8836558)
MIL-M-50276/6(MU) - Module, Plug-in Safe Reply (see dwg 8836559)
MIL-M-50276/7(MU) - Module, Plug-in NPN Multivibrator (see dwg 8836560)
MIL-M-50276/8(MU) - Module, Plug-in Inverter, Integrator (see dwg 8836561)
MIL-M-50276/9(MU) - Module, Plug-in Positive Amplifier (see dwg 8836562)
MIL-M-50276/10(MU) - Module, Plug-in Negative Amplifier (see dwg 8836563)
MIL-M-50276/11(MU) - Module, Plug-in Amplifier No. 1 (see dwg 8836564)
MIL-M-50276/12(MU) - Module, Plug-in Amplifier No. 2 (see dwg 8836565)
MIL-M-50276/13(MU) - Module Assembly (Transformer) (see dwg 8857424)
MIL-M-50276/14(MU) - Module Assembly (Diode) (see dwg 88657425)
MIL-M-50276/15(MU) - Module, Oscillator (Encapsulated) (see dwg 8860584)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-M-50276 (MU) Modules, General Specification For

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.