MILITARY SPECIFICATION

PACKING KIT, 6-INCH HOSELINE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a packing kit consisting of items such as a hoist, hose puller, and hose clamps designed for use in packing sections of a hoseline system in flaking boxes.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-T-60	- Tape: Packaging, Waterproof.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-E-52798	- Enamel, Alkyd, Camouflage.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4610

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:49Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13226E1571	- Hoseline Packing Kit, 6-Inch.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The hoseline packing kit (hereinafter called "kit") shall be in accordance with TA13226E1571 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the kit. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (first produced kit). The contractor shall furnish one or more kits as specified (see 6.2) for examination within the time frame specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

(see 6.2) to prove that his production methods will produce kits that comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.2).

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.3.1 Material deteriorations prevention and control (MADPAC). The packing kit shall be fabricated from compatible materials, suitably finished, to provide protection from corrosion and other forms of material deterioration. Assurance shall be given in the form of a finish plan which clearly identifies the specific finish or treatment to be used on the various components and assemblies, to provide protection against the various forms of material deterioration in the applicable operating and storage environments to which they may be exposed.

3.3.2 Galvanic corrosion. Dissimilar metals as defined in MIL-T-704 shall not be used in intimate contact without suitable protection to circumvent galvanic corrosion.

3.4 Chest. All components of the kit shall be furnished in a steel chest not less than 0.0747 inch (USS 14 gage) in thickness. The chest shall have a hinged cover, fastening devices, and handles. Bins and cradles or blocking, or both, shall be provided for components of the kit to prevent damage during shipment or handling. The chest shall not exceed 22 inches in height.

3.5 Treatment and painting. The chest and all components of the kit, except the hoist cable, shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A with a finish coat in accordance with MIL-E-52798, Type I, color sand.

3.6 Identification marking. The kit shall be identified in accordance with MIL-STD-130. Marking shall be applied to the outer cover of the chest.

3.7 Workmanship. All components of the kit and chest shall be free from defects such as dirt, rust, scale, and welding flux.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:49Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Inspection requirements specified herein are classified as follows:

a. First produced kit inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First produced kit inspection.

4.3.1 Examination. The first produced kit shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each kit shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The kit shall be examined as speeified herein for the following defects:

101. Dimensions not as specified.
102. Finish plan not adequate.
103. Material not as specified.
104. Components missing or not as specified.
105. Identification marking missing, incomplete, or illegible.
106. Treatment and painting not as specified.
107. Workmanship not as specified.
108. Dissimilar metals not in compliance with MIL-T-704.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

109. Materials and containers not as specified. Each incorrect material or container shall be considered one defect.
110. Unpainted metal surfaces of components requiring a contact preservative not coated as specified for level A.
111. Chest lid not sealed with tape as specified for level A.
112. Marking missing, illegible, incorrect or incomplete for level A, level B, or commercial.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:49Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Unpainted metal surfaces of components of the kit requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 or P-19 preservative. The preservative shall conform to the applicable specification listed in, and shall be applied in accordance with, MIL-P-116. The components comprising the complete kit shall then be placed and secured in the chest in accordance with the loading plan. After closure, all edges of the chest lid shall be sealed with tape conforming to PPP-T-60, Type IV.

5.1.2 Commercial. The components of the kit shall be preserved in accordance with MIL-STD-1188 and placed and secured in the chest.

5.2 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

5.2.1 Level A. The chest containing the kit components shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional. Box closure and strapping shall be in accordance with appendix of the box specification.

5.2.2 Level B. Packing shall be as specified for level A except the boxes shall be domestic type.

5.2.3 Commercial. The chest containing the kit components shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or level B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The kit is intended for use with a 6-inch, lightweight, collapsible hoseline system.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Time frame required for submission of first produced kit and number of kits required (see 3.2).
c. Degree of preservation and degree of packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:49Z
Check the source to verify that this is the currentversion before use.

6.3 First produced kit. Any changes or deviations of production kit from the approved first produced kit during production will be subject to the approval of the contracting officer. Approval of the first produced kit will not relieve the contractor of his obligation to furnish kits conforming to this specification.

6.4 Recycled materials. Unless otherwise specified herein all equipment, material and articles incorporated in the products covered by this specification shall be new, and shall be fabricated using materials produced from recycled materials to the maximum extent practicable without jeopardizing the intended use. The term "recycled materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically authorized (see 3.4).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4610-A081

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-53016(ME) Packing Kit, 6-Inch Hoseline

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R & D Command
Attn: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.