INCH-POUND

MIL-STD-1490H
28 August 2026
SUPERSEDING
MIL-STD-1490G
26 August 1992

MILITARY STANDARD

PROVISIONS FOR EVALUATING QUALITY

OF

COATS, MEN'S, DRESS



AMSC N/A

FSC 8405

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

FOREWORD

1. This standard is approved for use by Department and Agencies of the Department of Defense (DoD).

2. This standard is intended to provide standard practice for evaluating quality of men's dress coats. This standard provides the following information:

- A standard method for visually inspecting and evaluating the quality of men's dress coats.
- Standard descriptions for coats defect.
- Standardized examination requirements for coats.

3. Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, you may want to verify the currency of this ad information using ASSIST at https://assist.dla.mil.

THIS SPACE INTENTIONALLY LEFT BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
1	SCOPE	1
1.1	Scope	1
2	APPLICABLE PUBLICATIONS	1
2.1	General	1
2.2	Government publications	1
2.2.1	Specifications, standards and handbooks	1
2.2.2	Other Government publications	1
2.3	Non-Government publications	1
2.4	Order of precedence	2
3	DEFINITIONS	
3.1	End item	2
3.2	Fabric defects	2
3.3	Inside and outside	2
3.4	Knots and slubs	2
3.5	Major defects	3
3.6	Minor defects	3
TABLE	Defect Tables	3-21
3.7	Puckering	22
3.8	Defective buttons	22
3.9	Quality assurance terms and procedures	22
3.10	Raw edge	22
3.11	Stitches, seams and stitching	22
3.11.1	Open seam	22
4	GENERAL REQUIREMENTS	
4.1	General	22
4.2	Coverage	22
4.3	Normal viewing conditions	22
5	DETAILED REQUIREMENTS	
5.1	Sampling and acceptance criteria	23
5.2	End-item dimensional examination	23
5.3	End item visual examination	23

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

5.4	Shade variation examination……..	23
5.5	Dimensional examination……	23
5.6	Shade match and appearance examination……..	23
5.7	Inspection procedures……...	23
6.	NOTES ……...	23
6.1	Intended use ……..…….....	23
6.2	Acquisition requirements……	24
6.3	Subject term (key word) listing …….	24
6.4	Changes from previous issue……..	24
	CONCLUDING MATERIAL	24

THIS SPACE INTENTIONALLY LEFT BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard covers the inspection provision requirements for coats, men's, dress worn by male members of the military.

2. APPLICABLE PUBLICATIONS

2.1 General. The publications listed in this section are specified in sections 3, 4 and 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of publications cited in sections 3, 4 and 5 of this standard whether or not they are listed.

2.2 Government publications. N/A

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these publications are those cited in the solicitation or contract.

2.3 Non-Government publications. The following publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these publications are those cited in the solicitation or contract.

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS (AATCC)

AATCC Photographic Seam Smoothness Scales - 68373

(Copies are available at https://www.aatcc.org.)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this publication are available online at https://asq.org or https://www.ansi.org.)

ASTM INTERNATIONAL

ASTM D3990 - Standard Terminology Relating to Fabric Defects
ASTM D6193 - Standard Practice for Stitches and Seams

(Copies of these publications s are available online at https://www.astm.org.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

SDL ATLAS

Fabric Replica Defect Scales
Part Number 402985 – Slub/Knot Replica Set

(Replica set is available for purchase from SDL Atlas Customer Service, 1-803-329-2110).

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. DEFINITIONS

3.1 End-item. End-item refers to finished coats constructed, labeled, pressed and presented for acceptance. Other criteria may be specified in an end-item detailed specification.

3.2 Fabric defects. End-item fabric defects willbe specified in Table I and are defined in ASTM D3990. The defects willbe scored in accordance with Table I are specified in the appropriate fabric specification. (See 2.3).

3.3 Inside and outside. The terms “inside” and “outside” as used in this standard are defined as follows:

“Inside” Any part of the coat that is not visible when the completely buttoned coats is observed on the model form.

“Outside” Any part of the coat that is visible when completely buttoned coat is observed on the model form. Areas also included are the undersleeve, under the pocket flaps (when untacked), and the area covered by the overlap of the back vent.

3.4 Knots and slubs. Knots and slubs willonly be scored when they exceed the limits specified in the basic material cloth specification. Knots and slubs willbe rated using Fabric Defects Replica Scales (see 2.3) .

3.5 Major defects. A departure of a quality characteristic from its intended level of the specification that occurs with sufficient severity that is likely to result in a failure, or to reduce considerably the usability of the coat for its intended purpose. (See Table I).

3.6 Minor defects. A departure of a quality characteristic from its intended level of the specification but the service is still considered serviceable. (See Table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/

Defect description	Major	Minor
• **I. MATERIAL DEFECT AND WORKMANSHIP DAMAGE**		
• Any hole, cut, tear, run 2/, smash, burn, hole, scorched • Area, or open place:		
• On outside	101	
• On inside (longest dimension in any direction		201
• Up to 1/4-inch, inclusive		202
• More than 1/4-inch up to 3/8-inch	102	
• More than 3/8-inch	103	
• Loose yarn, snag 2/ barre 2/, uneven knitting 2/, misweave, area or no dye penetration, dye streak, missing yarn, broken yarn, thin place, shade bar, or woven in waste; more than 1/4-inch (largest dimension in any direction) on outside.	104	
• Permanent fold, pleat, or crease in cloth (when caught in seaming or stitching) on outside.	105	
• Woven in spot or stain debris and/or waste on outside visible at 3-feet		203
• Visible needle hole(s) (no thread present) or needle chew, i.e. presence of scuffed or broken yarns caused by stitching:	106	
• On outside: Up to 1/4-inch inclusive	107	
• More than 1/4-inch	108	
• On inside: Up to 1/2-inch inclusive (Army and Navy only)		204
• More than 1/2-inch	109	
• Knot or slub (see 3.2) on outside	110	
• **II. SHADED PARTS**		
• On outside:		
• Variation in shade within a part or between parts • (except parts cut from ends):	111	
• Army and Navy	112	
• Seriously affecting appearance for Air Force and Marine Corps	113	
• Affecting appearance, but not seriously for Air Force and Marine Corps	114	
• Part cut from ends shades, seriously affecting appearance	115	
• On inside:		
• Any lining part shades, seriously affecting appearance (except sleeve linings)		205
• Sleeve lining part shaded, seriously affecting appearance, pairs not matching each other		206

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/

Defect description	Major	Minor
• **III. PRESSING**		
• Pressing omitted (entire item)	116	
• Excess gloss, causing serious change in appearance	117	
• Edge bulky, i.e., not pressed solid	118	
• Lapel not roll pressed as specified	119	
• Sleeve not pressed as required	120	
• Armhole stretched	121	
• Armhole not blocked	122	
• Inside or armhole not creased as required	123	
• Lining (except sleeve linings) not finished pressed smooth and flat for more than 1/2-inch.	124	
• Waist dart not pressed as specified.	125	
• Collar break line not creased	126	
• Finished pressed width of lapel not uniform (i.e., one side finishing 1/4-inch or more than other when measured across upper portion on horizontal from forced out edge to lapel crease line).	127	
• Improper pressing, i.e., pleat, pressed fold, or crease • (on outside).	128	
• **IV. CLEANNES**		
• Spot or stain on outside:	129	
• Up to 1/4-inch inclusive in longest direction	130	
• More than 1/4-inch in longest direction	131	
• Any marking exposed or visible on outside	132	
• Five or more thread ends on outside not trimmed to 3/8-inch or less		207
• Two or more shade or size tickets on coat		208
• Basting thread (including monofilament thread or fragments of monofilament thread) not completely removed from outside.		209

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/ - Continued

Defect description	Major	Minor
• **V. COMPONENT AND ASSEMBLY**		
• Any component part or operation omitted (unless otherwise classified herein)	133	
• Any component not as specified	134	
• Any component part tight, twisted, distorted, pleated, or full (unless otherwise classified herein)	135	
• Any operation not performed as specified (unless otherwise classified herein)	136	
• The edge of any component part required to be forced out having folds of more than 1/8-inch (unless otherwise classified herein)	137	
• **VI. Cutting**		
• Any component pat not cut in accordance with specified pattern or directional lines on patens, or not in accordance with specification requirements.	138	
• Twill line of any outside part not running specified direction.	139	
• **VII. SEAMS AND STITCHING**		
• Accuracy of seaming:		
• Seam puckered (on outside)		210
• From 1/4 to 1/2-inch the length of seam	140	
• More than 1/2-inch to length of seam	141	
• Seam irregular, pleated, or wavy (less otherwise classified herein)	142	
• Any part of coat caught in an unrelated operation or stitching	143	
• Blind stitching, tacking, or hand felling of armhole exposed on outside		211
• Machine felling or hand felling (other than around armhole) exposed for a distance of 3/8-inch or more		212
• End of stitching when not caught in another seam or stitching not finished as specified	144	
• Stitching overlapping end of thread break less than 1/2-inch		213
• Not specified color thread used on outside	145	
• Needle perforations clearly visible on outside of coat	146	
• Gage of stitching and seam allowance:		
• Edge, top, or raised stitching sewn too close to edge resulting in damage to cloth	147	
• Seam allowance not as specified by 1/16-inch (1/8-inch) Air Force or more (score only when condition exists on more than half the length of the seam)		214

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/ - Continued

Defect description	Major	Minor
• VII. SEAMS AND STITCHING - Continued		
• Irregular or not within range specified or varies more than 1/16-inch (1/8-inch Air Force) when no range is specified (score only when condition exists on more than half the length of the seam)		215
• On outside (excluding lower edge of under collar):		
• More than 3/4-inch	148	
• More than 1/2-inch up to 3/4-inch inclusive	149	
• Up to 1/2-inch inclusive		216
• On inside: machine felling and hand felling (other than hand felling around armhole):		
• More than two skipped stitches or 1/4-inch up to • 2-inches inclusive		217
• More than 2-inches	150	
• On inside Stitch type 301 and hand felling around armhole:		
• More than 3/8-inch up to 2-inches inclusive		218
• More than 2-inches	151	
• Seam and stitch type:		
• Not specified seam or stitch type	152	
• Any line of stitching omitted or insecure	153	
• Any line of stitching not beginning or ending where specified (unless otherwise classified herein)		219
• Looper thread of 401 stitch type on outside		220
• Stitch tension:		
• Loose tension resulting in a loose seam:		221
• 1/4 up to 1/2 length of seam inclusive	154	
• More than 1/2 length of seam up to 3/4 length of seam inclusive	155	
• More than 3/4 length of seam	156	
• Loosely exposed loops of lower or top thread on edge, top, or raised stitching	157	
• Tight, tension (stitches break when strain is applied in the direction of the seam or stitching)	158	
• Stitches per inch (score only when condition exists or more than half the length of seam):		
• More than the maximum specified (affecting construction or appearance)		222

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/ - Continued

Defect description	Major	Minor
• **VII. SEAMS AND STITCHING - Continued**		
• More than the maximum specified (affecting construction or appearance):		
• - Less than the minimum specified:		
• By one or two stitches (Army and Navy; by two stitches (AF&MC)		223
• By three or more stitches	159	
• Run-off, skipped, or broken stitch:		
• Joining seam – use open seam classification:		
• Edge, top, or raised stitching (more than 1/4-inch)		224
• Bartack, tack, or tracking (except buttonhole bartack):		
• Missing, insecure, misplaced, not serving intended purpose	160	
• Loose stitch tension		225
• Not specified size or type		226
• **VIII. BUTTONHOLE OR EYELET**		
• Omitted, added, not specified type, or not finished as specified	161	
• Stitched buttonhole or eyelet:		
• Gimp omitted, uncut, finished length or diameter not as specified, or end of gimp not pulled through to underside on square bar type buttonholes	162	
• Ragged edge, incomplete stitching, stitching not securely caught in fabric, bulky appearance, stitches not uniform, or loose tension	163	
• Broken stitch, or two or more skipped stitches	164	
• Buttonhole stitching extending beyond bartack	165	
• Bartack missing, loose or misplaced (not serving intended purpose)	166	
• Stitches per buttonhole, eyelet or bartack specified by:		
• One to three stitches		227
• Four or more stitches	167	
• Bound buttonhole:		
• Finished length not as specified	168	
• Tongue notch at one or both ends exposed, or not securely tacked on inside of raw edges at ends	169	
• Piping uneven, or top and bottom piping not uniform in width by more than 1/16-inch		228

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. 1/ - Continued

Defect description	Major	Minor
• Width of piping not within tolerance specified, or (± 1/16)-inch from required width when no tolerance is specified		229
• Any open seam (i.e., any visible opening between binding and shell fabric on inside or outside)	170	
• Ends of piped buttonhole spread apart or overlapped by more than 1/16-inch		230
• Any stitching visible on piping on outside		231
• Piping joining seam visible on inside		232
• **IX. BUTTON OR TOGGLE**		
• Omitted, broken, or defective	171	
• Out of horizontal or vertical alignment by:		
• 3/16 to 3/8-inch		233
• More than 3/8-inch	172	
• Misplaced, loose, not attached as specified, or insecurely sewn		234
• Tacking stitches omitted or insecure (hand sewn)		235
• Button sewn with wings of eagle or shield in other than upright position (front and flap buttons) or shoulder loop buttons sew to coat with the spread wings of the eagle, or shield not in specified position		236
• Shank wrapping (when required) omitted, loose, or insecurely wrapped	173	
• Stitching on button not locked at end of cycle (tug at loose end of the thread when accessible to determine whether it will ravel)		237
• **X. SNAP FASTENER (when applicable):**		
• Stitching of stud visible on outside of flap	174	
• Missing, loose, broken, defective, or mismatched		238
• Misplaced or not positioned as specified		239
• Tacking stitches omitted or insecure on one or more handsewn fasteners		240
• **XI. ALIGNMENT OF FRONT BUTTON OR BUTTONHOLE:**		
• Top front button or buttonhole of a coat out of horizontal alignment with breast pocket flap buttons:		
• By more than 1/2-inch	175	
• Top front button or buttonhole of a coat out of horizontal alignment with breast pocket flap buttons:		

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XI. ALIGNMENT OF FRONT BUTTON OR BUTTONHOLE: - Continued**		
• By more than 1/3-inch but not more than 1/2-inch	176	
• Button or buttonhole misplaced:	177	
• For Army and Air Force coats, bottom front button or buttonhole varies from 7/8-inch (Army coats) or 3/4-inch (Air Force coats) above top edge of lower pocket flap by:		
• More than 1/8-inch up to 1/4-inch (Army coats)		241
• More than 1/4-inch up to 3/8-inch	178	
• Top front button or buttonhole of coat or lower front button or buttonhole (all coats misplaced):		
• By more than 3/8-inch but not more than 1/2-inch	179	
• By more than 1/2-inch	180	
• Left front rolling outward below button front button	181	
• Button and buttonhole not aligned, causing a bulge or twist on front	182	
• Front buttonhole position (from inside edge of eyelet):		
• Less than 5/8-inch but not less than 3/8-inch, or more than 3/4-inch but not more than 7/8-inch from edge		242
• Less than 3/8-inch or more than 7/8-inch from edge	183	
• Spacing between front buttonholes varying more than 1/4-inch		243
• Button on left front of coats not in horizonal alignment with button on right front by:		
• 1/4-inch but not more than 1/2-inch		244
• More than 1/2-inch but not more than 1-inch inclusive	184	
• More than 1-inch	185	
• Anchor button not aligned with buttonhole, causing a noticeable bulge or twist on front	186	
• **XII. LENGTH OF BUTTONED FRONT**		
• Left front shorter than right front at bottom by:		
• More than 1/4-inch	187	
• More than 1/8-inch up to 1/4-inch inclusive	188	
• Left front longer than right front at bottom by:		
• More than 1/4-inch	189	
• More than 1/8-inch up to 1/4-inch inclusive	190	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XIII. POCKET OR FLAP**		
• Misshapen or distorted – any point varying:		
• More than 1/4-inch from specified dimension or with corresponding point on finished shaper	191	
• 1/8 up to 1/4-inches (inclusive) from specified dimension or with corresponding point on finished shaper (except Marine Corps)	192	
• Not uniform in size or shape – any point varying more than 1/4-inch with corresponding point on matching part	193	
• Out of alignment or misplaced by (horizontal or vertical):		
• All coats except Marine Corps coats: 3/	194	
• More than 3/8-inch	195	
• More than 1/4-inch up to 3/8-inch inclusive	196	
• 1/8-inch up to 1/4-inch inclusive	197	
• Marine Cops coats only: 4/		
• More than 3/16-inch (vertical)	198	
• Flap not in horizontal alignment Marine Corps coats only:		
• More than 3/16-inch	199	
• More than 1/8-inch up to 3/16-inch inclusive	100a	
• Flap any:		
• Twisted or bulged when snapped or tacked	101a	
• Bottom corner of flap curled upwards; stitching joining flap to front not caught through twill cloth stay piece or flap not completely covering pocket opening	102a	
• Misplaced, not positioned as specified	103a	
• Raw edge beneath top edge of flap; corner of flap not securely backstitched		245
• Buttonhole out of alignment with point at center of flap y more than 1/8-inch or not positioned as specified		246
• Overedge stitching omitted		247
• Breast pocket flap:		
• Point at center or flap from center of pocket pleat:	104a	
• More than 1/8-inch up to 1/4-inch inclusive	105a	
• More than 1/4-inch	106a	
• Lower side edge of flap covering side of pocket less than 1/16 or more than 3/16-inch	107a	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XIII. POCKET OR FLAP - Continued**		
• When pocket flaps are tacked at each corner:		
• Tacking visible on outside of flap less than 2 stitches on hand tacking		248
• Breast pocket:		
• Side pocket not parallel with front edge of coat by: 5/		
• More than 3/8-inch	108a	
• 1/4-inch up to 3/8-inch	109a	
• Fold of pleat on outside: Pleat off center at lower edge of flap by 1/4-inch or more; or pleat set on crookedly or slanted by 1/8-inch or more	110a	
• Twill cloth exposed on pocket edge (when lined pocket construction is used or twill cloth tight or short causing fullness or puckers in outside of pocket)	111a	
• Pleat not stitched closed; width of pleat not portion of pocket under pleat	112a	
• Stitching at end of pocket opening not securely stitched thorough stay piece; or end of stitching at end of pocket not backtracked as specified		249
• Lower pocket opening:		
• Opening gap by 1/4-inch or more or length of opening not as specified		250
• Width of corded or piped edge not as spaced by more than 1/8-inch		251
• Front edge of flap not parallel with front edge of coat by more than 1/4-inch when coats are buttoned		252
• End of facing not caught in twill cloth pocket seaming		253
• Bartacking at ends of pocket opening omitted or insecure		254
• Welt pocket:		
• Top edge of welt short causing puckers in front, or too loose causing welt to gap by 1/4-inc or more at any point	113a	
• Tape stitching exposed and visible on outside surface		255
• Diagonal reinforcing row of stitching on corners of welt, omitted or insecure		256
• Tacking at top front corner or tacking to seam allowance of hanging pocket along front edge to interlining omitted or insecure	114a	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XIII. POCKET OR FLAP - Continued**		
• Cash pocket in inside right lower pocket omitted or misplaced, i.e., more than 1-inch from center of pocket		257
• Notch exposed beyond outside end of welt or not securely caught within the row of stitching at end of welt	115a	
• Any portion of welt setting seam on one or more pockets not spread open for a distance of 1/2-inch or more		258
• Top back edge of welt not equidistant from side seam by more than 3/4-inch		259
• Finished width of welt on hip pockets less than • 1 1-/8-inches or more than 1 1/4-inches		260
• Finished width of welt on outside breast pocket less than 7/8-inch or more than 1-inch		261
• Finished width or dept not as specified		262
• Lower patch pockets Marine Corps coats:		
• Top edge of pocket set less than 3/4-inch or more than 1 1/4-inch below top edge of flap	116a	
• Binding on top edge omitted or not securely caught in fabric, causing binding to pull away from fabric	117a	
• Fullness at pocket opening affecting appearance		263
• Button and buttonhole not aligned causing a noticeable bulge or twist on pocket or flap when button, affecting appearance	118a	
• Bottom edge of pocket not parallel with bottom edge of coats by 1/4-inch or more	119a	
• Pocket corners not securely stitched	120a	
• Tightness at pocket opening affecting appearance	121a	
• **XIV. LAPEL OR COLLAR**		
• Misshapen or distorted – any point varying 1/4-inch or more with corresponding point on finished shaper	122a	
• Not uniform in size or shape – any point varying:		
• More than 5/16-inch with corresponding point on matching part	123a	
• More than 1/4-inch but not more than 5/16-inch with corresponding point on matching part	124a	
• More than 1/8-inch but not more but not more than 1/4-inch with corresponding point on matching point	125a	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XIV. LAPEL OR COLLAR -CONTINUED**		
• Twisted, short, or tight causing collar or lapel to turn out	126a	
• Collar rolling up above collar break line by:		
• 1/8-inch to 3/16-inch (inclusive)	127a	
• More than 3/16-inch	128a	
• Long, i.e., setting away from neck or lapel rolling higher than 2-inches above top front button or buttonhole	129a	
• Tight at joining to gorge seam or across back, causing excessive fullness or pleats on:	130a	
• Lapel Across outside back	131a	
• Lapel Collor outside back	132a	
• Collar edge:		
• Crooked, irregular, or wavy	133a	
• Undercollar exposed along collar edge for 1/4-inch or more		264
• Gorge seam not spread open (any portion): not straight; tacking insecure or tacking omitted		265
• Gorge seams not uniform in length by 1/4-inch or more (measure from collar break line to end of gorge seam notch)		266
• Tacking in corner of undercollar t lapel omitted or insecure		267
• Bridle lapel basted onto or extending beyond breakline on lapel side	134a	
• More than 5/8-inch behind lapel breakline	135a	
• Bridle tape basted onto or extending beyond breakline on lapel side	136a	
• Bridle tape more than 7/8-inch behind lapel breakline	137a	
• Bridle tape end not within 1 to 1/2-inches from bottom of lapel	138a	
• **XV. SHOULDER CONSTRUCTION**		
• Improperly joined or set, causing shoulder or back to twist	139a	
• Shoulder seam curved towards back from normal position at armhole end by:	140a	
• More than 3/8-inch		268
• 1/4-inch up to 3/8-inch, inclusive		269

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XVI. SHOULDER PAD**		
• Note completely caught in armhole tacking; or misplaced, not service intended purpose, i.e., too far back or too far forward	141a	
• **XVII. SHOULDER LOOP**		
• Not uniform in size or shape – any point varying:		
• More than 3/8-inch with corresponding point on matching part	142a	
• 1/4-inch up to 3/8-inch (inclusive) with corresponding point on matching part	143a	
• Misplaced, i.e., shoulder seam exposed or loop will not lay flat when buttoned causing bulge or twist	144a	
• Button not aligned with buttonhole causing bulge or twist on loop or pucker on shoulder	145a	
• Point of look extending beyond collar crease line		270
• Width of loop at sleeve head or at base of point not as specified		271
• Buttonhole 1/4-inch or more off center, or buttons not uniformly set by more than 1/4-inch		272
• Back edge of loop more than 3/4-inch from shoulder seam at any hole; point of loop back of shoulder seam or point of loop more than 1/2-inch forward of shoulder seam		273
• Position of shoulder loop button from collar edge not as specified:	146a	
• Less than 1/8-inch but not covered by collar edge or more than 1/2-inch		274
• Partially covered by collar edge (half of button or less)		275
• Button more than half covered by collar edge		276
• Interlining not caught in seaming of loop • Other than one piece construction		277
• Set upside down exposing underside seam	147a	
• Back edge of loop more than 1/2-inch from shoulder seam (Marine Corps coasts only)	148a	
• **XVIII. ARMHOLE OR SHOULDER**		
• Fullness or puckering in the following locations:	149a	
• Over shoulder in back area	150a	
• In collar or shoulder area	151a	
• Between lapel and sleeve seam	152a	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
XVIII. ARMHOLE OR SHOULDER - Continued		
Puckering on front or back of coats around armhole from back seam to forearm seam	153a	
Stretched, affecting appearance	154a	
Crooked seam; armhole not completely tacked; sleeve head pad not complexly tacked; or sleeve head pad misplaced, not serving intended purpose	155a	
XIX. SLEEVE		
Break or twist on sleeve, or top sleeve head too short	156a	
Sleeve fullness misplaced or concentrated in one area	157a	
Sleeve tight, i.e., front or back part of sleeve not having roll effect at armhole	158a	
Sleeve too far front or back, i.e., front edge of sleeve away from center of lower flap button or center of pocket:	159a	
Front creased edge of sleeve more than 2 1/2-inches or less than 1-inch behind	160a	
Setting and hag:		
Center of lower flap button or forward of button (Marine Corps coats only)	161a	
More than 2-inches 6/	162a	
More than 1-inch up to 2-inches, inclusive 6/	163a	
Construction of sleeve:		
Wigan twisted, tight, or pleated, causing ridge or puckering on outside of sleeve	164a	
Bottom edge of wigan not extending to bottom edge of sleeve by more than 1/8-inch, or tacking on bottom turn up to wigan omitted or insecure		278
Sleeve lining twisted, tight, or short causing fullness or twist on outside of sleeve		279
Sleeve braid:		
Edge of braid not positioned as specified, ends of braid finished at forearm seam, or ends of braid staggered more than 1/8-inch at joining seam	165a	
Stitched to sleeve tightly causing puckers; or stitched loosely causing puckers or pleat on braid	166a	
Sleeve cuffs:		
Hight of cuffs at front and back edges:	167a	
More than 3 5/8-inches or less than 3 1/8-inches at front	168a	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XIX. SLEEVE - CONTINUED**		
• More than 3 1/2-inches or less than 3-inches at back	169a	
• Height of cuffs at point on top sleeve more than • 6 1/4-inches or less than 5 3/4-inches	170a	
• Top edge on top sleeve part poorly shaped, affecting appearance	171a	
• The point of cuff not centered between lower back arm and forearm creased edges of sleeves by more than 3/16-inch	172a	
• Cuffs not uniform in size or shape with corresponding points by more than 1/4-inch	173a	
• **XX. FITTING**		
• Fitting of body and yoke lining: tight, short, or twisted causing fullness or twist on outside of coats	174a	
• Fitting of front interlining: tight or short, causing fullness on outside of coats	175a	
• Top full, causing coats front to have a wavy appearance or not lie smoothly	176a	
• **XXI. FRONT AND BOTTOM EDGE**		
• Front rolling outward below bottom button	177a	
• Front edge stretched, puckered or folded more than 1/8-inch on front or bottom edge, front edge irregular, or bottom corner of left front misshapen or distorted	178a	
• Left front below bottom button swings to right or left of the perpendicular by more than 1/2-inch		280
• **XXII. VENT OPENING**		
• Left vent edge stretched, causing vent to spread open	179a	
• Left vent edge crooked or irregular; or right vent lining tight, short, or twisted, causing fullness on outside of right vent	180a	
• Left vent 1/4-inch or more longer or shorter than right vent, or bottom turnup exposed or visible on left front edge		281
• Diagonal row of stitching across top of vent opening omitted		282
• Vent not topstitched as specified (Marine Corps coats only)		283

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XXIII. SIDE SEAM OR CENTER BACK SEAM**		
• Side seam or center back seam puckered	181a	
• Side seam or center back seam full	182a	
• Side seam or center back seam twisted (i.e., having a diagonal twist on front or back of coats)	183a	
• **XXIV. BELT LOOP**		
• Any end not securely stitched	184a	
• Loop set at an angle (more than 3/16 off perpendicular)	185a	
• Length or width not as specified		284
• Bottom folded edge of loop more than 1/4-inch above top edge of lower edge		285
• Not positioned as specified		286
• Under loop on left side omitted	186a	
• Length of under loop not as specified		287
• **XXV. BELT**		
• Interlining omitted	187a	
• Pointed end poorly shaped, affecting appearance		288
• Square end of belt not overedged		289
• Lining or interlining short, full, or twisted, causing fullness or twists on outer side of belt, affecting appearance		290
• Width of belt not as specified		291
• Irregular in width by 1/8-inch or more, affecting appearance		292
• Belt keeper:	188a	
• Omitted	189a	
• Length of belt keeper not as specified when measured from bartack to folded end	190a	
• Finished width not as specified		293
• Belt fastener:		
• Omitted	191a	
• Finished width not as specified		294
• Finished length not as specified		295
• Fastener not securely bartacked		296
• Buttonhole not stitched through double thickness of fastener		297

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• Fastener button:		
• Stitched through outer cloth		298
• Misplaced, causing a noticeable bulge or twist on belt, affecting appearance	192a	
• Purling of buttonhole on reverse side		299
• Ends of buttonhole not securely tacked:		
• Tacking on one end of buttonhole omitted or insecure		200a
• Tacking on both ends of buttonhole omitted or insecure	193a	
• Center of buttonhole to end of belt:		
• Less than 7/8-inch but not less than 3/4-inch or more than 1 1/8-inches		201a
• Less than 3/4-inch	194a	
• Office-center by more than 1/4-inch	195a	
• Purling of buttonhole finished underside of belt		202a
• Button on overedged end of belt (position):	196a	
• Less than 3 1/2-inches or more than 3 3/4-inches from the overedged end		203a
• Button not stitched through outer cloth	197a	
• Misplaced, causing turnback to be exposed beyond edge of let.		204a
• **XXVI. WAIST SEAM**		
• Not pressed open	198a	
• Excessively stretched, affecting appearance	199a	
• Staggered more than 1/4-inch when fronts are buttoned		205a
• **XXVII. WAIST DART**		
• Seam not pressed open	100b	
• **XXVIII. BREAST POCKET (TACKING)**		
• One or both corners of stay piece of breast pockets not tacked or not securely tacked to the interlining		206a
• **XXIX. FRONT WAIST DART (Construction and tacking)**		
• Waist dart seam not pressed as specified		207a
• Tacking of waist dart seam to interlining omitted or insecure		208a

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XXX. LOWER POCKET (Tacking)**		
• Top front corner or top edge of stay piece of lower pocket not tacked or not securely tacked to interlining		209a
• **XXXI. HANGER**		
• End not secure or length not as specified		210a
• **XXXII. FRONT FACING**		
• Short, tight or twisted, causing fullness or twist on fronts	201b	
• Exposed beyond edge of left front by more than • 1/16-inch		211a
• Tacking catching through pocket or forepart		212a
• Tacking on back edge to interlining insecure or incomplete for a distance of more than 2 1/2-inchs below shoulder seam, more than 2-inches above pocket opening, or more than 2-inches above bottom of coat; or felling at bottom corner of facings omitted or insecure		213a
• **XXXIII. INSIDE POCKET**		
• Opening not extending into facing or extending into armhole		214a
• Tacking along front edge of twill cloth pocket through facing and interlining (hand):		215a
• Omitted or insecure		216a
• Extending for a distance of less than 5-inches		217a
• Stay piece not extending to armhole seam, stay piece not stitched to lining, pocket opening badly gapped, width of opening or depth of pocket not as specified.		218a
• Tacking on back upper corner t interlining omitted or insecure		219a
• **XXXIV. LABEL**		
• Missing incorrect or illegible:		220a
• Size, label, instruction or combination labels		221a
• Identification label		222a
• Not attached as specified, misplaced, or stitching through the printing		223a

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XXXV. CARBOARD INSTRUCTION FOLDER**		
• Missing, incorrect, or illegible		224a
• **XXXVI. SIZE TICKET**		
• Missing, incorrect, or illegible		225a
• Not securely tacked to right front sleeve		226a
• **XXXVII. BACK YOKE**		
• Width of center pleat less than specified, center pleat omitted, or width of bottom hem not as specified	102b	
• Felling at lower edge of yoke lining to side seam outlet omitted or insecurely felled one or both sides	103b	
• **XXXVIII. FRONT BODY LINING**		
• Pleat omitted at shoulder, underarm dart omitted		227a
• Lining exposed below bottom edge of coat		228a
• Felling on bottom corners of lining and vent omitted or insecure		229a
• Pleat on center back lining omitted	104b	
• Hand/machine felling stitch caught through fold bottom pleat for 1/4-inch or more restricting bellow of pleat		230a
• **XXXIX. RIGHT VENT LINING**		
• Top edge not completely covering edge of center back seam outlet		231a
• Diagonal stitching across top of vent not full width of left back seam allowance		232a
• **XL. LINING SIDE OF ARMHOLE**		
• Backstitching at armpit of armhole, from forearm seam of sleeve to side seam omitted (hand sewing only)		233a
• **XLI. BINDING ON COATS (When Applicable)**		
• Not caught on fabric, causing binding to pull away from fabric easily		234a
• Binding tight, causing seam to curl and not lie flat	105b	
• Back folded edge of body lining not covering end of binding		235a
• **XLII. BOTTOM HEM AND TURNUP**		
• Hem and back parts twisted or irregular in width by 1/4-inch or more		236a
• Tacking on turnup of front to front omitted or insecure		237a

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Major	Minor
• **XLIII. LEFT FRONT FLY**		
• Omitted	106b	
• Raised stitching along front edge omitted	107b	
• Width of fly stitching from open edge less than • 2-inches or more than 2 3/4-inches		238a
• **XLIV. SWEAT SHIELD**		
• Placed so that front edge covers inside pocket opening 1/4-inch or more, or 1/2-inch or mor back of forearm seam of sleeve lining		239a
• Top edge not securely caught in armhole tacking or stitching		240a
• Tracking on lower edge omitted or insecure		241a
• Puckered, pleated, or twisted		242a
• Constructed of other than required material		243a
• Top or bottom raw edge of binding on shield (when applicable) not turned under and caught in stitching		244a
• Binding (if applicable) not securely stitched to fabric	108b	
• **XLV. FUSING**		
• Delamination	109b	
• Partial or complete delaminating on any fused component	110b	
• Bubbling on any fused component	111b	
• Any resin transfer to coats	112b	
• On any fused component	113b	
• Non-fused component	114b	

1/ Defects I though X are general defects. Defects XI through XXVII should be inspected for with the coat completely buttoned and buckled on a model form. Defects XXVIII through XLV should be inspected with the coats spread out on a table.

2/ For knitted fabric imperfection definitions, see MIL-STD-1491.

3/ The following focal points will be measured in the examination for this condition:

1. **Flap**: Top corner of flap nearest front edge of coats and front edge of flap just before the curved corner.
2. **Patch pocket**: Bottom of straight edge nearest front edge of coats.
3. **Welt pocket**: Top corner of pocket nearest front edge of coats.

4/ The following focal points are applicable only to Marine Corps coats:

1. Front edge of breast pocket not in vertical alignment with the front edge of the lower flap.
2. Upper front corner of lower patch pocket not set back 1/8-inch and the lower corner of the pocket not set back 3/8-inch from the above vertical alignment.

5/ Measure from straight front edge of coats to front edge of pocket at top (at the top front buttonhole or button position), and also at bottom pocket. Any difference between measurements is the amount pocket is not parallel with front edge.

6/ Excluding Marine Corps coats.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

3.7 Puckering. Refers to the gathering of a seam/stitches during sewing and after sewing causing unacceptable seam appearance when compared to the AATCC Photographic Seam Smoothness Scales - 68373 (see 2.3). Examine seams suspected of being puckered as specified in 4.3. Score as a puckered seam, those major portions of the suspected seam that has a rating of less than "3" for single or double needle seams.

3.8 Defective buttons. A button will be considered defective when it is broken or cracked, has sharp, rough, cracked or split edges; has scratches or dents, blemishes, or foreign matter embedded; or is badly or unevenly shaded. Additional button defects may be found in the defect Table I included in this document or in applicable button specifications.

3.9 Quality assurance terms and procedures. Definitions of quality assurance terms and procedures, where applicable, will be in accordance with ASQ/ANSI Z1.4 (see 2.3)

3.10 Raw edge. Raw edge is defined as any edge not finished as specified including any protruding edge on the outside of the coat.

3.11 Stitches, seam and defects. Unless otherwise specified, seams will be as defined in ASTM D6193. Open seam defects will be defined in 3.11.1.

3.11.1 Open seam. A seam is considered open when one (1) or more stitches joining a seam are broken or runoff, or when two (2) or more continuous skipped stitches occur. Double stitched seams are considered open when one or both rows of stitching are open.

4. GENERAL REQUIREMENTS

4.1 General. This standard contains provisions and terminology for end-item inspection, examination, and dimensional examination for the coats. If there are any inconsistencies between the requirements of the appropriate end-item specification and the provisions of this standard, the end-item specification shall govern.

4.2 Coverage. A standard shall be prepared to describe essential technical requirements for engineering or technical criteria, methods, processes, or practices. To the greatest extent possible, standards shall be written so that commercial practices and processes may be used to meet the requirement, and requirements should be stated in terms of desired outcomes as opposed to detailed procedures.

4.3 Normal viewing conditions. Normal viewing conditions for the inspection of coats, are 3-feet from the surface being examined. Unless otherwise specified, the coats shall be examined while lying flat on a suitable table using the following illumination criteria. The overhead direct lighting source shall be parallel to the viewing surface so as to illuminate with direct perpendicular impinging light rays. The surface illumination level shall be a minimum of 1075 lux (100-foot candles). The lights shall be cool white preheat rapid start fluorescent lamps with white reflectors and without baffles or glass.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Sampling and acceptance criteria. The sample unit shall be one (1) finished coats, men's and lot size shall be expressed in the number of sample units. The sample size and Acceptance Quality Limit (AQL) shall be as specified in the contract or purchase order. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 – Sampling Procedures and tables for Inspection by Attributes Sampling shall be represent all types, classes, and styles included in the production lot, and shall be include samples from the beginning, middle and end of production of the end-item specification.

5.2 End-item dimensional examination. The finished coats shall be measured for conformance to the finished measurements as stated in the end item specification. The sample size for end item dimensional examination shall be as specified in the contract or purchase order.

5.3 End-item visual examination. The coats shall be examined for the defects stated in Table I of this document. Defects are assigned as "Major" or "Minor". The sample unit shall be one (1) finished men's coats.

5.4 Shade variation examination. During the examination, each coat in the sample shall be examined for shade variation. Any coats in the sample containing uneven shade or shade variation, within a part or between parts, shall be cause for rejection of entire lot represented by the sample.

5.5 Dimensional examination. During the examination, each coat in the sample shall be examined for compliance with the dimensions specified in the associated specification.

5.6 Shade match and appearance examination. The shade match and appearance examination shall be conducted as specified in the end-item specification, contract or purchase order.

5.7 Inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 – Sampling Procedures and Tables for Inspection by Attributes . The inspection level and AQL shall be as specified in the contract or purchase order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory).

6.1 Intended use. This standard is intended to provide a standardized procedure for evaluating quality of men's dress coats for procured by the department of defense…

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this standard
b. Type of material defects allowed.
c. The specific issue of individual documents referenced (see 2.3)
d. Acceptance Quality Level (AQL) (see 5.1)

6.3 Subject term (key word) listing.

Examination
Fabric defect
Inspection

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – GL
Navy – NU
Air Force – 11

Preparing activity:
DLA - CT

(Project: 8405- 2026-008)

Review activities:
Army- MD
Navy – MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST at https://ASSIST.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.