MIL-STD-1493(GL)
11 May 1973

MILITARY STANDARD

CONTRACTUAL SERVICE REQUIREMENTS FOR AUTOMATIC DISHWASHING MACHINE ACCESSORY EQUIPMENT AND SUPPLIES

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY

U. S. ARMY NATICK LABORATORIES, (GL) NATICK, MASS. 01760

Contractual service requirements for automatic dishwashing machine accessory equipment and supplies

1. This Military Standard was approved 11 May 1973 for use by the Department of the Army.

2. Recommendations, corrections, additions or deletions should be addressed to Commander, U. S. Army Natick Laboratories, Attn: AMXRET-EQS Natick, Massachusetts 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

FOREWORD

This Military Standard has been developed to provide information, guidance, and requirements needed in procuring commercially supplied dishwashing compounds, the installation and use of accessory dispensing equipment, and requirements necessary for contractual service from accessory equipment and dishwashing compound manufacturers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

CONTENTS

		PAGE
1.	SCOPE	1
1.1	Purpose	1
1.2	Classification	1
1.2.1	Types	1
1.2.2	Classes	1
1.2.3	Styles	2
2.	REFERENCED DOCUMENTS	2
2.1	STANDARDS	2
3.	DEFINITIONS	2
3.1	Spray type dishwashing machine	2
3.1.1	Single tank, rack type, dishwashing machine	2
3.1.2	Multiple tank rack type dishwashing machine	3
3.1.3	Multiple tank, rackless (flight type) dishwashing machine	3
3.2	Effectively wash	3
3.3	Sanitize	3
3.4	Clean	3
3.5	Dishwashing compound (detergent)	3
3.6	Dishwashing compound (detergent) dispenser	3
3.7	Rinse additive	3
3.8	Rack	4
3.9	Rinse additive injector	4
3.10	Toxic	4
3.11	Washing	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

CONTENTS (Continued)

		PAGE
4.	GENERAL REQUIREMENTS	4
4.1	Biodegradability	4
4.2	Workmanship	4
4.3	Safety	4
5.	DETAIL REQUIREMENTS	4
5.1	Machine dishwashing compounds	4
5.1.1	Description	4
5.1.2	Use	5
5.1.3	Labeling precautions	5
5.1.3.1	Liquid machine dishwashing compounds	5
5.1.3.2	Powdered machine dishwashing compounds	5
5.1.3.3	Storage	5
5.2	Rinse additive	6
5.2.1	Description	6
5.2.2	Use	6
5.3	Supplies	6
5.3.1	Dishwashing compound	6
5.3.2	Rinse additive	6
5.3.3	Contractor furnished	6
5.4	Services	6
5.4.1	Initial services	6
5.4.1.1	Installation of dispensers	7
5.4.1.2	Installation of hour meter devices	7

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

CONTENTS (Continued)

		PAGE
5.4.1.3	Test kit or apparatus	7
5.4.2	Periodic services	7
5.4.2.1	Service calls	7
5.4.2.2	Descaling of equipment	8
5.4.3	Reports	8
5.5	Instruction	9
5.6	Emergency calls	9

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Purpose. The purpose of this standard is to outline in detail the items, procedures and required frequency of contractor inspection and maintenance visits necessary to accomplish satisfactory diswashing and sanitizing operations, based upon the average operating conditions and duration of dishwashing activity within a mess area. It is to be referenced in all machine dishwashing service or supply contracts initiated by Army Military installations. The specified frequencies of contractor servicing and time periods of actual machine operation can be adjusted or regulated, as required, to meet the needs of each installation because of fluctuations in troop strength, types of meals served and the size and type of permanent machine dishwashing equipment present in messes.

1.2 Classification. This standard covers 2 types, 3 classes and 2 styles of dishwashing supplies and accessory equipment for use under contractural service.

1.2.1 Types.

Type I-A liquid type system dishwashing compound, with contractor's standard supplies commercially procured on an "as needed" basis by post procurement personnel with contractor supplied, installed, and maintained accessory dispensing equipment.

Type I-B liquid type system dishwashing compound, accessory dispensing equipment supplied, installed, and maintained by contractor, with contractor's standard supplies furnished by the contractor on an hourly operational rate basis.

Type II-A powdered type system dishwashing compound, contractor's standard supplies commercially procured on an "as needed" basis by post procurement personnel, with contractor supplied, installed, and maintained accessory dispensing equipment.

Type II-B powdered type system dishwashing compound, accessory dispensing equipment supplied, installed, and maintained by contractor, with contractor's standard supplies furnished by contractor on an hourly operational rate basis.

1.2.2 Classes.

Class 1 - For single tank rack type, dishwashing machines
Class 2 - For multiple tank, rack type dishwashing machines
Class 3 - For multiple tank, rackless (flight type) dishwashing machines

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

1.2.3 Styles.

Style A - Machine dishwashing compound with dishwashing compound dispenser and rinse additive with injector; Combination System.

Style B - Machine dishwashing compound with dishwashing compound dispenser system only, no rinse additive used.

2. REFERENCED DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or requests for proposal, form a part of this standard to the extent specified herein.

STANDARD

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

HANDBOOK

MIL-HDBK-740 - Dishwashing Operations

(Copies of specifications, standard, drawings, and publications required by suppliers in connection with specific procurmennt functions should br obtained from the procuring activity or as directed by the contracting officer.)

3. DEFINITIONS

3.1 Spray type dishwashing machine. The term "spray type dishwashing machine" shall mean a machine designed, constructed and intended for use in a food service area and which effectively washes, cleans and sanitizes dishes, tableware, trays and glassware by means of a sprayed wash and sprayed sanitizing rinse.

3.1.1 Single tank, rack type, dishwashing machine. A single tank, rack type dishwashing machine consists of a tank for wash water at the temperature required (150°F) and containing a detergent, followed by a final rinse of fresh water at the temperature required (180°-195°F). An electric motor-driven pump circulates the washwater in the volume required through spray pipes or nozzle above and below the dishes. The final rinse introduces fresh water or fresh water and rinse additive, as required, in the volume and at the temperature required through spray pipes or nozzles above and below the dishes. The dishes are washed and sanitized by a series of sprays by a timed cycle. Such machines may include a prewashing section ahead of the washing section.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

3.1.2 Multiple tank rack type dishwashing machine. A multiple tank, rack type dishwashing machine consists of one or more tanks for wash water at the temperature required (150°F) and containing a detergent, one or more tanks for pumped rinse water at the temperature required (160°F) followed by a final rinse of fresh water or fresh water with rinse additive at the temperature required (180-195°F).

Electric motor-driven pumps circulate the wash and pumped rinse water in the volumes required through spray pipes or nozzles above and below the dishes. The final rinse introduces fresh water in the volume and at the temperature required through spray pipes or nozzles above and below the dishes. The dishes are carried through the series of sprays by a timed conveyor moving the rack through the machine. Such machines may include a prewashing section ahead of the washing section.

3.1.3 Multiple tank, rackless (flight type) dishwashing machine. A multiple tank, rackless type dishwashing machine is similar to that described in 3.1.2, however, dishes and dinnerware may be placed directly onto a pegged conveyor belt for carrying through the machine.

3.2 Effectively wash. The term "effectively wash" means the removal of all physical soil from the surfaces of dishes, tableware, and glassware by subjecting all surfaces of soiled articles to sprays of hot water and cleaning compound solutions.

3.3 Sanitize. The term "sanitize" means the effective bactericidal treatment of clean surfaces of equipment and utensils by a process which has been proven effective in destroying microorganisms, including pathogens.

3.4 Clean. The term "clean" means the removal of residues of food, dirt, dust, foreign matter or other soiling ingredients or materials.

3.5 Dishwashing compound (detergent). The term " dishwashing compound" or "detergent" means a cleaning agent suitable for use in spray type dishwashing machines, or in the event of the machines non-operability, a cleaning agent for use while hand washing and which, when used effectively, aids in the removal of soil from dishes, tableware, and glassware and trays. The cleaning compound or detergent may be in either a liquid or powdered form.

3.6 Dishwashing compound (detergent) dispenser. A dishwashing compound (detergent) dispenser is a device capable of adding dishwashing compounds to the wash water tank of spray type dishwashing machines so that a desired pre-established dishwashing compound concentration can be maintained.

3.7 Rinse additive. A rinse additive, commonly known as a drying agent or wetting agent, is a chemical additive which when added in a pre-determined amount to the final rinse cycle of a spray type dishwashing machine will accelerate drying and aid in the removal of water spotting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

3.8 Rack. The word "rack" shall mean a device that is not attached to the dishwashing machine, intended to hold dishes, glassware, tableware, or trays in proper position for washing, cleaning, and sanitizing in a particular type of spray type dishwashing machine.

3.9 Rinse additive injector. The rinse additive injector is a device which automatically injects or otherwise adds a rinse additive to the final rinse cycle of a spray type dishwashing machine.

3.10 Toxic. The work toxic shall refer to the adverse physiological effect to man that may be anticipated under use conditions.

3.11 Washing. Washing means subjecting all surfaces of dishes, tableware, glassware, and trays to sprays of hot water and dishwashing compound for such times and at such temperatures, as are required by MIL-HDBK-740.

4. GENERAL REQUIREMENTS

4.1 Biodegradability. The supplier shall certify by a certificate of compliance that the biodegradability of his supplies meets the minimum requirement of 90%. The certificate shall be accompanied by actual test data (field or laboratory) including the detail test procedure utilized in making the biodegradability determination.

4.2 Workmanship. All workmanship relative to installation, repair, maintenance and service shall be in accordance with the best practices in the warewashing industry. It is intended that the services and equipment shall include all supplies, dispenser components or accessory equipment processes necessary for washing and final rinsing (except hot water), even though every part is not specifically mentioned. All work shall be in conformance to post sanitary regulations and equipment installation and its correctness shall be approved by the Facilities Engineer and Post Medical Officer prior to actual use of the dispensing equipment.

4.3 Safety. All toxic or hazardous compounds shall be noted as such and contain the caution paragraphs of section 5, and shall be labeled in accordance with MIL-STD-129.

5. DETAIL REQUIREMENTS

5.1 Machine dishwashing compounds.

5.1.1 Description. Machine dishwashing compounds shall be either liquid or powdered compounds and shall be the standard product manufactured by the supplier. Liquid machine dishwashing compounds may be either a single part compound or combination detergent-water softener two part system. The machine dishwashing compou shall be appropriate and suitable for use with the water hardness encountered in the mess area where it is to be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

5.1.2 Use. The machine dishwashing compounds are intended for use in washing dishes, glassware, tableware, and trays under whatever water hardness conditions exist in the area where it is used.

5.1.3 Labeling precautions.

5.1.3.1 Liquid machine dishwashing compounds. All individual containers of liquid machine dishwashing compounds shall display the following information in clear, legible permanent print:

WARNING! HARMFUL IF SWALLOWED AND CAUSES IRRITATION.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING.
WASH THOROUGHLY AFTER HANDLING.
CAUTION:- ALKALINE CAUSTIC-LIQUID-VENTED CONTAINER
DO NOT DROP
REMOVE LEAKING PACKAGES
WASH CAUSTIC ALKALINE LIQUID OFF WITH WATER
DO NOT LOAD WITH EXPLOSIVES OR NEAR ARTICLES BEARING YELLOW WARNING LABELS
DO NOT TAKE INTERNALLY
DO NOT MIX WITH ACID OR OTHER CHEMICALS
IN CASE OF SKIN CONTACT FLUSH FREELY WITH WATER
FOR EYE CONTACT, CONTINUE FLUSHING FOR AT LEAST 15 MINUTES AND GET IMMEDIATE MEDICAL ATTENTION
KEEP FROM FREEZING - DO NOT ATTACH TO RINSE INJECTOR PORTION OF DISPENSER
STORE ABOVE 45°F

5.1.3.2 Powdered machine dishwashing compounds. All individual containers of powdered machine dishwashing compound shall contain the following information in clear, legible permanent print:

WARNING! INJURIOUS TO SKIN AND EYES
HARMFUL IF INHALED OR SWALLOWED
CAUTION: - ALKALINE POWDER
AVOID CONTACT WITH SKIN AND EYES
AVOID BREATHING DUST FROM POWDER
IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN OR EYES WITH PLENTY OF WATER
FOR EYE CONTACT, CONTINUE FLUSHING WITH WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IMMEDIATELY
DO NOT MIX WITH ACID OR OTHER CHEMICALS
USE ONLY AT WATER INLET SUPPLY FOR DISHWASHING COMPOUND DISPENSER
DO NOT USE IN THE RINSE INJECTOR PORTION OF DISPENSING EQUIPMENT
NOT RECOMMENDED AS A DIP DESTAINER FOR DINNERWARE
NOT RECOMMENDED FOR CLEANING OR DESTAINING COFFEE URNS.

5.1.3.3 Storage. Liquid machine dishwashing compounds shall be stored in a cool dry place, above 45°F and kept from freezing. Powdered machine dishwashing compounds shall be stored in a cool, dry place.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

5.2 Rinse additive.

5.2.1 Description. Rinse additives are distinctively colored, liquid wetting agents combined with or without a defoamer, as necessary to prevent foaming in actual use at 180° to 195°F in the final rinse spray cycle of spray type dishwashing machines.

5.2.2 Use. Liquid rinse additives are intended for use in the final rinse of dishwashing machines to aid in the elimination of water spotting and filming on tableware, dishes, glassware and trays and decrease drying time.

5.3 Supplies.

5.3.1 Dishwashing compound. When supplies are furnished on an hourly basis of charge, the dishwashing compound supplied by the contractor or supplier shall be a standard product manufactured by the contractor or supplier, suitable for use under the water hardness, workload and any other limiting condition present in the mess area where the supplies are to be used to provide to most satisfactory results obtainable. When supplies are ordered on an "as needed" basis of procurement by the procuring activity, the procuring activity shall be able to choose any standard product manufactured by the commercial supplier for use in their messes. This does not necessarily mean the same product is to be used postwide, assuming not all messes may choose to use the liquid or the powdered medium of dishwashing supplies.

5.3.2 Rinse additive. When supplies are furnished on an hourly basis of charge, the rinse additive supplied by the contractor or supplier shall be a standard product manufactured by the contractor or supplier, suitable for use under any water hardness encountered in the mess area where the rinse additive is to be used. When supplies are ordered on an "as needed" basis of procurement by the procuring activity, the procuring activity shall be able to choose any standard product manufactured by the commercial supplier or contractor for use in its messes.

5.3.3 When the contract calls for contractor furnished supplies on an hourly operational rate basis (see 1.2.1, type I-B and II-B), the contractor shall insure that a minimum 30 day supply of chemicals (dishwashing compound and rinse additive, if required, see 1.2.3) is on hand at the Property Section Warehouse. Due to possible lack of storage space, the products on hand shall not exceed a maximum of 90 days supply inventory.

5.4 Services. Unless specifically stated otherwise in the invitation for bid or request for proposal, the following services and procedures shall apply.

5.4.1 Initial services.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

5.4.1.1 Installation of dispensers. The contractor, upon notification of acceptance of his bid, shall provide, install with minimum modification of the dishwasher, and maintain automatic dispensing control systems for dishwashing compounds and rinse additives, as required in accordance with the requirements specified in 1.2.1, 1.2.2 and 1.2.3. The electronic equipment shall remain the property of the contractor. The contractor will, upon termination of the contract, remove all contractor supplied components, effectively plug all holes put into the dishwasher during installation and, if contracted on an hourly basis of charge, remove all remaining chemical products (see 1.2.1, type I-B and type II-B). The equipment shall be that best suited for use on each particular dishwashing machine throughout the installation.

5.4.1.2 Installation of hour meter devices. When the contract calls for supplies and services to be furnished the Government on an hourly basis, an hour meter device shall be installed on each dishwashing machine so contracted, to record the actual time the dishwashing machine is in operation. The meter shall be supplied by the Government and installed by the contractor.

5.4.1.3 Test kit or apparatus. The contractor shall furnish a wash water testing device or test kit to enable the Government to insure that the proper dishwashing compound to water ratio is being maintained.

5.4.2 Periodic services.

5.4.2.1 Service calls. The contractor shall provide for regular service calls to be made by technically trained service personnel having practical experience in servicing dishwashing machines. These men shall be qualified to train and instruct dishwashing machine operators in the proper use of dishwashing and dispensing equipment and dishwashing supplies by use of slides, films and charts at the request of the activity Post Food Advisor, should he desire this service (see 5.5).

At least one inspection and maintenance call to the dishwashing area of every mess containing dishwashing equipment covered under the contract shall be made by the contractor or his authorized representatives, at least once a month during the entire period of the contract.

At this time all necessary repairs and cleaning of accessory equipment shall be accomplished. In addition, the following procedures shall be completed:

(a) Inspect and maintain all dispensing accessory equipment.
(b) Check all dishwashing machines in operation at the activity, including the functioning of mechanical parts, gauges, valves, cleanliness of wash arms and rinse nozzles and make adjustments where necessary.
(c) Check wash water concentrations on each dishwashing machine when the machine is clean, not being used, and when no normal food soil is present in the wash tank.
(d) Check the temperatures and pressures for wash, power and final rinse at each regular service call.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

(e) Instruct mess attendant on duty at the time of the service call in the proper use of the equipment and supplies if he sees the personnel on duty are not using the equipment properly or if they request such information relative to the equipment or supplies.

(f) Check the time, in seconds, for wash and rinse cycles.

(g) Check the bleeder tube and overflow tube for correct operation or seating as applicable and correct if operating improperly.

(h) Inspect wash arms and rinse sprays for efficient operation and, if clogged, clean and adjust them.

(i) Check rotating wash and rinse arms for proper pitch and spray patterns and adjust or balance as necessary. Check if gaskets or seals are leaking at rotation points.

(j) Check pumps, doors, draw valves and plumbing for leaks, and the motors, shafts, and universal joints for excessive heat buildup, wear, noise, or vibration. Clean air intake filter if necessary and remove and clean the strainer if necessary.

(k) Inspect all fill valves and steam valves for leaks and, if detected, install new valve disks if possible and note major valve trouble on reports.

(l) All repairs shall be made as necessary to assure proper uninterrupted operation and functioning of equipment. Inspection and maintenance shall be accomplished at times other than regualr meal hours.

5.4.2.2 Descaling of equipment. At each periodic visit, the contractor or his authorized representative shall descale (delime) the dishwasher if scale is visibly detectable on the wash or rinse spray arms or final rinse spray arm of the dishwasher being serviced. The scale removing compound used shall be furnished by the using agency, and shall conform to Scale Removing Compound; FSN 6850-637-6142.

5.4.3 Reports. A written report provided by the contractor, in triplicate, at each time of servicing for each individual dishwasher being serviced shall be submitted to the using activity, one copy of which will be forwarded to each of the following individuals: The Post Food Advisor, the installation Contracting Officer and the Mess Supervisor of the area being serviced. The report shall contain the following information:

(1) Name of the activity or installation, name of the company or unit being serviced and the building number.

(2) Date of call.

(3) Make, model and manufacturer of dishwashing machine.

(4) Analysis of results of trays, glassware, tableware and dinnerware.

(5) Type dispenser and/or injector being used and note if it is working properly.

(6) Type or name of detergent and rinse additive being used.

(7) Percent concentration of the wash solution and rinse additive concentrati

(8) Indicate the proper concentration, and if it is not being attained, expla why it is not correct.

(9) Wash water temperature.

(10) Rinse water temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

(11) Final rinse water temperature.
(12) General mechanical condition of the dishwasher.
(13) Repairs needed to the machine, injector or dispenser. State what they are and corrective measures taken.
(14) Discuss pertinent problems existing in the dishwasher area.
(15) Contractor's or his authorized representatives signature with position or title.
(16) Authorized signature of the Activity. (Contracting Officer or his authorized representative.)

5.5 Instruction. The contractor shall supply the Post Food Advisor the following information, at the request of the Post Food Advisor, at least one time during the period of the contract and not later than 60 days after the award of the contract unless specifically stated otherwise in the Invitation for Bid or Request for Proposal.

(1) Operating charts for dishwashing machine operators regarding care and use of the dishwashing machine.
(2) A slide training program of not less than 50 slides, on proper warewashing procedures, with a script for each slide, both directly related to the installation under contract. This program will be used to train dishwashing machine operators and mess personnel, as needed in correct warewashing methods and procedures.

5.6 Emergency calls. Unless specifically stated otherwise in the Invitation for Bid or Request for Proposal, emergency calls shall be unlimited. Services of an emergency nature shall commence within 4 hours after receipt of call by the contractor or his authorized representative. Emergency calls will be requested by the Contracting Officer or his authorized representative only.

The contractor shall insure that the proper chemical to water ratio is maintained and that the end product in the warewashing operation conforms to the requirements of MIL-HDBK-740.

Custodians:

Army - GL

Preparing activity:

Army - GL

Project No. 7930-A288

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY NATICK LABORATORIES
NATICK, MASS. 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AMXRET-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S. MAIL

Commander
US Army Natick Laboratories
ATTN: AMXRET-EQS
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-STD-1493(GL) CONTRACTUAL SERVICE REQUIREMENTS FOR AUTOMATIC DISHWASHING MACHINE ACCESSORY EQUIPMENT AND SUPPLIES

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:31Z
Check the source to verify that this is the current version before use.