MIL-C-60943A (AR)
AMENDMENT 1
10 March 1982

MILITARY SPECIFICATION

CARTRIDGE, 40MM, HE, M384
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-60943A (MU), dated 9 March 1970, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 3

3.3, last line, after "position": Add the following:

"or presence of the setback pin flange seated against bottom surface of the rotor plate (Dwg. 8876197) counterbore".

3.6.1, line 2: Delete "790 ± 15" and substitute "795 ± 20".

PAGE 4

Add new paragraph 3.9 as follows:

"3.9 X-ray examination of ballistic samples. - Prior to forwarding the cartridges to the proving ground for ballistic testing, as specified in 4.3.3.13 and 4.3.3.14, they shall be subjected to x-ray examination when tested as specified in 4.4.16."

PAGE 6

4.3.1g: Delete in its entirety and substitute the following:

"g. Cartridges in less than full belt quantities shall be handled in the following manner:

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

(1) If remaining quantity exceeds 25 rounds, use rounds from next lot to complete belt.

(2) If remaining quantity is less than 25 rounds, include rounds in next lot produced.

(3) Packing box and data cards shall be annotated as to the mixture."

PAGE 9

4.3.2.8: Add Major defect 104 as follows:

"104. Support missing Visual 08004."

PAGE 11

4.3.3.4: After "assembly" add the following:

"beginning with the first group produced (a "group" is defined as a quantity consisting of four (4) hours production) and continuing until one-hundred (100) consecutive groups have been accepted under the criteria specified. Thereafter, ten (10) base plug and primer assemblies shall be randomly selected every four (4) hours from each automatic primer assembly machine."

PAGE 12

4.3.3.11, line 4: Delete "as M384 Cartridges" and substitute "to an M533 Fuze Test Vehicle (Dwg. 9206914)."

PAGE 13

4.3.3.13:

Line 4: Delete "three-hundred (300)" and substitute "five-hundred (500)."

Last sentence: Delete in its entirety and substitute the following:

"The sample cartridges shall be selected at random prior to linking and then linked with the same lot of links to which its respective end item lot has been assembled."

4.3.3.13.1a: Delete "Thirteen (13)" and substitute "Twenty-two (22)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

PAGE 14

4.3.3.13.1.1: Delete in its entirety.

4.3.3.14: Delete in its entirety and substitute the following:

"4.3.3.14 Functioning (See para. 3.6), Major defect, Regular Production, Code No. 22001. - After three (3) consecutive lots have met the criteria of 4.3.3.13, the Government inspector shall select three-hundred (300) cartridges from each lot and subjected to this test. The sample cartridges shall be selected at random prior to linking and then linked with the same lot of links to which its respective end item lot has been assembled."

4.3.3.14.1:

a: Delete "Seven (7)" and substitute "Twenty (20)".

h: Delete "300" and substitute "500".

PAGE 15

4.3.3.14.1.1:

Line 1: Delete "four (4) to six (6)" and substitute "thirteen (13) thru nineteen (19)".

Line 2: Delete "one-hundred (100)" and substitute "three-hundred (300)".

Line 4: Delete "nine (9)" and substitute "twenty-seven (27)".

4.3.3.16: Delete the first sentence and substitute the following:

"Two (2) full boxes (100 linked cartridges) shall be randomly selected from a completed linked lot and subjected to this test."

Add new paragraphs 4.3.3.17, 4.3.3.18 and 4.3.3.19 as follows:

"4.3.3.17 - Pot life of adhesive (See 6.11), (See Dwg. 9217500), Major defect, Code No. 25001. - Each batch of adhesive mixed for use in assembly of fuzes to bodies shall be subjected to this determination. If any batch fails to comply with the applicable requirements, it shall not be used for assembly of fuzes to bodies. Projectile assemblies which have been assembled with adhesive which exceeded the pot life requirement shall be disassembled, cleaned and new adhesive applied. The test shall be performed as specified in 4.4.14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.3.18 Disassembly torque of fuze (See Dwg. 8886398), Major defect, Code No. 26001. - One (1) cartridge shall be selected from each batch of adhesive and held for 24 hours, after which each of the selected cartridges shall be subjected to this test. If any cartridge fails to comply with the applicable requirement the lot shall be rejected. This test shall be performed as specified in 4.4.15 using equipment in accordance with 4.3.4.

4.3.3.19 X-ray examination of ballistic sample (See para. 3.9), Code No. 27001. - Prior to forwarding the cartridges to the proving ground for ballistic testing, as specified in 4.3.3.13 and 4.3.3.14, they shall be subjected to x-ray examination. The cartridges shall be x-rayed for critical and major defects. If any critical defect is found, it shall be noted and the samples forwarded to the proving ground. There shall be no replacement of samples. This test shall be performed as specified in 4.4.16 using equipment in accordance with 4.3.4."

PAGE 17

4.4.7: Add the following sentence:

"Side view shall show the flange of the setback pin seated against bottom surface of the rotor place (Dwg. 8876197) counterbore."

PAGE 18

Add new paragraphs 4.4.14, 4.4.15 and 4.4.16 as follows:

"4.4.14 Pot life of adhesive. - The time from preparation of the adhesive for use in assembly of fuzes to bodies, to its application shall be determined. Any method considered satisfactory to the Contracting Officer may be used in performing this determination. This is a non-destructive test. Adhesive so tested shall be returned to the lot.

4.4.15 Disassembly torque of fuze. - The projectile assembly shall be placed in a fixture as specified on the Equipment List and the torque specified on Dwg. 8886398 shall be applied. This is a destructive test, no cartridge so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.4.16 X-ray examination of ballistic samples. - The cartridge, prior to forwarding to the proving ground, shall be subjected to x-ray examination using the x-ray equipment specified on the Equipment List or any other method satisfactory to the Contracting Officer. This test is a non-destructive test. Parts so tested may be returned to the lot. This test shall be conducted in two planes. From the top of the fuze assembly down and from the side."

Add new paragraph 6.11 as follows:

"6.11 The period of time during which an adhesive after mixing with catalyst, solvent, or other compounding ingredients, remains suitable for use.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A280)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.