MILITARY SPECIFICATION

HOOD, CHEMICAL-BIOLOGICAL MASK: M6A2

This amendment forms a part of MIL-H-51291A(EA), dated 22 February 1977, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: After list of drawing and TDPL, add the following:

"PUBLICATIONS

Special Packaging Instructions

P5-35-86 - Hood, Chemical-Biological Mask, M6A2."

3.1.2.2: Delete in its entirety and substitute:

"3.1.2.2 Slide fastener low temperature operation. The force required to operate the dry slide fastener, after conditioning, shall not exceed 4.0 pounds when tested as specified in 4.4.4.6."

PAGE 3

3.4.2: Delete in its entirety and substitute the following:

"3.4.2 Luting compound. A luting compound shall be used on the seams of the hood. The luting compound shall be applied on the inside of the hood. The luting compound shall be a self-curing solvent neoprene rubber diisocyanate adhesive (see 6.3). When used in combination with the coated fabric, the luting compound shall meet the following requirements when tested as specified in 4.4.4.2.



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:56Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| Blocking of seams | Scale rating No. 3 |
| Resistance to low temperature | Pass test with no cracking, flaking, or separation from the fabric |
| Stiffness (centimetres) | |
| Initial | 10 max |
| *After heat aging | 12 max |
| Solids content | 20 min |

*The specimen shall show no cracking, flaking, or separation from the fabric."

PAGE 4

Add a new paragraph 3.10 as follows: "3.10 Circumference of inlet valve and lens openings. The inside circumference of the opening of inlet valve and lens shall conform to Drawing D5-35-86 when tested in accordance with 4.4.4.4."

PAGE 5

Change in 4.3.2 Examination and tests. From ". . . five hoods selected at random . . ." to ". . . ten hoods selected at random . . ."

4.4.3.3: Change "(b) Preparation of delivery" to "(b) Packaging inspection".

4.4.3.3(b): Add immediately following major category "102", the following:

"103 Intermediate package quantity not as specified
104 Intermediate container construction and closure incorrect
105 Marking missing, incorrect, or illegible"

PAGE 9

4.4.4.2.1, lines 4 and 5: Delete "after it has been treated with an approved preparation (see 6.4)." and substitute "(see 3.4.2)."

PAGE 10

4.4.4.3: Delete "6.5" and substitute "6.4".

4.4.4.4: Delete "The inside circumference of the openings shall be determined under these tensions and shall conform to Drawing D5-35-86."



Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:56Z
Check the source to verify that this is the current version before use.

PAGE 11

4.4.4.6: Delete in its entirety and substitute the following:

"4.4.4.6 Slide fastner low temperature operation. The slide fastener shall be conditioned at -54°C for four hours in the closed position and removed one at a time from the chamber for testing. The closed slide fastener shall be laid flat, without tension, on a horizontal surface with both ends fastened down. The slide fastener shall be tested within three minutes after removal from the conditioning chamber. The chain shall be opened and closed three times, by drawing the slider back and forth, at a 15 to 20 degree angle from the horizontal, by means of a calibrated spring scale attached to the slider pull. The opening and closing shall begin and end at least 1 inch from stops and tested over a 5-8 inch portion of the chain. The calibrated scale shall be accurate within 1/4 pound over the range of three to five pounds. A maximum load indicator shall be attached to the spring scale and the load indicated for each opening and closing shall be recorded."

Delete Section 5 in its entirety and substitute the following:

"5. PACKAGING

5.1 Packaging requirements shall be as specified on SPI P5-35-86."

6.1: Delete in its entirety and substitute the following:

"6.1 Indended use. The M6A2 hood is intended for use with the M17 series chemical-biological mask."

6.2: Delete line (b) entirely and substitue with "(b) Level of packing required (5.1)."

PAGE 12

6.4: Delete in its entirety.

6.5: Renumber to "6.4".

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A988



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:56Z
Check the source to verify that this is the currenversion before use.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:56Z
Check the source to verify that this is the current version before use.